



# Curved Conveyor

## SPECIFICATIONS

Overall length, width, height	7050 x 5850 x 1670mm
Min/Max stud length	3600 - 6000mm
Min/Max feed length	1710 - 3600mm
Working height	1670mm
Safe working load	1000kg
Machine mass	1400kg
Operational noise	50dB
Operating temperature	0 - 40°C
Electrical requirement	400V 8A 3Ph

\* Specifications shown reflect a typical configuration. Machine design, layout and features may vary depending on final configuration and customer requirements. Details will be confirmed at the time of order.

## OVERVIEW

The Curved Conveyor is used to transfer studs and minor sub-assemblies from the assembly point to the Wall Extruder or Raked Wall Extruder operator, ready for insertion into the wall frame. Given its design, the Curved Conveyor is an efficient use of space within your factory.

## FEATURES

- Curved Conveyor delivers pre-assembled components and studs from the component assembly station to the Wall Extruder or Raked Wall Extruder
- Conveyors mounted on sturdy steel bridge straddling the frame line conveyors, allowing continuous frame flow along the line
- Fitted with a robust bow chain for transport of timber

## OPTIONS

- Also available in sizes 4800mm and 6000mm with 3rd rail for handling pre-assembled components and studs over 3600mm

