



Rapid Stop

SPECIFICATIONS

Overall length, width, height	21.4 x 3.8 x 5.9ft
Min/Max feed lengths	0 - 20ft
Min/Max cut lengths	0 - 20ft
Working height	34.25in
Safe working load	400lb
Machine mass	550lb
Operational noise	50dB
Operating temperature	32 - 104°F
Electrical requirement	400V 10A 3Ph

* Specifications shown reflect a typical configuration. Machine design, layout and features may vary depending on final configuration and customer requirements. Details will be confirmed at the time of order.

OPTION WITH PLATE MARKER



OPTION WITH INKJET PRINTER



For more information, visit spida.com

OVERVIEW

The Rapid Stop is designed to provide an automated and accurate method of measuring material.

Save time and money with the Rapid Stop, dramatically reducing the time spent measuring lengths and eliminating the wastage associated with incorrect measuring.

FEATURES

- Ideal for lumber processors looking to automate the measuring of lengths
- Stop is accurate to within +/- 0.2"
- Easy operation of stop with 24" industrial touch screen
- Automated operation. Simply cut from the list on screen as generated from the detailing office
- Easily fitted to any Spida saw to automate the measuring function
- MDF table top
- UL Listed Industrial Control Panels



OPTIONS

- Customizable length options to suit your factory requirements
- Can be fitted to most saws
- Plastic table top
- Also available as a Roller Table
- Pneumatic and manual plate marker available - works with plastic table top only
- Inkjet printer available - works with plastic table top only



See more

