



# Stud Extruder

## SPECIFICATIONS

Overall length, width, height	27.25 x 7.2 x 6.3ft
Max stud length	12ft
Max sub assembly width	16in
Min Lumber dimension	2 x 4in
Max Lumber dimension	2 x 8in
Working height	36in
Machine mass	1300lb
Operational noise	90dB
Operating temperature	32 - 104°F
Electrical requirement	400V 16A 3Ph+Neutral
Air requirement	2.119CFM @ 116psi

\* Specifications shown reflect a typical configuration. Machine design, layout and features may vary depending on final configuration and customer requirements. Details will be confirmed at the time of order.

## OVERVIEW

The Stud Extruder is used for the assembly of C, L and U studs along with the nailing of fireblocks to studs. This machine has been designed with both accuracy and safety in mind.

## FEATURES

- Automatically nails C, L & U stud assemblies, double & triple studs, ladders and blocks
- Operator follows screen controlled process, places pre-cut lumber in C or L configuration
- Studs are progressed through nailer and automatically nailed at specified nail centers
- Studs up to 11.8ft long can be nailed
- High capacity 1000 nail coil holders
- Nail usage counter - alerts operator when nails need to be replaced
- Compatible with wide range of standard industry data exports
- 24" industrial touch screen
- UL Listed Industrial Control Panels



## OPTIONS

- Customized table length proportionate to stud length
- Left and right hand configurations

For more information, visit [spida.com](http://spida.com)



See more

