




TrussMaker

SPECIFICATIONS

These specifications are for a TrussMaker with 7 tables.

Overall length, width, height	67.6 x 20.3 x 13.9ft
The operator station sits outside this width	
Max automated puck opening	9.78ft
Table height	10.83ft
Max truss length	51.67ft
Min/Max lumber height	1.38 – 5.51in
Working height	31.57in
Machine mass	88,185lb
Operating temperature	14 - 122°F
Pressing force	30T @ 124 Bar & 38T @ 151 Bar
Max press throat opening	6.18in
Platen size	129.9(w) x 23.6(d)in
Jigging slot spacing (1 bobbin per slot)	17.72in
Electrical requirement	
Press head	400V 32A 3Ph + Neutral & Earth
Tables	400V 63A 3Ph + Neutral & Earth
Air requirement	2.82CFM @100psi

* Specifications shown reflect a typical configuration. Machine design, layout and features may vary depending on final configuration and customer requirements. Details will be confirmed at the time of order.

OPTIONS

- 2 configurations - side eject, end eject
- Ride-on platform either side of table
- Automated or manual jigging
- Laser projection
- Configurable length by adding or reducing tables
- 1, 2, or more press heads (normally dependent on table length)
- 1 or multiple operator stations for automated jigging

For more information, visit spida.com

OVERVIEW

The TrussMaker is used in the assembly of lumber roof trusses. Precut lumber components are positioned within the jigging system, and nailplates are placed at each joint.

The ride-on press head then travels along the truss, accurately pressing the plates into the lumber to secure every connection. Once complete, the finished truss is manually ejected from the table.

The TrussMaker streamlines the assembly of lumber roof trusses while maximizing floor space - combining technology, precision and efficiency to produce high quality trusses.

FEATURES

- Truss jigging included:
 - Jigging bobbins (2 per table)
 - Octa-cam (1 per table)
 - Adjustable heel jigs (2 per operator station)
 - Apex jig (1 per operator station)
 - Vertical upright jig (1 per operator station)
 - Bridging plates (20 per operator station)
 - Magnetic stops (4 per operator station)
 - T Bar allen key (1 per operator station)
- Heavy duty construction
- Horizontal manual ejection system
- Safety laser scanner
- Ride-on platform (table height)
- Direct drive
- Bell crank pressing action
- Pressure boost button
- Compatible with wide range of standard industry data exports
- UL Listed Industrial Control Panels



See more

