



ALL TRUCK PARTS CORPORATION





TECHNICAL DATA

TUBELESS WHEEL



17.5X6.00 SERIES 500PCS-20GP 990PCS-40GP 1100PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENTER HOLE	OFFSET	RECOM MEND VALVE	THICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
17.5X6.00	5	29	JSR22	203.2	146	128	V3-20-4	5	10	1850	8R17.5
	5	32	JSR22	208	150	120/125	V3-20-4	5	12	1850	8.5R17.5
	6	21	H1	205	161	125	V3-20-4	5	12	1850	9R17.5
	6	32	JSR22	222.25	164	127/135	V3-20-4	5	10	1850	9.5R17.5
	6	20.5	JSR22	190	140	128	V3-20-4	5	10	1850	205/65R17.5
	8	21.5/27	JSR18	275	221	135	V3-20-4	5	12	1850	205/75R17.5
	8	24	H1	275	221	134	V3-20-4	5	10	1850	215/75R17.5
	10	26	H1	225	176	135/124	V3-20-4	5	10	1850	225/70R17.5

17.5X6.75 SERIES 450PCS-20GP 990PCS-40GP 1100PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENTER HOLE	OFFSET	RECOM MEND VALVE	THICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
17.5X6.75	6	29	JSR22	205	161	138	V3-20-4	6	12	1360	8R17.5
	6	32	JSR22	222.25	164	140/145	V3-20-4	6	12	1360	8.5R17.5
	6	21	H1	205	161	131	V3-20-4	6	12	1360	9R17.5
	8	26	H1	275	221	143	V3-20-4	6	12	1360	9.5R17.5
	10	26	H1	225	176	144/153	V3-20-4	6	12	1360	10R17.5

19.5X6.00 SERIES 360PCS-20GP 720PCS-40GP 800PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENTER HOLE	OFFSET	RECOM MEND VALVE	THICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
19.5X6.00	6	21	H1	205	161	127	V3-20-4	5	12	1600	8R19.5
	6	32	JSR22	222.25	163	135	V3-20-4	5	12	1600	8R19.5
	8	32	JSR22	275	214	123/135	V3-20-4	5	12	1600	8R19.5



TECHNICAL DATA

TUBELESS WHEEL

19.5X6.75 SERIES 360PCS-20GP 720PCS-40GP 800PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENTER HOLE	OFFSET	RECOM MEND VALVE	THICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
19.5X6.75	6	32	JSR22	222.25	163	140	V3-20-4	6	12	2500	9.5R19.5
	8	32	JSR22	275	214	136	V3-20-4	6	12	2500	245/70R19.5
	8	26	H1	275	221	140	V3-20-4	6	12	2500	265/70R19.5
	8	32	JSR22	285	221	144	V3-20-4	6	12	2500	265/70R19.5
	10	26	H1	225	176	135	V3-20-4	6	12	2500	265/70R19.5

19.5X7.5 SERIES 360PCS-20GP 720PCS-40GP 800PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENTER HOLE	OFFSET	RECOM MEND VALVE	THICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
19.5X7.5	6	32	JSR22	222.25	164	147	V3-20-4	7	12	2900	245/70R19.5
	8	26	H1	275	221	140	V3-20-4	7	12	2900	265/70R19.5
	8	32	JSR22	275	214	145	V3-20-4	7	12	2900	285/70R19.5
	8	26	H1	275	221	151/155	V3-20-4	7	12	2900	285/70R19.5
	10	26	H1	225	176	151	V3-20-4	7	12	2900	285/70R19.5

22.5X6.00 SERIES 360PCS-20GP 720PCS-40GP 800PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENTER HOLE	OFFSET	RECOM MEND VALVE	THICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
22.5X6.00	10	26	H1	225	176	135	V3-20-4	5	14		85R22.5
	8	32	JSR22	275	214	135	V3-20-4	5	14		85R22.5

22.5X6.75 SERIES 360PCS-20GP 720PCS-40GP 800PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENTER HOLE	OFFSET	RECOM MEND VALVE	THICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
22.5X6.75	6	32	JSR22	222.25	164	140	V3-20-4	6	14	2800	8R22.5
	8	32	JSR22	285	221	140	V3-20-4	6	14	2800	9R22.5
	8	32	JSR22	275	214	144	V3-20-4	6	14	2800	10R22.5
	10	26	H1	335	281	144/155	V3-20-4	6	14	2800	255/70R22.5
	10	26	H1	225	176	140	V3-20-4	6	14	2800	255/70R22.5

22.5X7.5 SERIES 320PCS-20GP 640PCS-40GP 640PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENTER HOLE	OFFSET	RECOM MEND VALVE	THICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
22.5X7.5	demountable					115	V3-20-4			3250	10R22.5
	8	32	JSR22	275	214	165	V3-20-4	7	14	3250	11R22.5
	8	24	H1	275	221	152	V3-20-4	7	14	3250	255/70R22.5
	8	32	JSR22	285	221	150/165	V3-20-4	7	14	3250	265/60R22.5
	10	26	H1	335	281	155/165	V3-20-4	7	14	3250	275/70R22.5
	10	26	H1	285.75	220	152	V3-20-4	7	14	3250	275/80R22.5
	10	32	JSR22	285.75	222	152	V3-20-4	7	14	3250	275/80R22.5

22.5X8.25 SERIES 280PCS-20GP 560PCS-40GP 640PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENTER HOLE	OFFSET	RECOM MEND VALVE	THICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
22.5X8.25	8	32	JSR22	285	221	168	V3-20-6	7	14	3550	11R22.5
	8	32	JSR22	275	214	168	V3-20-6	7	14	3550	12R22.5
	10	26	H1	285.75	220	170/175	V3-20-6	7	14	3550	255/70R22.5
	10	26	H1	285.75	220	168	V3-20-6	6	11	3550	265/60R22.5
	10	32	JSR22	285.75	222	170	V3-20-6	7	14	3550	275/70R22.5
	10	26	H1	335	281	165/171	V3-20-6	7	14	3550	275/80R22.5
	10	26	H1	335	281	120	V3-20-6	7	14	3550	285/60R22.5
	10	26	H1	335	281	0	V3-20-6	7	14	3550	295/80R22.5
	10	26	H1	335	281	169	V3-20-6	7	14	3550	305/70R22.5
	10	27	JSR18	335	281	169	V3-20-6	7	14	3550	305/70R22.5
	10	26	H1	285.75	220	168	V3-20-6	7	14	3550	305/70R22.5
	10	32	JSR22	285.75	220	168	V3-20-6	7	14	3550	305/70R22.5
	demountable					120	V3-20-6			3550	305/70R22.5



TECHNICAL DATA

TUBELESS WHEEL

22.5X9.0 SERIES 280PCS-20GP 560PCS-40GP 640PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENTER HOLE	OFFSET	RECOM MEND VALVE	THICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
22.5X9.0	8	26	H1	275	221	175	V3-20-6	7	14	4000	12R22.5
	8	32	JSR22	285	221	175	V3-20-6	7	14	4000	285/60R22.5
	10	26	H1	285.75	220	175	V3-20-6	7	14	4000	295/60R22.5
	10	32	JSR22	285.75	222	175	V3-20-6	7	14/16	4000	295/80R22.5
	10	26	H1	335	281	175	V3-20-6	7	14	4000	305/60R22.5
	10	26	H1	335	281	175	V3-20-6	6	11	4000	305/70R22.5
	10	26	H1	335	281	170	V3-20-6	7	14	4000	315/60R22.5
	10	26	H1	335	281	0	V3-20-6	7	14	4000	315/70R22.5
	10	26	H1	335	281	120	V3-20-6	7	14	4000	315/75R22.5
	demountable					130	V3-20-6			4000	315/80R22.5
demountable					122	V3-20-6			4000	315/80R22.5	

22.5X9.75 SERIES 280PCS-20GP 560PCS-40GP 600PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENTER HOLE	OFFSET	RECOM MEND VALVE	THICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
22.5X9.75	10	26	H1	285.75	220	180	V3-20-6	7	14	4000	13R22.5
	10	26	H1	335	281	180	V3-20-6	7	14	4000	13R22.5

24.5X8.25 SERIES 210PCS-20GP 420PCS-40GP 480PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENTER HOLE	OFFSET	RECOM MEND VALVE	THICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
24.5X8.25	10	26	H1	285.75	220	168	V3-20-6	7	12	3550	11R24.5
	10	26	H1	335	281	170	V3-20-6	7	16	3550	11R24.5
	10	32	JSR22	285.75	222	168	V3-20-6	7	16	3550	11R24.5



24.5X9.0 SERIES 208PCS-20GP 416PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENTER HOLE	OFFSET	RECOM MEND VALVE	THICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
24.5X9.0	10	26	H1	335	281	175	V3-20-6	7	16	3750	12R24.5
	demountable					127	V3-20-6			3750	12R24.5

22.5X11.75 SERIES 240PCS-20GP 480PCS-40GP 480PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENTER HOLE	OFFSET	RECOM MEND VALVE	THICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
22.5X11.75	8	24	H1	275	221	0	TR570	7	12	4500	355/50R22.5
	10	26	H1	335	281	120	TR570	7	14	4500	365/70R22.5
	10	26	H1	335	281	120	TR570	6	12	4500	375/90R22.5
	10	26	H1	335	281	0	TR570	7	12	4500	385/55R22.5
	10	26	H1	335	281	120	TR570	7	14	4500	385/65R22.5
	10	26	H1	335	281	0	TR570	7	12	4500	385/65R22.5
	10	26	H1	335	281	135	TR570	7	14	4500	385/65R22.5
	10	26	H1	335	281	98	TR570	7	14	4500	385/65R22.5
	10	26	H1	335	281	98	TR570	7	14	4500	385/65R22.5

22.5X13.00 SERIES 240PCS-20GP 480PCS-40GP 480PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENTER HOLE	OFFSET	RECOM MEND VALVE	THICKNESS		WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE					RIM	DISC		
22.5X13.00	10	26	H1	335	281	0	TR570	7	14	5300	415/45R22.5
	10	26	H1	285.75	220	0	TR570	7	14	5300	425/65R22.5 445/65R22.5



TECHNICAL DATA

TUBE TYPE WHEEL

5.50F-16 SERIES 840PCS-20GP

SIZE	BOLT HOLE			P.C.D	CENTER HOLE	OFFSET	DISC THICKNESS	WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE						
16-5.50F	5	32	JSR22	208	150	125	10	1220	7.00R16
	5	29	JSR22	203.2	146	115	10	1220	7.50R16
	5	32	JSR22	208	150	115	10	1220	7.50R16
	6	20.5	JSR22	190	140	110	10	1220	7.50R16
	6	32	JSR22	222.25	164	115	10	1220	7.50R16

6.00G-16 SERIES 760PCS-20GP

SIZE	BOLT HOLE			P.C.D	CENTER HOLE	OFFSET	DISC THICKNESS	WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE						
6.00G-16	5	32	JSR22	203.2	146	127	10	1400	8.25R16
	5	32	JSR22	208	150	127	12	1400	8.25R16
	5	32	JSR22	208	150	136	10	1400	8.25R16
	6	20.5	JSR22	190	140	125	10	1400	8.25R16
	6	32	JSR22	222.25	163	125	10	1400	8.25R16
	6	32	JSR22	222.25	164	135/141	10	1400	8.25R16

6.50-16 SERIES 780PCS-20GP

SIZE	BOLT HOLE			P.C.D	CENTER HOLE	OFFSET	DISC THICKNESS	WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE						
6.50-16	6	32	JSR22	222.25	163	135	10	1400	7.50R16
	8	24	H1	222.25	164	135	10	1400	8.25R16

TECHNICAL DATA

TUBE TYPE WHEEL

7.5V-20 SERIES 360PCS-20GP 560PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENTER HOLE	OFFSET	DISC THICKNESS	WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE						
7.5V-20	8	32	JSR22	285	221	165	14	3730	10.00R20
	10	32	JSR22	285.75	222	170	14	3730	10.00R20
	10	26	H1	335	281	165	14	3730	10.00R20
	10	26	H1	285.75	220	165	14	3730	10.00R20

8.00V-20 SERIES 320PCS-20GP 520PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENTER HOLE	OFFSET	DISC THICKNESS	WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE						
8.00V-20	8	32	JSR22	275	214	173	16	3270	11.00R20
	10	26	H1	335	281	175	16	3270	11.00R20
	10	32	JSR22	285.75	222	175	14	3270	11.00R20
	10	26	H1	285.75	220	173	16	3270	11.00R20

8.50-20 SERIES 360PCS-20GP 560PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENTER HOLE	OFFSET	DISC THICKNESS	WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE						
8.50-20	8	32	JSR22	285	221	175	14	3730	1200R20
	10	26	H1	335	281	180	14	3730	1200R20
	10	32	JSR22	285.75	221	175	14	3730	1200R20
	10	26	H1	285.75	220	180	16	3730	1200R20

8.50-24 SERIES 208PCS-20GP 370PCS-40HQ

SIZE	BOLT HOLE			P.C.D	CENTER HOLE	OFFSET	DISC THICKNESS	WHEEL LOAD (KGS)	TYRE SIZE
	NO.	DIA.	TYPE						
8.50-24	10	27	JSR18	335	281	180	14/16	4500	1200R24
	10	26	H1	335	281	180	14/16	4500	1200R24

