


NOTES:

1. MOUNT RAIN GAUGE PER MANUFACTURERS INSTRUCTIONS.
2. RAIN GAUGE CAN BE MOUNTED WITH WORM-DRIVE HOSE CLAMPS TO FIT ANY SIZE POLE. ALTERNATIVELY, CHANNEL STRUT OR 90 DEGREE METAL BRACKET CAN SUPPORT THE RAIN GAUGE FROM UNDERNEATH. THE RAIN GAUGE MUST BE MOUNTED LEVEL.
3. RAIN GAUGE CAN BE MOUNTED ON ANY EXPOSED FREE STANDING POLE OR SURFACE ON SITE.
4. RAIN GAUGE TO BE MOUNT WHERE THERE ARE NO OBSTRUCTIONS OF RAINFALL AT LOW ANGLES -- SUCH AS TREES, HOUSES, FENCES -- AND AS LOW AS POSSIBLE OUT OF THE WIND
5. RAIN GAUGE TO BE ACCESSIBLE FOR NORMAL CLEANING AND LOCATED AWAY FROM TREES OR OTHER SOURCES OF HEAVY POLLEN OR DEBRIS.
6. ALL CONDUIT PENETRATIONS ARE TO BE IP68 RATED.



GENERIC DETAIL

RAIN GAUGE



OPTIRTC, INC.
98 NORTH WASHINGTON ST.
SUITE 210
BOSTON, MA 02114
(844) 678-4782

RAIN GAUGE GENERIC

NOT FOR CONSTRUCTION
REFERENCE USE ONLY
NOT TO SCALE
© OPTIRTC, INC. 2026
ALL RIGHTS RESERVED

REVISED: 04/14/2026

DRAWING NUMBER:
RG-1