



## Dryback LVT Flooring - Product Collection Data Sheet

### Technical Specifications

#### Indoor Air Quality (IAQ) Criteria

- No ortho phthalates are used in the making of this product.
- FloorScore® Certified

#### Dimensions (nominal)

- 2mm Thickness
- 12 mil (0.3mm) High Performance Urethane
- 7.4" (187mm) Wide
- 48.3" (1227mm) Long

#### Construction

- Top Layer - High Performance High Wear Urethane Top Coat
- 2<sup>nd</sup> Layer – Wear Resistant PVC Wear Layer
- 3<sup>rd</sup> Layer – Print Film
- 4<sup>th</sup> Layer – LVT Core Layer
- Micro-bevel side and end edges

#### Finish Coatings

- Wood grain surface texture
- UV-cured urethane based finishes with High Performance Coating Anti-Scratch Top Coats.

#### Warranty

- 25 Year Residential, 10 year Light Commercial

#### Test Methods and Standards

- ASTM F1914-07(2011) – Residual indentation (140 lbs) – **3.9%**
- ASTM F2199-09(2014) – Dimensional Stability – **MD = -0.27% / AMD = -0.17%**
- ASTM F925-13 – Resistance to Chemicals – All Reagents = **0 reaction**
- ASTM F137-08 – Test Method for Flexibility = **PASS**
- ASTM E648 – Critical Radiant Flux = **1.01 watts/cm<sup>2</sup> (Class 1)**