



RUFF NECK

PUNCH PANEL LIVESTOCK TRAILER

MODERN STYLING, PREMIUM FEATURES, LEGENDARY EBY QUALITY

The Eby Ruff Neck Punch Panel is the ultimate livestock trailer for commercial transporters, commercial swine operators, and show enthusiasts across North America. Designed to work in the harshest environments, it combines modern styling with premium features and legendary Eby quality — consistently setting the mark for reliability, performance, and versatility year after year.

BOLD DESIGN — Modern styling with no visible fasteners and chiseled features, backed by a full swing, slam-shut tailgate.

SMOOTH INTERIOR — Tapered side posts, smooth flat walls, and tapered wheel pockets create a safer environment for livestock and easier clean-out, all on a high-button diamond plate floor.

STRONG FOUNDATION — Exclusive Eby aluminum extrusions, including a massive 7" x 5" rear frame post with 7" x 4-½" corner reinforcements, and a 12-¼" tubular bottom rail, ensure exceptional strength and durability.

STANDARD SIZES

Lengths: 24'6" - 35'

Width: 7'3", 8', 8'6"

Heights: 6'7" to 8'1"



RUFF NECK

PUNCH PANEL LIVESTOCK TRAILER

STANDARD FEATURES



Front and rear cast aluminum corners



Formed aluminum fenders with multi-function lights



Slam shut tailgate




All Eby trailers come standard with Dexter axles



Fully framed, full-height side door



High button diamond plate floor



All-aluminum sub-frame

POPULAR OPTIONS

Additional options and custom sizes available.



Rolling gate partition



Spare wheel and tire




Available in a variety of colors: White, Gun Metal Gray, Black & Mill Finish Aluminum (standard)


STANDARD SPECIFICATIONS

Floor Lengths	24'6" to 35'
Widths	7'3", 8', 8'6"
Inside Height	6'7" to 8'1"
GVW	18,000 LB to 25,000 LB
Axles	Rubber ride (grease packed bearings); 102" wide - (2) 8,000 LB on 24'6" and 26' lengths - (2) 10,000 LB on 27'6" and longer lengths
Brakes	Electric, self adjusting
Wheels	17.5 Heavy-duty steel, 8 lug
Tires	235/75R17.5 LRH
Safety Equipment	Tow chains and electronic break-away kit
Nose	Aluminum double wall construction
Coupler	2-5/16" Ball coupler (30,000 LB) adjustable height
Side Wall	.075 thick aluminum sheet riveted to extruded aluminum hat shaped side-post on 18" centers.
Punch Patterns	Standard punch patterns A, B, C and D (custom available)
Floor	.115 6061 T-6 high grip diamond plate floor with 3" I-beams on 12" centers. (4) 1" high longitudinal ridges
Side Door	28-1/2" wide, curb side escape door
Tailgate	Full swing slam shut with 32" wide sliding door on roadside. (3) heavy-duty 4" offset hinges for extended swing
Roof Sheet	One piece .040 aluminum sheet
Divider	(1) Center divider with outside release
Lights	(3) LED clearance lights on roof rail, (2) LED S/T/T/R lights, (2) LED inside lights. 12-Volt electrical, 7-way RV style plug


PUNCH PATTERNS




Punch Panel A



Punch Panel B



Punch Panel C



Punch Panel D



Eby is a proud member of The National Association of Trailer Manufacturers, dedicated to improving trailer safety and performance. Eby trailers are manufactured in compliance with NATM guidelines.

800-292-4752
www.mheby.com