Access Your Digital Downloads

Homeowner Downloads

Who should download this:
Homeowners



PRO Downloads

Who should download this:
Installers

CONTROL YOUR WATER®

LEAKSECURE®

Thank you for choosing LeakSecure!

You can download the full version(s) of your device & app documentation by scanning these QR codes.

Quick Start Guide

What's In The Box?




LeakSecure Device



Power Supply



1 ¼" NPSM Installation Tube



1 ¼" NPSM to 1" NPT Fittings

Installation Requirements

IMPORTANT:
LeakSecure® should be installed by a licensed plumber. Failure to follow installation instructions may lead to a malfunctioning or leaking device and void the manufacturer's warranty. For complete warranty terms and conditions, refer to page 20 of the User Guide, available for download.

1. The LeakSecure device is installed in an accessible location on the main cold water supply line from water provider.
2. The device must be installed AFTER water meter, main water shut-off, and pressure reducing valve (if applicable).
3. For accurate leak detection and water usage data, your device must be installed BEFORE water heaters, water softeners, whole-home filtration, etc.
4. The power supply and device must not be buried or installed where the ambient temperature can exceed 140 deg F (60 deg C) or below 32 deg F (0 deg C).
5. 110/220V 15W power supply with continuous power within 20' of the installation. A GFCI outlet is recommended.
6. A smartphone with the LeakSecure app installed is required to activate your LeakSecure device, receive notifications, and perform remote water shutoff.
7. The device must be in range of a Wi-Fi network (WLAN connectivity / IEEE 802.11 bgn, 2.4 GHz range)

Installation Diagram

