SALO | SUSPENSION

PRODUCT PHOTOGRAPHY & SPECIFICATIONS

CARLYLE COLLECTIVE

BY CAMERON DESIGN HOUSE



DIMENSIONS

Salo Taso - Standard dimensions: From 40 to 80cm (15"-32"); From 50 to 90cm (20"-36"); From 60 to 100cm (24"-40")
Salo Elama - Standard dimensions: From 50 to 120cm (20"-47")
Salo Lunar - Standard dimensions: From 50 to 120cm (20"-47")
Standard profile size: 40x40mm. Up to 12 rings from 20 to 300cm in diameter.

SPECIFICATIONS

Hanging: Fully adjustable drop height on 1.2mm stainless steel suspension cables.
Light Source: External and internal crystal profile diffusers. Integral LED lighting. LED ribbon, CRI>95, ~50K hours life. LED standard colour temperature options: 2.4k, 2.7k and 3k (other temperatures available on request). Power to fixtures via suspension cables.
Light Output: Decorative lighting element only. Indicative Lux level available on request.
LED Driver: Triac Dimmable (5%-100%) as standard, all dimming protocols available on request. Wattage from 30-200W dependent on sizing. Output Voltage: 24V. Input Voltage: 110-277V, to be specified.
Hanging Options: Ceiling Rose or Direct Attach as standard. Custom hanging option available.
Maintenance: Clean with smooth and dry cloth. Do not use any ammonia, solvents or abrasives. No user serviceable components.
Bespoke options and design service available. All fittings and installation instructions are provided.

ABOUT

Hinting at the glamour and exuberance of the Art Deco period, the Salo exudes mystique.

FINISHES

Brushed Metal, Polished Metal and Powder Coat (full range of RAL colours): Gold, Almond Gold, Rose Gold, Brass, Copper, Antique Bronze, Chrome, Nickel, Black Nickel.

SALO | SUSPENSION

PRODUCT PHOTOGRAPHY & FINISHES

FINISHES

Brushed Metal, Polished Metal and Powder Coat (full range of RAL colours): Gold, Almond Gold, Rose Gold, Brass, Copper, Antique Bronze, Chrome, Nickel, Black Nickel.

ABOUT

Hinting at the glamour and exuberance of the Art Deco period, the Salo exudes mystique.

SPECIFICATIONS

Hanging: Fully adjustable drop height on 1.2mm stainless steel suspension cables.
Light Source: External and internal crystal profile diffusers. Integral LED lighting. LED ribbon, CRI>95, ~50K hours life. LED standard colour temperature options: 2.4k, 2.7k and 3k (other temperatures available on request). Power to fixtures via suspension cables.
Light Output: Decorative lighting element only. Indicative Lux level available on request.
LED Driver: Triac Dimmable (5%-100%) as standard, all dimming protocols available on request. Wattage from 30-200W dependent on sizing. Output Voltage: 24V. Input Voltage: 110-277V, to be specified.
Hanging Options: Ceiling Rose or Direct Attach as standard. Custom hanging option available.
Maintenance: Clean with smooth and dry cloth. Do not use any ammonia, solvents or abrasives. No user serviceable components.
Bespoke options and design service available. All fittings and installation instructions are provided.