BROOKLYN | WALL SCONCE

PRODUCT PHOTOGRAPHY & SPECIFICATIONS

CARLYLE COLLECTIVE

BY BOYD LIGHTING

DETAILS

Model 10910, 10911
Materials Brass, Glass
Lamping Brooklyn Sconce I: LED: 13 watts max, Standard 3000K, 90+ CRI, ~1400 lumens, Universal 120-277V. Brooklyn Sconce II: LED: 19 watts max, Standard 3000K, 90+ CRI, ~2100 lumens, Universal 120-277V. 2700K color temperature is available. The lamps standard in this fixture can be dimmed with 0-10v, ELV or MLV style dimmers. Driver must be mounted remotely.

The Brooklyn Sconces transform walls and mirrors into luminous architectural elements. Their slim brass frame and fused cast-glass surface create a subtle yet brilliant glow — elegant when used singly, dramatic when arranged in multiples. Designed by Mark Figueredo for Boyd.

BACKPLATES

Optional Backplates: A set of two half-sized backplates (2.38") when mounting to drywall without an electrical box or a set of two full-sized backplates (3.62") when mounting to drywall with a mud ring style electrical box.

Shown In Antiqued Boyd Brass



DIMENSIONS & WEIGHT

Brooklyn Sconce I: Ht 21.62" x W 1.5" x Projection 3.5" (549 mm x 38 mm x 171 mm). Weight: 8.5 lbs (3.9 kg). Brooklyn Sconce II: Ht 36" x W 1.5" x Projection 3.5" (914 mm x 38 mm x 171 mm). Weight: 11 lbs (5.2 kg).

NOTES

UL listed (or equivalent) for damp locations. Mirror Mount Backplates: 1.50" x 2.00". ADA Compliant at any height. Glass shade: Fused & Cast Clear.

