VALE II | WALL SCONCE

PRODUCT PHOTOGRAPHY & SPECIFICATIONS

CARLYLE COLLECTIVE

BY BOYD LIGHTING

DETAILS
Model 10978, 10980
Materials Brass, Glass
Shade Cast and Slumped Glass in Clear, Smoke or Topaz.
Lamping Vale Sconce II - 48" model: LED: 50 watts max, Standard 2700K, 90+ CRI, ~3500 lumens, Universal 120-277V. Vale Sconce II - 60" model: LED: 50 watts max, Standard 2700K, 90+ CRI, ~3500 lumens, Universal 120-277V. 3000K color temperature is available. The lamps standard in this fixture can be dimmed with 0-10v, ELV or MLV style dimmers. Dimming Form Not Required. Driver must be mounted remotely.

VALE expresses light as a continuous sculpted form, pairing precision machined brass with flowing cast glass to create a balanced interplay of clarity and movement. Available at 48" and 60" in height, the sconce creates a statement with large scale, in multiple glass finishes, and custom options, making it a versatile solution for residential, hospitality, and large-volume architectural applications.

Shown In Antique Boyd Brass and Smoke Glass



VALE II | WALL SCONCE

DIMENSIONED DRAWINGS

CARLYLE COLLECTIVE

BY BOYD LIGHTING

DIMENSIONS & WEIGHT

Vale Sconce II - 48" model: Ht 48" x W 13" x Projection 6.5" (1219 mm x 330 mm x 165 mm). Weight: 40 lbs (18.2 kg). Vale Sconce II - 60" model: Ht 60" x W 13" x Projection 6.5" (1524 mm x 330 mm x 165 mm). Weight: 45 lbs (20.5 kg).

NOTES

UL listed (or equivalent) for damp locations. Backplates: 4" x 11" (102 x 279mm).



