# VALE II | PENDANT

**PRODUCT PHOTOGRAPHY & SPECIFICATIONS**

**CARLYLE COLLECTIVE**

BY BOYD LIGHTING

**DETAILS**
**Model** 10970, 10972
**Materials** Brass, Glass
**Shade** Cast and Slumped Glass in Clear, Smoke or Topaz.
**Lamping** Vale Pendant II - 48" model: LED: 50 watts max, Standard 2700K, 90+ CRI, ~3500 lumens, Universal 120-277V. Vale Pendant II - 60" model: LED: 50 watts max, Standard 2700K, 90+ CRI, ~3500 lumens, Universal 120-277V. 3000K color temperature is available. The lamps standard in this fixture can be dimmed with 0-10v, ELV or MLV style dimmers. Dimming Form Not Required.

VALE expresses light as a continuous sculpted form, pairing precision machined brass with flowing cast glass to create a balanced interplay of clarity and movement. Available at 48" & 60" in length, the series offers multiple glass finishes, and custom colorways, making it a versatile solution for residential, hospitality, and large-volume architectural applications.

**WOVEN TEXTILE SUSPENSION**
Cable: Anthracite, Brick, Oat

Shown In Earthen Brass with Anthracite Textile Suspension



# VALE II | PENDANT

**DIMENSIONED DRAWINGS**

**CARLYLE COLLECTIVE**

BY BOYD LIGHTING

**DIMENSIONS & WEIGHT**

Vale Pendant II - 48" model: W 13" x L 48" x 24"-60" OAH (specify) (330 mm x 1219 mm x 610-1524mm). Weight: 45 lbs (20.5 kg). Vale Pendant II - 60" model: W 13" x L 60" x 24"-60" OAH (specify) (330 mm x 1524 mm x 610-1524mm). Weight: 50 lbs (22.7 kg).

**NOTES**

UL listed (or equivalent) for damp locations. Canopies: 9 1/2" x 14" (241 x 356mm).



