

PowerFlex X Enabled ZeroVa DZ 480



Charger Specifications

Subject to change, refer to zerovatech.com

DZ 480

AC Input Voltage	CE/CNS: 3 Φ 380 ~ 415Vac (+/-15%) 50/60HZ UL: 3 Φ 480Vac (+10%,-15%) 50/60HZ
AC Input Current Rating	Max: 920A Nominal: 621A
Connection/Power Grid System	3P+ N+ PE , TN/TT
Power Factor	>0.99
Efficiency	>96%
DC Output Voltage	200 ~ 950V
Max Power Output	480kW
Dimension (W x D x H)	1500 x 800 x 1965 mm / 59.06 x 31.50x 77.36 inch
Weight	1300 kgs / 2866 lbs

DZ 480

Operating Temperature	-30~50°C / -22~122°F
Humidity	5~95% RH, non-condensing
IP/IK Rating	IP55 IK10 NEMA 3R IK10
EMC/EMI	IEC.61851-21-2, FCC Part 15 Subpart B, ICES-003
Safety	IEC.61851-1., IEC.61851-23, UL 2202, UL 2231
Input Protection	OVP, UVP, OCP, OPP, OTP, SPD, RCD
Output Protection	OCP, SCP, OVP, LVP, OTP, IMD
Backend Support	OCPP 1.6 JSON,OCPP 2.0 core profile *Simultaneously connect to client & maintenance server
External Communication	4G/ Wi-Fi/ Ethernet (RJ45)

See how Powerflex can empower you and your site. [Contact us](#) today.



[Connect on LinkedIn](#)



[Learn More on YouTube](#)