


Micro Crystal







kHz Tuning Fork Crystals

MHz AT-Cut Crystals

Real-Time Clocks

Low Frequency Oscillators



Short Form Catalog October 2016

Micro Crystal - Where timing begins!

Company

Micro Crystal is a company fully owned by the Swatch Group, the worldwide leader in watchmaking. Micro Crystal uses a high tech Swiss MEMS technology for the ultrahigh precision manufacturing of Quartz Crystal Resonators, Oscillators and Real-Time Clock Modules. Focused on mass production of high quality components, Micro Crystal serves not only high volume consumer applications, but also high reliability automotive and medical implantable applications. Using its manufacturing facilities in Switzerland and Thailand, Micro Crystal produces the smallest Quartz Crystal Resonators, Oscillators and Real-

Time Clock Modules. Micro Crystal's products achieving the world lowest power consumption, are perfectly suited for the IoT and wearables applications. Most of our products are also AEC-Q200 rev. D qualified. Micro Crystal and its production facilities are ISO 9001 and ISO 14001 qualified, and fulfill all social and environmental regulations.

Micro Crystal, as a major player in this field, offers cost competitive products using its worldwide operation, distribution and support networks.




Applications and Markets


Telecommunications and Industrial




Wearables and IoT










Automotive



Medical and Health Care / Implantable



kHz Tuning Fork Crystals in Metal Packages

Crystal Type		Watch Crystal	30 kHz to 200 kHz SMT Package Crystal		Units
Product Type		DS26-L3N	MS1V-T1K	MS3V-T1R	
Dimensions (w x h x l) mm		Ø 2.0 x 6.0	2.0 x 2.0 x 6.1	1.4 x 1.4 x 5.2	
					
					
Package Form		Round	Square	Square	
Leads		Straight	SMD Formed Leads	SMD Formed Leads	
Operating Temp. Range TA		-10 to +60	-40 to +85	-40 to +85	°C


Frequency	F _L	32.768	32.768	32.768	kHz
Standard Load Capacitance ¹⁾	C _L	8.2	7 / 9 / 12.5	7 / 9 / 12.5	pF
Frequency Tolerance @ 25°C ²⁾	ΔF/F	±20	±20	±20	ppm
Series Resistance typ./max.	R _s	30 / 42	45 / 60	50 / 65	kΩ
Motional Capacitance typ.	C ₁	2.25	2.25	2.25	fF
Static Capacitance typ.	C ₀	0.9	0.9	0.9	pF
Drive Level max.	P	1.0	1.0	1.0	μW
Aging max. 1st Year @ 25°C	ΔF/F	±3	±3	±3	ppm
Turnover Temperature	T ₀	25 ±5	25 ±5	25 ±5	°C
Frequency vs. Temperature	ΔF/F	-0.035 ppm/°C ² (T-T ₀) ² ±10%			ppm

1) Other load capacitance on request.
2) Tighter and wider frequency tolerances on request.














Applications

- IoT
- White Goods
- Cellular Phones
- Gaming Electronics
- Wearables, Watches
- TV and Set Top Boxes
- ATM and POS Systems
- Medical and Health Care
- Security and Access Control
- Industrial and Consumer Electronics
- Data Logger, Home and Factory Automation
- E-Meter, Heating Counter, Smart Meter, PV Converter

Ordering Information



kHz Tuning Fork Crystals in Ceramic Packages

Crystal Type	32.0 kHz to 2'000 kHz Tuning Fork Crystals							Units
Product Type	CC1V-T1A	CC4V-T1A	CM7V-T1A	CM7V-T1A low ESR	CM8V-T1A	CM9V-T1A		
Dimensions (l x w x h) mm	8.0 x 3.7 x 1.75	5.0 x 1.9 x 0.9	3.2 x 1.5 x 0.65	3.2 x 1.5 x 0.65	2.0 x 1.2 x 0.6	1.6 x 1.0 x 0.5		
			 h = 0.35 on request					
	 h = 1.75	 h = 0.9	 h = 0.65	 h = 0.65	 h = 0.6	 h = 0.5		
Lid Material	Ceramic	Ceramic	Metal	Metal	Metal	Metal		
Operating Temp. Range TA	-40 to +85	-40 to +85	-40 to +85	-40 to +85	-40 to +85	-40 to +85	°C	
Operating Temp. Range TB ¹⁾	-40 to +125	-40 to +125	-40 to +125	-40 to +125	-40 to +125	-40 to +125	°C	

Frequency	F _L	32.768	32.768	32.768	32.768	32.768	32.768	kHz
Standard Load Capacitance ²⁾	C _L	7 / 9 / 12.5	7 / 9 / 12.5	6 / 7 / 9 / 12.5	6 / 7 / 9 / 12.5	4 / 7 / 9 / 12.5	4 / 7 / 9 / 12.5	pF
Frequency Tolerance @ 25°C ³⁾	ΔF/F	±20	±20	±20	±20	±20	±20	ppm
Series Resistance typ./max.	R _s	37 / 60	50 / 65	50 / 70	40 / 50	55 / 75	75 / 90	kΩ
Motional Capacitance typ.	C _i	2.1	2.1	3.7	4.7	4.0	6.3	fF
Static Capacitance typ.	C ₀	1.6	1.2	1.2	1.3	1.2	1.4	pF
Drive Level max.	P	1.0	1.0	1.0	1.0	0.5	0.5	μW
Aging max. 1st Year @ 25°C	ΔF/F	±3	±3	±3	±3	±3	±3	ppm
Turnover Temperature	T ₀	25 ±5	25 ±5	25 ±5	25 ±5	25 ±5	25 ±5	°C
Frequency vs. Temperature	ΔF/F	-0.035 ppm/°C ² (T-T ₀) ² ±10%						ppm

1) Also available in -55 to +125°C temp. range (TC).


2) Other load capacitance on request.

3) Tighter and wider frequency tolerances on request.












Applications

- IoT
- Computing
- Wireless Units
- Engine Control
- Industrial Control
- GPS and Navigation
- Embedded Modules
- Multimedia Systems
- Tablets, Smart Phones
- Security and Access Control
- Wearables, Portable Devices
- Remote Keyless Entry Systems
- High Temperature Range Designs
- Ultra Small Size Devices, Smart Cards
- Health Care, Medical and Medical Implantable

Ordering Information



MHz AT-Cut Crystals in Ceramic Packages

Crystal Type	MHz AT-Cut Crystals				
Product Type	CC1A/F	CC2A	CC6A/F	CC7A	CC8A
Dimensions (l x w x h) mm	8.0 x 3.7 x 1.75	5.0 x 3.2 x 1.2	3.5 x 2.2 x 0.9	3.2 x 1.5 x 0.9	2.0 x 1.2 x 0.63
			 4 or 2 pads available		
	 h = 1.75	 h = 1.2	 h = 0.9	 h = 0.9	 h = 0.63

Standard

Product Type	Dimensions (l x w x h) mm	Frequency MHz	Operating Temp. °C	R _s typ. Resistance at Fmin and Fmax	C ₁ typ. Capacitance at Fmin and Fmax	C ₀ typ. Capacitance at Fmin and Fmax	Features
CC1A-T1A	8.0 x 3.7 x 1.75	8 - 30	-55 to +125	60 to 30 Ω	4.0 to 11 fF	2.0 to 4.0 pF	
CC1F-T1A	8.0 x 3.7 x 1.75	30 - 250	-55 to +125	50 to 15 Ω	4.0 to 6.0 fF	2.4 to 6.0 pF	
CC2A-T1A	5.0 x 3.2 x 1.2	12 - 70	-55 to +125	60 to 10 Ω	3.0 to 12 fF	2.0 to 5.0 pF	
CC6A-T1A	3.5 x 2.2 x 0.9	16 - 70	-55 to +125	60 to 20 Ω	2.0 to 5.0 fF	1.5 to 3.0 pF	
CC6F-T1A	3.5 x 2.2 x 0.9	70 - 250	-55 to +125	60 to 15 Ω	2.7 to 5.6 fF	2.4 to 2.9 pF	
CC6F-T1AF	3.5 x 2.2 x 0.9	70 - 200	-55 to +125	60 to 35 Ω	2.0 to 3.0 fF	2.4 to 2.9 pF	Filter Applications Low Spurious
CC7A-T1A	3.2 x 1.5 x 0.9	24 - 50	-55 to +125	100 to 50 Ω	1.0 to 3.0 fF	0.5 to 2.0 pF	Med. Implantable
CC8A-T1A	2.0 x 1.2 x 0.63	24 - 50	-55 to +125	120 to 50 Ω	1.0 to 3.0 fF	0.5 to 2.0 pF	Med. Implantable

High Temperature

CC1A-T1AH	8.0 x 3.7 x 1.75	8 - 24	-55 to +200	100 to 50 Ω	4.0 to 9.0 fF	2.0 to 3.2 pF	Harsh Environment
CC2A-T1AH	5.0 x 3.2 x 1.2	12 - 40	-55 to +200	70 to 40 Ω	5.0 to 10 fF	2.5 to 4.0 pF	Harsh Environment
CC6A-T1AH	3.5 x 2.2 x 0.9	16 - 40	-55 to +200	80 to 50 Ω	2.0 to 9.0 fF	1.5 to 3.0 pF	Harsh Environment

Applications

Products are screened and specially tested.

- Telemetry
- Optical Network
- Airborne Equipment
- Medical Implantable
- Radio Communications
- Health Care and Medical
- Down Hole and Well Drilling

Description

This SMT quartz crystal in ceramic package has been specially designed for surface mounting using vapor phase soldering, epoxy assembling technology, and standard reflow soldering.







All quartz crystals are in fundamental mode frequency range up to 250 MHz.

Specially designed for harsh environmental shock and vibration.

Extremely wide operating temperature range up to 200°C, with an ultra low internal moisture level.



RTC Modules in Ceramic Packages

Product Type	RV-xxxx-C2	RV-xxxx-C3	RV-xxxx-C7
Dimensions (l x w x h) mm	5.0 x 3.2 x 1.2	3.7 x 2.5 x 0.9	3.2 x 1.5 x 0.8
			
			
Lid Material	Glass	Metal	Metal

I²C-Bus Interface

Product Type	Main Feature	Bus	Time Accuracy	Supply V _{DD} V	Current I _{DD} nA	T _{OP} °C	Offset Comp.	Temp. Comp.	Backup Switch	Trickle Charge	Event Input	RAM Bytes	EEPROM Bytes
RV-4162-C7	Standard	I ² C	±20 ppm @ 25°C	1.0 to 4.4	350	-40 to +85	✓						
RV-8564-C2	Standard	I ² C	±20 ppm @ 25°C	1.2 to 5.5	250	-40 to +85							
RV-8564-C3	Standard	I ² C	±20 ppm @ 25°C	1.2 to 5.5	250	-40 to +85							
RV-2251-C3	Power Management	I ² C	±20 ppm @ 25°C	0.9 to 5.5	210	-40 to +85	✓		✓	✓		1	
RV-8523-C3	Ultra Low Power	I ² C	±20 ppm @ 25°C	1.2 to 5.5	130	-40 to +85	✓		✓				
RV-1805-C3	X-Treme Low Power	I ² C	±2 ppm @ 25°C Factory calibrated	1.5 to 3.6	60	-40 to +85	✓		✓	✓	✓	256	
RV-3029-C2	Temperature Comp.	I ² C	A ±6 ppm @ -40°C to +85°C B ±25 ppm @ -40°C to +85°C	1.3 to 5.5	800	-40 to +125		✓	✓	✓		8	2
RV-3029-C3	Temperature Comp.	I ² C	A ±6 ppm @ -40°C to +85°C B ±25 ppm @ -40°C to +85°C	1.3 to 5.5	800	-40 to +125		✓	✓	✓		8	2
RV-8803-C7	Temperature Comp.	I ² C	±3 ppm @ -40°C to +85°C	1.5 to 5.5	240	-40 to +85	✓	✓			✓	1	

SPI-Bus Interface

Product Type	Main Feature	Bus	Time Accuracy	Supply V _{DD} V	Current I _{DD} nA	T _{OP} °C	Offset Comp.	Temp. Comp.	Backup Switch	Trickle Charge	Event Input	RAM Bytes	EEPROM Bytes
RV-8063-C7	Standard	SPI	±20 ppm @ 25°C	0.9 to 5.5	190	-40 to +85	✓					1	
RV-2123-C2	Ultra Low Power	SPI	±20 ppm @ 25°C	1.1 to 5.5	130	-40 to +85	✓						
RV-3049-C2	Temperature Comp.	SPI	A ±6 ppm @ -40°C to +85°C B ±25 ppm @ -40°C to +85°C	1.3 to 5.5	800	-40 to +125		✓	✓	✓		8	2
RV-3049-C3	Temperature Comp.	SPI	A ±6 ppm @ -40°C to +85°C B ±25 ppm @ -40°C to +85°C	1.3 to 5.5	800	-40 to +125		✓	✓	✓		8	2

Applications

System power management can be greatly enhanced using Micro Crystals high precision, low power RTC modules:

- IoT
- POS, SPS Control
- Metering, Smart Meter
- Battery Management System
- Automotive, GPS and Drive Recorder
- Industrial, Computing, Embedded Systems
- Wearables, Activity Bands, Sports Monitors
- Health Care, Glucose Meters, Drug Dispensers
- IP Cameras, Alarm and Building Control, Telemetry

Ordering Information

RV - 3029 - C3 TA QC Option A

RTC module


Product type

Package size
C2 = 5.0 x 3.2 x 1.2 mm
C3 = 3.7 x 2.5 x 0.9 mm
C7 = 3.2 x 1.5 x 0.8 mm

Time accuracy
Option A = ±6 ppm @ -40°C to +85°C
Option B = ±25 ppm @ -40°C to +85°C









Qualification
QC = Commercial Grade (Standard)
QA = Automotive Grade AEC-Q200

Temperature range
TA = -40 to +85°C (Standard)
TB = -40 to +125°C

 Linux Drivers available



Low Frequency Oscillators in Ceramic Packages

Product Type	OV-xxxx-C7	OM-xxxx-C7	OV-xxxx-C8	OM-xxxx-C8
Dimensions (l x w x h) mm	3.2 x 1.5 x 1.0	3.2 x 1.5 x 0.7	2.0 x 1.2 x 0.85	2.0 x 1.2 x 0.7
				
				
Lid Material	Ceramic	Metal	Ceramic	Metal

32.768 kHz Oscillators

Product Type	Frequency kHz	$\Delta F/F @ 25^\circ\text{C}$ ppm	Supply V_{DD} V	Current I_{DD} nA	T_{OP} °C	Duty Cycle %	CLKOE Input	$\Delta f/V$ ppm/V	Aging 1Y @ 25°C ppm	T_0 °C	Frequency vs. Temperature ppm
OV -7604-C7	32.768	± 20 ¹⁾	1.2 to 5.5	300	-40 to +125	40 to 60	✓	± 1.5	± 3.0	25 \pm 5	-0.035 ppm/°C ² (T-T ₀) ² \pm 10%
OM -7604-C7	32.768	± 20 ¹⁾	1.2 to 5.5	300	-40 to +125	40 to 60	✓	± 1.5	± 3.0	25 \pm 5	
OV -7605-C8	32.768	± 20 ¹⁾	1.6 to 5.5	450	-40 to +85	40 to 60	✓	± 3.0	± 3.0	25 \pm 5	
OM -7605-C8	32.768	± 20 ¹⁾	1.6 to 5.5	450	-40 to +85	40 to 60	✓	± 3.0	± 3.0	25 \pm 5	

100 kHz Oscillators

OV -0100-C7	100.000	± 20 ¹⁾	1.2 to 5.5	650	-40 to +85	40 to 60	✓	± 1.5	± 3.0	18 \pm 5	-0.035 ppm/°C ² (T-T ₀) ² \pm 10%
OM -0100-C7	100.000	± 20 ¹⁾	1.2 to 5.5	650	-40 to +85	40 to 60	✓	± 1.5	± 3.0	18 \pm 5	
OV -0100-C8	100.000	± 20 ¹⁾	1.6 to 5.5	550	-40 to +85	40 to 60	✓	± 3.0	± 3.0	28 \pm 5	
OM -0100-C8	100.000	± 20 ¹⁾	1.6 to 5.5	550	-40 to +85	40 to 60	✓	± 3.0	± 3.0	28 \pm 5	

1) Tighter and wider frequency tolerances on request.

Applications

High precision, low current, and small package sizes make Micro Crystal Oscillators ideal for:

- IoT
- Smart Pens
- Industrial Computing
- Wearables and Activity Bands
- Health Care, Medical and Medical Implantable
- Clock Source (i.e., for sleep mode Bluetooth LE)
- Automotive, Emergency Call Units, Remote Keyless Entry

Ordering Information

O	V	-7604	-C7	± 20 ppm	TA	QC
Oscillator	Package lid	Frequency	Package size	Frequency tolerance	Temperature range	Qualification
	V = Ceramic lid M = Metal lid	7604 = 32.768 kHz 7605 = 32.768 kHz 0100 = 100.000 kHz	C7 = 3.2 x 1.5 mm C8 = 2.0 x 1.2 mm		TA = -40 to +85°C (Standard) TB = -40 to +125°C	QC = Commercial Grade (Standard) QA = Automotive Grade AEC-Q200 QM = Medical Grade



Europe

Headquarters-Switzerland

Micro Crystal AG
Muehlestrasse 14
CH-2540 Grenchen
Switzerland
Phone +41 32 655 82 82
Fax +41 32 655 82 83
sales@microcrystal.com
www.microcrystal.com

Germany

Micro Crystal
Swatch Group (Deutschland) GmbH
Wagenbacher Weg 11
74924 Neckarbischofsheim
Germany
Phone +49 72 68 91 12 53
Fax +49 72 68 91 12 54
sales.germany@microcrystal.com

America

Western US

Micro Crystal
The Swatch Group (U.S.) Inc.
10061 Talbert, Suite 205
Fountain Valley, CA 92708
USA
Phone +1 714 963 7002
Fax +1 714 963 6044
sales.us@microcrystal.com

Central US

Micro Crystal
The Swatch Group (U.S.) Inc.
Carrollton, TX
USA
Phone +1 404 960 3375
Fax +1 714 963 6044
sales.us@microcrystal.com

Eastern US

Micro Crystal
The Swatch Group (U.S.) Inc.
Vernon Hills, IL
USA
Phone +1 847 984 0548
Fax +1 714 963 6044
sales.us@microcrystal.com



www.microcrystal.com/contacts

Asia

Japan

Micro Crystal
The Swatch Group Japan KK
Nicolas G. Hayek Center
7-9-18 Ginza, Chuo-ku
Tokyo 104-8188
Japan
Phone +81 3 6254 7283
Fax +81 3 6254 7126
sales.japan@microcrystal.com

Singapore

Micro Crystal
The Swatch Group S.E.A (S) Pte. Ltd.
1 Harbourfront Avenue
#14-03/07 Keppel Bay Tower
098632 Singapore
Singapore
Phone +65 6513 3103
Fax +65 6272 0186
sales.singapore@microcrystal.com

Taiwan

Micro Crystal
The Swatch Group (Taiwan) Ltd.
14F, No. 8, Sec. 7, Civic Blvd.,
Nangang Dist. Taipei (115)
Taiwan
Phone +886 2 2652 3689
Fax +886 2 2653 2938
sales.taiwan@microcrystal.com

Korea

Micro Crystal
The Swatch Group (Korea) Ltd
10F National Pension Service Building
36 Chungjeongno
Seodaemun-gu, Seoul 03741
Korea
Phone +82 2 3149 8290
Fax +82 2 393 4094
sales.korea@microcrystal.com

China (Shenzhen)

Micro Crystal
The Swatch Group (China) Ltd.
8F, Tower A, HongLong Century Plaza
Shennan East Road 4002, Luohu District
Shenzhen 518001
China
Phone +86 755 8832 0687
Fax +86 755 8832 0696
sales.shenzhen@microcrystal.com

China (Shanghai)

Micro Crystal
The Swatch Group (China) Ltd.
6F, Metro Tower
30 Tian Yao Qiao Road
Shanghai 200030
China
Phone +86 21 2412 5280
Fax +86 21 2412 5015
sales.shanghai@microcrystal.com



www.microcrystal.com