



©2025 TownSteel, Inc. REV 1.0 July 08, 2025



The TownSteel Promise

We have built our company around the promise of creating durable hardware solutions for your projects. Our complete product line is the result of decades of determined engineering. This allows TownSteel to provide you with the right product to meet your exacting specifications. With end-to-end customer support, you will find that TownSteel is the ideal company for you to partner with. Check us out at townsteel.com for more information!

ED1200/EF1200 Series is a wide stile heavy-duty grade 1 surface vertical rod exit device, fabricated and blended with simplicity, strength, durability, aesthetics and installer-friendly innovations. The center case is made of heavy wrought steel, with top and bottom rod adjustors. The push bar assembly's smooth and reduced projection minimizes catch hazards. A full complement of exit trims is available in various types and functions.

ED1200 EF1200 SVR



| CONTENTS | PAGE |
|---------------------|------|
| Features | 4 |
| Specifications | 5 |
| Finishes | 6 |
| Exit Device Profile | 7 |
| Dimensions | 8 |
| Strikes | 9 |
| How to Order | 13 |

3 877 858 0888 ED1200 / EF1200

Features

ED1200/EF1200 Series exit devices are made to comply with the highest safety and security standards in the industry. The ED1200/EF1200 series provides superior durability for heavy use applications such as schools, hospitals, assisted living facilities, banks, offices, hospitality, and other institutions or commercial buildings.







REV 1.0 July 08, 2025

| Features | Benefits |
|--|--|
| ANSI / BHMA A156.3 | Grade 1 certified exit device |
| ANSI / UL 305 | ANSI/UL 305 listed |
| UL10C | UL10(C) 3-hour fire rated (EF1200 only) |
| ADA compliant | Meets requirements of the Americans with Disabilities Act |
| BAA compliant | Meets guidelines of Buy American Act |
| All exit devices are non-handed or field reversible design | Allows for changing the handing without requiring new hardware |
| Shock-resistant latching design | Provides superior vandalism protection |
| All internal components made of corrosion-resistant alloy | Provides superior weather-resistance and durability |

Specifications

| Door Size | 36", standard |
|---------------------------|--|
| | 48", optional |
| Door Thickness | 1-3/4" - 2-1/4" |
| | *Others available upon request |
| Door Undercut | 1/4" |
| Mounting Height | 39-5/8" from device center line to finished floor |
| Handing | Non-handed |
| Push Bar Projection | Neutral: 3-13/16" |
| | Depressed: 3-1/16" |
| Top Latch Bolt | 5/8" throw, stainless steel, pullman type, deadlocking |
| Bottom Bolt | 5/8" throw, stainless steel, pullman type, deadlocking, independent action |
| | Round slide bolt, optional |
| Top and Bottom Latch Case | 4-1/2" x 2-1/8" x 1-1/2" |
| Top Rod | 1/2" square tube, 36-1/8" for 7' door |
| | 1/2" square tube, 48-1/8" for 8' door |
| Bottom Rod | 1/2" square tube, 31-7/8" |
| Rod Extension | Available 24" for doors ranging between 8' and 10' high |
| Dogging | Flat/Hex key dogging, standard (ED1200 only) |
| | Cylinder dogging, optional (ED1200 only) |
| | Electrical dogging (ELR), optional |
| | Less dogging, optional |

877 858 0888 **ED1200 / EF1200**

Finishes



Dark Oxidized Bronze (613)




Satin Stainless Steel (630)

Other finishes available upon request


Finishes are for illustration only and may vary from actual product provided

Exit Device Profile



Dimensions





106 Rim Strike

Top strike for surface vertical rod exit device. For panic applications.



108 Rim Strike

Top strike for surface vertical rod exit device. For fire applications.



9

136 Rim Strike

Rim strike for double door surface vertical rod exit device in combination with a coordinator. For panic and fire applications.



215 Top Strike


Top strike for flush transom for surface vertical rod exit devices. For panic and fire applications.



10 www.townsteel.com ED1200 / EF1200 ©2025 TownSteel, Inc.

224 Bottom Strike

Optional bottom strike for surface vertical rod exit devices. For panic and fire applications.



225 Bottom Strike (Flat)

Optional bottom strike for surface vertical rod exit device round slide bolt. For panic and fire applications.



11


226 Bottom Strike (Flat)

Optional bottom strike for surface vertical rod exit device round slide bolt. For panic and fire applications.



227/227F Bottom Strike

Standard bottom strike for surface vertical rod exit devices. For panic and fire applications.



12 www.townsteel.com ED1200 / EF1200 ©2025 TownSteel, Inc.

REV 1.0 July 08, 2025

ED1200/EF1200 Heavy Duty Surface Vertical Rod Exit Device

| ED1200 Suface vertical rod panic exit hardware EF1200 Surface vertical rod fire exit hardware Bottom Rod and Latch Options Blank Standard LBR Less bottom rod RBL Round bottom latch PL Pullman latch Device Size 36 36" (For doors 2'4"-3') 48 48" (For doors 2'10"-4') Door Height 84 84" (For doors up to 84" high) 96 96" (For doors over 84" and up to 96" high) 120 120" (For doors over 96" and up to 120" high) Finish 613 Dark Oxidized Bronze 630 Satin Stainless Steel Dogging Blank Flat/Hex key dogging (ED1200 only) | Fire Rating | |
|--|------------------------------|---|
| Bottom Rod and Latch Options Blank LBR Less bottom rod RBL Round bottom latch PL Pullman latch Device Size 36 36" (For doors 2'4"-3') 48 48" (For doors 2'10"-4') Door Height 84 84" (For doors up to 84" high) 96 96" (For doors over 84" and up to 96" high) 120 120" (For doors over 96" and up to 120" high) Finish 613 Dark Oxidized Bronze 630 Satin Stainless Steel | ED1200 | Suface vertical rod panic exit hardware |
| Blank Less bottom rod RBL Round bottom latch PL Pullman latch Device Size 36 36" (For doors 2'4"-3') 48 48" (For doors 2'10"-4') Door Height 84 84" (For doors over 84" and up to 96" high) 120 120" (For doors over 96" and up to 120" high) Finish 613 Dark Oxidized Bronze 630 Satin Stainless Steel | EF1200 | Surface vertical rod fire exit hardware |
| LESS bottom rod RBL Round bottom latch PL Pullman latch Pevice Size 36 36" (For doors 2'4"-3') 48 48" (For doors 2'10"-4') Door Height 84 84" (For doors up to 84" high) 96 96" (For doors over 84" and up to 96" high) 120 120" (For doors over 96" and up to 120" high) Finish 613 Dark Oxidized Bronze 630 Satin Stainless Steel | Bottom Rod and Latch Options | |
| RBL Round bottom latch PL Pullman latch Device Size 36 36" (For doors 2'4"-3') 48 48" (For doors 2'10"-4') Door Height 84 84" (For doors up to 84" high) 96 96" (For doors over 84" and up to 96" high) 120 120" (For doors over 96" and up to 120" high) Finish 613 Dark Oxidized Bronze 630 Satin Stainless Steel | Blank | Standard |
| PL Pullman latch Device Size 36 36" (For doors 2'4"-3') 48 48" (For doors 2'10"-4') Door Height 84 84" (For doors up to 84" high) 96 96" (For doors over 84" and up to 96" high) 120 120" (For doors over 96" and up to 120" high) Finish 613 Dark Oxidized Bronze 630 Satin Stainless Steel | LBR | Less bottom rod |
| Device Size 36 36" (For doors 2'4"-3') 48 48" (For doors 2'10"-4') Door Height 84 84" (For doors up to 84" high) 96 96" (For doors over 84" and up to 96" high) 120 120" (For doors over 96" and up to 120" high) Finish 613 Dark Oxidized Bronze 630 Satin Stainless Steel Dogging | RBL | Round bottom latch |
| 36 36" (For doors 2'4"-3') 48 48" (For doors 2'10"-4') Door Height 84 84" (For doors up to 84" high) 96 96" (For doors over 84" and up to 96" high) 120 120" (For doors over 96" and up to 120" high) Finish 613 Dark Oxidized Bronze 630 Satin Stainless Steel Dogging | PL | Pullman latch |
| 48" (For doors 2'10"-4') Door Height 84 | Device Size | |
| B4 84" (For doors up to 84" high) 96 96" (For doors over 84" and up to 96" high) 120 120" (For doors over 96" and up to 120" high) Finish 613 Dark Oxidized Bronze 630 Satin Stainless Steel | 36 | 36" (For doors 2'4"-3') |
| 84 84" (For doors up to 84" high) 96 96" (For doors over 84" and up to 96" high) 120 120" (For doors over 96" and up to 120" high) Finish 613 Dark Oxidized Bronze 630 Satin Stainless Steel | 48 | 48" (For doors 2'10"-4') |
| 96 96" (For doors over 84" and up to 96" high) 120 120" (For doors over 96" and up to 120" high) Finish 613 Dark Oxidized Bronze 630 Satin Stainless Steel Dogging | Door Height | |
| 120 120" (For doors over 96" and up to 120" high) Finish 613 Dark Oxidized Bronze 630 Satin Stainless Steel Dogging | 84 | 84" (For doors up to 84" high) |
| Finish 613 Dark Oxidized Bronze 630 Satin Stainless Steel Dogging | 96 | 96" (For doors over 84" and up to 96" high) |
| Dark Oxidized Bronze Satin Stainless Steel Dogging | 120 | 120" (For doors over 96" and up to 120" high) |
| Dogging Satin Stainless Steel | Finish | |
| Dogging | 613 | Dark Oxidized Bronze |
| | 630 | Satin Stainless Steel |
| Blank Flat/Hex key dogging (ED1200 only) | Dogging | |
| | Blank | Flat/Hex key dogging (ED1200 only) |
| CD Cylinder dogging (ED1200 only) | CD | Cylinder dogging (ED1200 only) |
| ED Electric dogging (ELR) | ED | Electric dogging (ELR) |
| LD Less dogging | LD | Less dogging |

13 877 858 0888 **ED1200 / EF1200**

ED1200/EF1200 Heavy Duty Surface Vertical Rod Exit Device

Options

| Blank | Standard |
|-------|---------------------------|
| AL | Alarm exit |
| DE | Delayed egress |
| ELR | Electric latch retraction |
| LM | Latch bolt monitoring |
| RX | Request to exit |
| SS | Signal switch |

Pick one item from each category when ordering.

Example order: ED1200-3684-630-DE

Strikes and Shim Kits

| Strikes | |
|-----------------------------|--|
| ED 106 Rim Strike | Top strike for SVR exit device. For panic applications. |
| ED 108 Rim Strike | Top strike for SVR exit device. For fire applications. |
| ED 136 Rim Strike | Rim strike for double door SVR in combination with a coordinator. For panic and fire applications. |
| ED 215 Top Strike | Top strike for flush transom for SVR. For panic and fire applications. |
| ED 224 Bottom Strike | Optional bottom strike for SVR. For panic and fire applications. |
| ED 225 Bottom Strike (Flat) | Optional bottom strike for SVR round slide bolt. For panic and fire applications. |
| ED 226 Bottom Strike (Flat) | Optional bottom strike for SVR round slide bolt. For panic and fire applications. |
| ED 227 Bottom Strike | Standard bottom strike for SVR. For panic applications. |
| ED 227F Bottom Strike | Standard bottom strike for SVR. For fire applications. |
| Shim Kits | |
| 616819-010 | Standard shim kit for 106 Rim strike, 2 pieces furnished |

15 877 858 0888 **ED1200 / EF1200**

Accessories

| Accessories | |
|---------------|--|
| ED 616823-010 | 31-7/8" bottom rod |
| ED 616823-020 | For 7' Door Height, 36-1/8" top rod |
| ED 616823-030 | For 8' Door Height, 48-1/8" top rod |
| ED 616823-040 | For 10' Door Height, 24" top extension rod for ED 616823-030 |
| TFL001-630 | Fire latch for LBR exit device |
| 6-1024 SNB | Sex bolts for Exit Only device (10-24 thread) |
| 4-4120 SNB | Sex bolts for Exit Only device or device with trim (1/4-20 thread) |
| 2-1024 SNB | Sex bolts for device with trim (10-24 thread) |

16 ED1200 / EF1200 www.townsteel.com REV 1.0 July 08, 2025

