

XMRX-L-303

Electrified/Motorized Mortise Lock with Ligature Resistant Trim-Lever



Escutcheon
(XMRX-E-L)



Sectional
(XMRX-S-L)



PCU

Electronic Specifications

- Motorized units 12 to 24 VDC
- Field adjustable for Fail Safe or Fail Secure
- Optional status sensors: RQE, PRIV, DAJ, MKO
- Power Conversion Unit (PCU) converts 12-24VDC to operating voltage

Code Compliance

- ANSI/BHMA: A156.13 Grade 1 Certified
- UL/ULC: UL 10C Listed 3 Hour Fire Rating
- BAA: Meets requirements of the Buy American Act
- ADA: Meets requirements of the Americans with Disabilities Act



Mechanical Specifications

- For facilities housing patients at risk
- For 1-3/4" door thickness, other upon request
- 2-3/4" backset
- Handed, field reversible
- 630 (US32D) finish
- Stainless steel rose (MRX-S-L), 2-3/4" in diameter
- Stainless steel escutcheon (MRX-E-L), 8"x3-1/4"x1/8"
- Stainless steel lever, ligature resistant
- Stainless steel turn piece, ligature resistant, ADA
- Stainless steel faceplate, 1-1/4" x 8"
- Stainless steel strike, ASA, 1-1/4" x 4-7/8"
- Through-bolt mounting, tamper resistant mounting screws, for wood and metal door
- Brass cylinder with stainless steel cover, 6 pin, Schlage "C" keyway standard, 2 keys per cylinder
- Small Format IC available with or without core, 6 or 7 pin core
- Schlage Large Format IC available in less core
- Corbin Large Format IC available in less core, for 6 pin core, Sargent Large format IC
- High Security Cylinder available, TownSteel "L" keyway, 6 pin
- High Security Small Format IC Core available, TownSteel "L" keyway, 7 pin
- Warranty: 2-year limited warranty

Important Note

It is TownSteel's position that if any of our keyed locks are to be used less cylinder, whether I.C. or standard, and another manufacturer's cylinder is to be used in place of the TownSteel original manufacturer's cylinder, that a sample of that product be provided to TownSteel in advance for testing.

How to Order:

Trim	XMRX-E-L Electrified Ligature Resistant Lever Mortise-Escutcheon Trim XMRX-S-L Electrified Ligature Resistant Lever Mortise-Sectional Trim
Function	303
Cylinder	SC / SFIC6 / SFIC7 / CLFIC6 / SLFIC / L6 / L7
Handing	LH / RH / LHR / RHR

Example Order: XMRX-E-L-303-SFIC7-LH

RX Ligature Resistant

REV 1.0 September 05, 2023