

SPECIFICATIONS

Product Line	Main Street
Product Type	Luxury Vinyl Plank (LVP)
Core Material	2mm Virgin Vinyl
Fiberglass Reinforced	FiberBlend
Wear Layer	8mil ScratchGuard
Overall Thickness	2mm (0.079")
Nominal Plank Size	7" x 48"
Actual Plank Size	177.8mm x 1219.2mm
Edge Profile	Square Edge
Embossing	Natural Wood Texture
Finish	Enhanced Polyurethane System
Installation Type	GlueDown
Bacteria Resistance	Standard

PACKAGING



CARTON

Planks	22
Square Feet	51.39 sqft
Weight (lbs)	39.02 lbs
Square Meters	4.77 m2
Weight (kg)	17.70 kg

PALLET

Cartons	50
Square Feet	2569.5 sqft
Weight (lbs)	1984.16 lbs
Square Meters	238.5 m2
Weight (kg)	900 kg

CONTAINER

Cartons	1,000
Square Feet	51390 sqft
Weight (lbs)	39683.16 lbs
Square Meters	4770 m2
Weight (kg)	18000 kg

PERFORMANCE TESTING

Slip Resistance	ASTM D2047	>0.6 (Dry)
Radiant Flux	ASTM E648	Class 1
Static Load	ASTM F970	2,000 PSI .005 Inch
Smoke Density	ASTM E662	Passes
Light Resistance	ASTM F1515	Passes
Heat Resistance	ASTM F1514	Passes
Chemical Resistance	ASTM F925	Passes
Phthalates	ASTM F3414 - 20 (CPSC)	Passes
Heavy Metals	ASTM F963	Passes
Formaldehyde	ASTM D6007	Passes
FloorScore Certified	California 01350	Passes
Leed Scorecard	EQ 4.3 Low-Emitting Materials	1 Point

WARRANTY

15
FIFTEEN YEARS
RESIDENTIAL

05
FIVE YEARS
LIGHT COMMERCIAL

00
NONE
HEAVY COMMERCIAL



WATERPROOF



PET FRIENDLY



EASY REPAIR

ARCHITECTURAL SPECIFICATION

All floors shown in the finish schedule or listed in the specification shall be Main Street Floor Vinyl Flooring provided by Urban Surfaces Inc., in design and color (list color TBD) selected from the range currently available from Urban Surfaces Inc, having a nominal total thickness of (Main Street - 2mm-0.079") gauge, and size in 7 in. x 48 in. (Main Street - 177.8 mm x 1219.2 mm). consisting of a (Main Street - 8 mil) thick wear layer over a printed film. Flooring meets composition, size, thickness, squareness, flexibility, resistance to chemicals, resistance to heat and resistance to light requirements of ASTM F 1700, "Standard Specification for Solid Vinyl Tile," Class III, Type B - Embossed Surface. For Main Street, shall have a 5-Year Limited Light Commercial warranty against manufacturing defects. For Main Street, the approved adhesives are: Prism 3010, Everlast 3020, and Omni 3050 and Underlayment FloorSilencer Pro. For additional installation, maintenance, or technical information, visit our website at www.urbansurfaces.com or contact us at 1-800-492-8722. Please view actual product samples when making a selection as our printed colors may vary from actual product.

INSTALLATION

End Use:	Suitable Grade Level:
Residential	All grades where excessive moisture conditions do not exist
Installation Method:	Installation Sundries As Required:
Glue Down	3010 Prism, 3020 Everlast, 3050 Omni, Infiniti Moisture Barrier