

Composite Premium Designer Flooring (Specification Data)

FLOORING PROPERTIES & PACKAGING

| Turns of Comptunitions | Company in Carolo O'' Longo Lou Lunion Vina d'Tile |
|------------------------|---|
| Type of Construction: | Commercial Grade 9" Loose Lay Luxury Vinyl Tile |
| Collection: | Composite |
| Use: | Commercial |
| Size: | 9" Width X 60" Length (228.6mm X 1524mm) |
| Installation Method: | Glue Down |
| Certification: | FloorScore Certified by SCS Global Services |
| Wear Layer: | 20mil (0.5mm) |
| Edge Detail: | Beveled Edge |
| Emboss: | Natural Wood Texture |
| Gauge: | 5mm Total Thickness |
| Planks/Case: | 6 |
| Coverage/Each Plank: | 3.77 Sq. Ft. (0.35 Sq. Meters) |
| Coverage/Case: | 22.6 Sq. Ft. (2.1 Sq. Meters) |
| Coverage/Pallet: | 52 Cases/Pallet (1175.2 Sq. Ft. / 109.2 Sq. Meters) |
| Warranty: | 20-Year Limited Commercial |

STANDARDS - SAFETY & PERFORMANCE

| Standard | Feature | Performance | |
|-----------|-----------------------|-----------------------------------|--|
| Stanuaru | | 9 in*60 in*0.5mm | |
| ASTM E648 | Critical Radiant Flux | Passes - >0.45 watts/cm², Class 1 | |

| ASTM D2047 | Coefficient of Friction, Slip Resistance | Meets SCOF for ADA walking surfaces |
|------------------------------------|---|-------------------------------------|
| CDPH/EHLB, Standard Method v1.2 | VOCs/TVOCs, Formaldehyde | Refer to Standard |

STANDARDS - SOUND

| Standard | Description | Requireme | nts | Results |
|-----------------------------|--|------------------------------------|----------|------------------------------------|
| ASTM E90 & ASTM E413 | Airborne Sound Transmission Loss of Building Partitions and Elements (STC / Sound Transmission Class) | 6" Concrete Slab + Drop-Ceiling | STC ≥ 50 | STC 62 (Surpasses Requirements) |
| ASTM E492 & ASTM E989 | Impact Sound Transmission Through Floor-Ceiling Assemblies (IIC / Impact Insulation Class) | 6" Concrete Slab + Drop-Ceiling | IIC ≥ 50 | IIC 54 (Surpasses Requirements) |

STANDARDS - MANUFACTURING & USAGE

| Standard | Foature | Performance |
|------------|-------------------------|---------------------------------|
| Stanuaru | Feature | 9 in*60 in*0.5mm |
| ASTM F970 | Static Load | Passes - 1000 psi |
| ASTM F2199 | Dimensional Stability | Passes |
| ASTM F1914 | Residual Indentation | Passes |
| ASTM F1514 | Resistance to Heat | Passes - less than 8.0 Delta E. |
| ASTM F1515 | Resistance to Light | Passes - less than 8.0 Delta E. |
| ASTM F925 | Resistance to Chemicals | Passes - no change |

| ASTM F410 | Wear Layer | Passes |
|------------|-------------------------------------|--------|
| ASTM D4060 | Abrasion Resistance | Passes |
| ASTM D7027 | Hoffman Scratch | Passes |
| EN 16094 | Micro-Scratch Resistance (A & B) | Passes |

Recommend Installation Options:





