

## **Veridian Premium Designer Flooring (Specification Data)**

#### **FLOORING PROPERTIES & PACKAGING**

| Type of Construction: | Commercial Grade 7.25" Loose Lay Luxury Vinyl Tile |
|-----------------------|--|
| Collection:           | Veridian   |
| Use:                  | Commercial   |
| Size:                 | 7.25" Width X 60" Length (184mm X 1524mm)          |
| Installation Method:  | Glue Down  |
| Certification:        | FloorScore Certified by SCS Global Services        |
| Wear Layer:           | 20mil (0.5mm)                                      |
| Edge Detail:          | Beveled Edge                                       |
| Emboss:               | Natural Wood Texture                               |
| Gauge:                | 5mm Total Thickness                                |
| Planks/Case:          | 8  |
| Coverage/Each Plank:  | 3 Sq. Ft. (0.28 Sq. Meters)                        |
| Coverage/Case:        | 24.11 Sq. Ft. (2.24 Sq. Meters)                    |
| Coverage/Pallet:      | 50 Cases/Pallet (1205.5 Sq. Ft. / 112 Sq. Meters)  |
| Warranty:             | 20-Year Limited Commercial                         |
|                       |  |

#### **STANDARDS - SAFETY & PERFORMANCE**

| Standard  | Feature               | Performance                       |  |
|-----------|-----------------------|-----------------------------------|--|
| Stanuaru  |                       | 7.25 in*60 in*0.5mm               |  |
| ASTM E648 | Critical Radiant Flux | Passes - >0.45 watts/cm², Class 1 |  |

| ASTM D2047                         | Coefficient of Friction,<br>Slip Resistance | Meets SCOF for ADA walking surfaces |
|------------------------------------|---|-------------------------------------|
| CDPH/EHLB, Standard Method<br>v1.2 | VOCs/TVOCs,<br>Formaldehyde                 | Refer to Standard                   |

### **STANDARDS - SOUND**

| Standard                    | Description  | Requireme                          | nts      | Results                            |
|-----------------------------|--|------------------------------------|----------|------------------------------------|
| ASTM E90 &<br>ASTM E413     | Airborne Sound Transmission<br>Loss of Building Partitions and<br>Elements (STC / Sound<br>Transmission Class) | 6" Concrete Slab +<br>Drop-Ceiling | STC ≥ 50 | STC 62<br>(Surpasses Requirements) |
| ASTM E492<br>& ASTM<br>E989 | Impact Sound Transmission Through Floor-Ceiling Assemblies (IIC / Impact Insulation Class)                     | 6" Concrete Slab +<br>Drop-Ceiling | IIC ≥ 50 | IIC 54<br>(Surpasses Requirements) |

## **STANDARDS - MANUFACTURING & USAGE**

| Standard   | Foature                 | Performance                     |
|------------|-------------------------|---------------------------------|
| Standard   | Feature                 | 7.25 in*60 in*0.5mm             |
| ASTM F970  | Static Load             | Passes - 1000 psi               |
| ASTM F2199 | Dimensional Stability   | Passes                          |
| ASTM F1914 | Residual Indentation    | Passes                          |
| ASTM F1514 | Resistance to Heat      | Passes - less than 8.0 Delta E. |
| ASTM F1515 | Resistance to Light     | Passes - less than 8.0 Delta E. |
| ASTM F925  | Resistance to Chemicals | Passes - no change              |

| ASTM F410  | Wear Layer                          | Passes |
|------------|-------------------------------------|--------|
| ASTM D4060 | Abrasion Resistance                 | Passes |
| ASTM D7027 | Hoffman Scratch                     | Passes |
| EN 16094   | Micro-Scratch Resistance<br>(A & B) | Passes |

# **Recommend Installation Options:**





