

QUARRY TILE

CERAMIC QUARRY



Quarry Tile is the ultimate solution for high-traffic environments where heavy use and functionality are paramount. These unglazed quarry tiles are meticulously crafted to excel in rigorous durability tests, including breaking strength and abrasion resistance, ensuring they maintain their exceptional quality over time.

Key Features:

- **Durable Matte Finish:** The tiles feature a timeless matte finish with a subtle through-body salt and pepper look, making them a standout choice for demanding projects.
- **Select from two colors:** Mayflower Red and Puritan Gray, to seamlessly complement your design vision.
- **Sturdy Thickness:** With a ½” thickness, these tiles are built to handle heavy commercial use without compromising performance.
- **GREENGUARD® Certified:** Our tiles promote healthier indoor air quality with low chemical emissions, making them a safe choice for any environment.
- **Superior Slip Resistance:** With a Dynamic Coefficient of Friction (DCOF) of ≥ .60, quarry tiles ensure safety while maintaining style.

Where performance and style are essential, Quarry Tile is the right choice. Elevate your space with a flooring solution that stands apart—unique, specifiable, and built to last.

QuarryBasics® Ironspot 6x6



311S
Mayflower Red

QuarryBasics® Ironspot 6x6



571S
Puritan Gray

Typical Uses

is appropriate for most residential and commercial, wall, countertop, backsplash, and floor applications.

Notice: Not all flooring products are suitable for wet areas, specialized applications, or commercial use. Please refer to the American National Standard Specifications for Ceramic Tile (ANSI® A137.1) for ceramic, stone, and glass installation for specific usage and installation information.

This product will contribute to USGBC LEED® points and the ANSI® approved NAHB® Green Building Points.

Notes

Color, texture, and finish variations may occur due to the nature of the product.

Color reproductions in this printed piece may vary from actual tile colors. Final selection should be made from actual tile samples.

Country of origin and other product features and characteristics are subject to change due to manufacturing efficiencies and other factors. See retailer or product packaging to verify country of origin and other product characteristics.

Technical Data	Results ¹
ANSI® A326.32	Oils/Greases (O/G)
Surface Hardness	7 Mohs
Break Strength	≥ 400 lbf. avg.
Water Absorption	≤ 3% ³
Intended Use ⁴	Residential, Light Commercial & Heavy Commercial

¹ Values are offered in good faith as being accurate and typical of normal production. Due to the natural variation of raw materials and manufacturing processes, the values of the purchased product for any particular installation may vary.

Color Variation



V2 Slight Variation

Field Tile Nominal Size (in) ¹	Metric (cm)	Pcs./Sq Ft ²	Thickness ³	Edge
6x6	15x15	4	12.7mm	Extruded

Trim	Shape	SKU	Nominal Size (in) ¹	Metric (cm)
Cove Base		Q3565	6x6	15x15

¹ These values may vary from lot to lot.

² These values are based on actual sizes including the grout joint.

³ May not apply to textured surfaces or tiles with uneven back patterns such as mesh mounted mosaics.