

## MC2V3X = Motor Control for 2 vents<sup>\*</sup>, 3 auxillary

The MC (motor control) series are preset packages that combine motor control and the ClimateBoss. These packages further reduce electrician time by simplifying installation and standardizing a package for greenhouse needs.

Need a customized relay cabinet and environmental controls? Know you'll have future equipment expansion? Look to the EasyWire package so we can help meet those specialized needs.



Mobile App & Desktop access available



## **BARTLETT**

— INSTRUMENT COMPANY —

P.O. Box 445 1032 Avenue H Fort Madison, IA 52627 1-888-404-9026 www.bartinst.com

## DEFAULT PACKAGE COMBINATIONS

 Option
 Ventilation
 Cooling
 Heating
 Timer

 1
 Vent C & D Side Wall Vent Motors 24V DC, ≤10A, ≤200Nm
 Cool 01 Endwall Louvers 120/240V AC Stall Motors
 Heat 01 (2x) Unit Heaters 24V AC Signal from T-Stat

120/240V AC, ≤20A, ≤3/4 HP

1	Vent C & D Side Wall Vent Motors 24V DC, ≤10A, ≤200Nm	Cool 01 Endwall Louvers 120/240V AC Stall Motors  Cool 02 Endwall Exhaust Fan Single Speed, 120/240V AC, ≤20A, ≤3/4 HP	Heat 01 (2x) Unit Heaters 24V AC Signal from T-Stat	-
2	Vent C & D Side Wall Vent Motors 24V DC, ≤10A, ≤200Nm	Cool 01 (2x) Endwall Louvers 120/240V AC Stall Motors	Heat 01 Unit Heater 24V AC Signal from T-Stat  Heat 02 Unit Heater 24V AC Signal from T-Stat	-
3	Vent C & D Side Wall Vent Motors 24V DC, ≤10A, ≤200Nm	Cool 01 Endwall Louvers 120/240V AC Stall Motors  Cool 02 Endwall Exhaust Fan Single Speed, 120/240V AC, ≤20A, ≤3/4 HP  Cool 03 Endwall Exhaust Fan Single Speed, 120/240V AC, ≤20A, ≤3/4 HP	-	-
4	Vent C Evaporative Pad Vent Motor 24V DC, ≤10A, ≤200Nm	Cool 01 (2x) Endwall Louvers 120/240V AC Stall Motors  Cool 02 (2x) Endwall Exhaust Fan Single Speed, 120/240V AC, ≤20A, ≤3/4 HP  Cool 03 Evaporative Pad Pump	-	Timer 01 Shade Curtain Motor 24V DC, ≤10A, ≤200Nm