



# HSW-3000 Portable Fume Extractor



H&S Autoshot manufactured self-contained, high vacuum fume extractor constructed of 14 and 16-gauge powder coated semi-gloss finish, steel. Unit capable of exhausting 450 CFM with filters in place with a 5 amp, 120v brushless DC vacuum motor. Unit includes built in spark trap and features 3-stage pre-filter screen 5/64" followed by a 5-micron primary filter and a secondary PP+PET 1-micron filter. Optional 2nd HEPA filter available. Unit includes 6 feet of flexible loc-line flex tube with flow valve and 5" conical screened inlet nozzle, LED power switch, speed potentiometer, 8" rubber wheels, front casters and extension handle.

|                         |   |
|-------------------------|---|
| <b>Motor</b>            | Brushless DC 120VAC @ 5 Amps, Single-Phase  |
| <b>Airflow</b>          | 450 cfm   |
| <b>Decibels</b>         | <65 db  |
| <b>Construction</b>     | 14 & 16 GA. Powder-coated steel w/ knob screw gasketed cover filter access            |
| <b>Length</b>           | 21"   |
| <b>Height</b>           | 12.5" (17" with wheels)   |
| <b>Width</b>            | 12"   |
| <b>Weight</b>           | 60 lbs.   |
| <b>Capture</b>          | 6 feet of flexible 2" loc-line flex tube with flow valve and 5" screened inlet nozzle |
| <b>Pre Filter</b>       | 11.5" x 11" x 1-3/4" Three stage stainless steel mesh 5/64" (2mm)                     |
| <b>Primary Filter</b>   | 11.5" x 11" x 2" High capacity G4 pleated poly 5-micron                               |
| <b>Secondary Filter</b> | 11.5" x 11" x 3-3/4" High capacity F8 multi-pleat PP+PET 1-micron                     |
| <b>Flammability</b>     | Class 2, UL Standard 900  |
| <b>Warranty</b>         | Two Year Limited  |
| <b>Source</b>           | H&S Autoshot/Mooresville, NC 28117  |

Specifications subject to change without notice.