

Conventional Horizontal Lathes Servoturn 500/2000



SKU: 300833

The Servoturn series of universal lathes combines the most modern feed technology with classic mechanical engineering. In contrast to standard conventional lathes, this series has ball screw drives and electronic hand wheels on all axes. High-torque servo motors implement every feed movement with the dynamics of modern CNC machines. Without gear change wheels and gears, feed and thread pitches can be selected electronically. Rapid traverses on all axes reduce non-productive time and electronic stops offer high repeat accuracy.

- Servo-feed system
- Preloaded ball screws on all axes
- Electronic hand-wheels
- Position indicator with V-constant feature
- Quick change tool holder

TECHNICAL SPECS

WORKING AREA

Center width	1950 mm
Turning diameter over bed	500 mm
Turning-Ø over support	300 mm
Bed width	400 mm

TRAVELS

Travel X-axis	250 mm
Travel Z-axis	1880 mm
Travel Z1-axis	100 mm

HEADSTOCK

Spindle speed	30 1/min - 1600 1/min
Spindle bore	86 mm
Spindle mount	A2-8
Lathe chuck diameter	250 mm

RAPID FEED

X-axis rapid feed	4 m/min
Z-axis rapid feed	4 m/min

FEED

Feed X-axis	0.01 mm/R - 2 mm/R
Feed Z-axis	0.01 mm/R - 2 mm/R

THREADING

Threading, whitworth 48	3-4 TPI

TAILSTOCK

Tailstock quill diameter	75 mm
Tailstock taper	5 MT
Tailstock quill stroke	150 mm

DRIVE CAPACITY

Motor rating main drive	6 kW - 9 kW
Motor rating X-axis	1.5 kW
Motor rating Z-axis	2.3 kW
Supply voltage	400 V

MEASURES AND WEIGHTS

Overall dimensions (length x width x height)	4.25 m x 1.28 m x 1.65 m
Weight	3450 kg



Micro-control via electronic hand-wheels but handling and positioning just as with a conventional machine









PRODUCT DETAILS

 The combination of a tried and tested machine base with the most advanced feed technology makes the change to a servo-conventional lathe even more attractive and cost-effective

Intuitive operation as we know it from conventional machines - only much better:

- Feed and thread leads can be selected via rotary switch what a brilliant concept
- Stops can be set electronically with the push of a button
- Feeds are infinitely variable via override potentiometer finally available on a conventional lathe
- Micro-control via electronic hand-wheels but handling and positioning just as with a conventional machine
- Axes are powered by high-quality servo drives that translate your hand movements with the precision and dynamics of modern CNC machines
- Infinitely variable speed adjustment and constant cutting speed of headstock
- Constant cutting speed: During face turning, the spindle speed automatically adapts to
 the changing workpiece diameter the constant cutting speed at the cutting edge of
 the turning tool ensures superior turning results with quality comparable to CNC lathes

Machine Frame

- Heavy ribbed machine bed with wide, hardened bed guides and V-blocks allow for heavy-duty machining
- Headstock and main spindle are designed for optimum rigidity, vibration damping and temperature balance
- This entire series also features large spindle bores
- A quick-action tool changer is included in the standard package and ensures maximum flexibility and productivity

Feed

• Ball screws on the X- and Z-axes ensure considerably fewer errors due to looseness (backlash), resulting in significantly higher precision

Equipment

- The low-maintenance machine is equipped with a central lubrication system
- The heavy-duty tailstock is easy to handle and features high clamping force
- Incl. 3-axis position indicator with integrated spindle speed display, fully assembled
- The Servoturn 500 standard equipment package includes a quick-change tool holder set type WB, and the Servoturn 660 models come with the larger type WC tool holder set

STANDARD EQUIPMENT

3-axis position indicator X.Pos 3.2
3-jaw chuck Ø 250 mm
Electronic hand-wheels
Quick change tool holder
Steady rest
Follow rest
Coolant system
Fixed splash guard (wall)
Traveling cover for the toolpost
Work lamp
Operating tools
Operator instructions



KNUTH on YouTubeInformation to the point

On our YouTube channel you can find videos for nearly all machines from our program. We show the machines from current deliveries and you get an impression of the handling, the processing quality and the machining performance.

Are you interested in a machine for which you cannot find a current video? Please feel free to contact us!