

Sizing Guidelines



Windows	Min width	Max width	Min height	Max height	Min area (sq. ft.)	Max area (sq. ft.)	Max Sash weight (lbs)
Picture	10"	11'8"	10"	11'8"	0.69	55	
Direct Set	1'2"	11'8"	1'2"	11'8"	1.36	55	
Awning	1'4"	6'0"	1'2"	4'0"	1.75	24	150
Casement	1'2"	3'4"	1'6"	7'8"	1.75	25	150
Fixed Sash	1'2"	9'0"	1'6"	9'0"	1.75	40	250

Swing Door Sizing Guidelines	Min width	Max width	Min height	Max height
Swing Door - Single	2'2"	3'8"	5'0"	10'0"
Swing Door - Double	4'3"	7'3"	5'0"	10'0"
Swing Door Sidelite	1'0"	3'8"	5'0"	10'0"
Swing Door Transom	1'0"	9'0"	1'0"	4'0"

Sidelite / Transoms less than 1' 2" available in direct set only

Sidelite / Transom more than 1'2" up to 9" wide available in direct set and panel

Sidelite wider than 3'8" and up to 55 sf available in direct set only

Sliding Patio Door Sizing Guidelines	Min width	Max width	Min height	Max height
2 Wide Sliding Patio Door	4'0"	10'0"	5'0"	10'0"
3 Wide Sliding Patio Door	6'0"	15'0"	5'0"	10'0"
4 Wide Sliding Patio Door	8'0"	19'8"	5'0"	10'0"

COMBINATION AND MULLION RULES

Combination units with (Picture, Casement, Awning, Fixed sash and Doors)

Maximum of 24' x 10' or 10' x 24' (240 sq. ft.)

Site mulling required for any combination window with both width and height exceeding 10' frame size and any combination wider or taller than 24'

All units larger than our maximum single and combination rules require DURABUILT engineering evaluation.



Lift Slide Sizing Guidelines	Max width (up to 8' height)	Max width (up to 10' height)	Max height (in)
Lift Slide 2-Panel	13' 9"	11' 9"	10'
Lift Slide 3-Panel Stackable (2 sliding, 1 fixed)	20' 6"	17' 6"	10'
Lift Slide 3-Panel (1 sliding, 2 fixed)	20' 9"	17' 9"	10'
Lift Slide 4-Panel (2 sliding, 2 fixed)	27' 6"	24' 6"	10'
Transom (Direct set)	up to 36"		



An exceptional Durabuilt product



Looking for more information? Questions?
Email us at deltafiberglass@durabuiltwindows.com

