

# CLAY-OUT! #2 SAFETY DATA SHEET

#### **SECTION 1: Identification**

Product identifier: Clay-Out! #2

Other means of identification: Specialty

SDS number: 1311

Recommended use: Spotter

**Recommended restrictions:** Not for personal care

Manufacturer/Importer/Supplier/Distributor information

Company name: U.N.X. Incorporated Address: 707 Arlington Blvd

Greenville, NC 27858

**Telephone:** Office hour (Mon-Fri)

8:00a.m. – 4:30p.m. (Eastern Time) OFFICE NUMBER: 252-756-8616

E-mail: unx@unxinc.com

Emergency phone number: CHEMTEL (800) 255-3924 (24 HOURS)

## SECTION 2: Hazard(s) identification

## **Classification of the Substance or Mixture:**

# Physical hazards

#### **Health hazards**

Acute toxicity, Oral/Inhalation/Dermal: Category 3
Skin corrosion/irritation: Category 1B
Serious eye damage/eye irritation: Category 1

Specific target organ toxicity,

Single exposure; Narcotic effects: Category 3

#### Label elements:







Signal word: Danger

#### **Hazard statements**

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

## SECTION 2: Hazard(s) identification (continued)

H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

#### **Precautionary statements**

Prevention:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P233 Keep container tightly closed.
P260 Do not breathe mist/vapors/spray.

P264 Wash hands, arms, face and exposed skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this products.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection.

Response:

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P361+P364 Take off immediately all contaminated clothing and wash it before reuse.

Storage:

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents / container in accordance with local / regional / national /

international regulations.

Hazard(s) not otherwise Classified (HNOC): Not classified.

#### **SECTION 3: Composition/information on ingredients**

## Substance/Mixtures:

Chemical name	CAS No.	Concentration (%)
Water	7732-18-5	50-65
Citric acid	77-92-9	15-30
Fluorosilicic acid	16961-83-4	5-15
Ammonium bifluoride	1341-49-7	5-15
Dipropylene glycol monomethyl ether	34590-94-8	0-5

#### Section 4: First-aid measures

#### **Description of first aid measures**

**General advice:** Remove victims from the danger zone without endangering your own safety. Remove contaminated clothing (including underwear and shoes) immediately.

**Inhalation:** Bring accident victims out into the fresh air. If not breathing, give artificial respiration. WARNING: It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. If patient has difficulty breathing, administer oxygen, keep the patient calm and warm. In case of unconsciousness place patient stably in side position for transportation. Call a physician immediately.

**Skin contact:** Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before re-use. After contact with small amounts get medical attention if any discomfort or irritation continues. For large amounts, obtain medical attention.

**Eye contact:** Immediately flush eyes with gentle but large stream of water or eye wash solution for at least 15 minutes, lifting lower and upper eyelids occasionally. If possible remove any contact lenses and continue to wash. Call a physician, immediately.

**Ingestion:** If swallowed, rinse mouth with water (only if the person is conscious). Never give anything by mouth to an unconscious person. Loosen tight clothing such as a collar, tie, belt or waistband. DO NOT induce vomiting unless directed to do so by medical personnel. Call a physician, immediately.

### Most important symptoms/effects, acute and delayed:

**Notes to physician:** The severity of the symptoms described will vary dependent on the concentration and the length of exposure. The substance is toxic to the nervous system, lungs, and mucous membranes.

**Inhalation:** Excessive inhalation of vapors can cause nasal and respiratory damage, dizziness, weakness, fatigue, nausea, vomiting, diarrhea, and possible unconsciousness.

**Ingestion:** May cause sore throat, abdominal pain, nausea, and severe burns of the mouth, throat, and stomach. May affect the urinary system, liver, and blood. Severe exposures can lead to shock, circulatory collapse, and death.

**Skin contact/Skin irritation:** Contact with vapors and liquid are corrosive to the skin, and may cause permanent skin damage, redness, pain and severe skin burns.

**Eye contact:** Liquid and vapors are corrosive to the eyes. May cause redness, pain, blurred vision, eye burns, and permanent eye damage. Brief contact of the liquid can cause severe eye burns and possible blindness. May cause corneal damage, conjunctivitis, and/or lachrymation.

#### Indication of immediate medical attention and special treatment needed, if necessary:

Cases of eye contact and ingestion should be treated immediately. Have facilities in place to wash skin and eyes in case of exposure. Ingestion damages mucous membranes and tissues of gastro-intestinal tract.

#### **SECTION 5: Fire-fighting measures**

**Suitable extinguishing media:** In case of fire use water, carbon dioxide, or foam extinguishing media. Applying water to this product may cause splattering of this corrosive powder. Water spray on large fires may be ineffective but may be used to keep fire-exposed containers cool. If water is used, use in abundance to control heat.

**Unsuitable extinguishing media:** Do not use water jet as this can spread the fire. Do not use carbon dioxide in enclosed spaces with insufficient ventilation.

**Specific hazards arising from the chemical:** Burning releases; carbon/nitrogen oxides, and hydrogen fluoride. In the event of fire and/or explosion do not breathe fumes. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. Move containers from fire area if you can do so without risk. Product containers can melt in the heat of a fire. Packaging materials will be combustible and provide fuel for the fire.

**Special protective equipment and precautions for fire-fighters:** In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode. During fire-fighting respirator with independent air-supply and airtight garment is required. Fight fire in early stages if safe to do so. Provide ventilation and be wary of hydrogen generation upon reactions with some metals.

## **SECTION 6: Accidental release measures**

**Personal precautions, protective equipment and emergency procedures:** Ventilate area of leak or spill. Ensure adequate ventilation/exhaust extraction. Put on protective equipment (see Section 8). Have emergency procedures in place for treating spillages, evacuating the area and informing the emergency services if necessary. Restrict access to the area until the spillage is treated, if large amounts of vapors are produced that will be hazardous to others, evacuate the area. Non-emergency personnel should be kept away from the area of spillage. Avoid ingestion, inhalation of vapors and contact with skin and eyes.

**Environment precautions:** Avoid unauthorized discharge of product into sanitary sewers system or to the environment. Clean up any spillages immediately; prevent material from spreading and entering drains or sewage systems. Large spillages or uncontrolled discharge to water systems must be alerted to the Environmental Agency or other regulatory body. If the product has entered a foul drain or sewage system in significant amounts to cause a hazard then the local water treatment company must be informed.

Methods and materials for containment and cleaning up: Contain and recover liquid when possible. Small spillages should be absorbed with an inert, non-combustible absorbent. Large Spillages: Dam and absorb spillages with sand, earth or other inert material. Fit drain covers where they are available if the spillage is likely to enter the drainage system. Collect spillage in containers, seal securely and deliver for disposal according to local regulations. Containers with collected spillage must be properly labeled with correct contents and hazard symbol. Flush area clean with lots of water. Be aware of potential for surfaces to become slippery. Ventilate area and allow drying before allowing access. Wash thoroughly after dealing with a spillage.

Reference to other sections: Refer to sections 8 and 13 for additional information.

#### **SECTION 7: Handling and storage**

Precautions for safe handling: Keep in a closed container and protect from physical damage. Store in a cool, dry, and ventilated area. Keep away from sources of heat, moisture, incompatibilities, and away from direct sunlight. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product. Do not wash out container and use it for other purposes. Avoid ingestion and/or inhalation of any vapors/mists if produced, and any contact with skin or eyes. Wash at the end of each work shift, before eating, drinking, smoking and using the toilet. Do not eat, drink or smoke when handling. Remove contaminated clothing/footwear/equipment before entering eating areas or places that would expose others to the product. Avoid spilling the product. Do not use in areas close to drainage systems unless measures are in place to prevent access of product. Ensure emergency procedures are in place to treat spillages and cope with other situations such as evacuation. Provide eye washing and skin washing facilities, when handling large amounts a safety shower is recommended.

**Conditions for safe storage, including any incompatibilities:** Store in closed original container at temperatures between 40°F and 80°F. If the product is transferred to another container, this should be made of a compatible material to the original container. Store away from heat, direct sunlight and moisture. Store in a stable situation to avoid spillages. It is advisable to store in a bunded area or use other protective measures such as a sump pallet or storage tray.

**Keep away from:** strong acids, oxidizing agents and reactive metals (i.e., aluminum, tin, zinc, and their alloys).

**Suitable packaging material:** stainless steel, nickel, polyethylene, polypropylene, glass and stoneware/porcelain.

Non-suitable packaging material: lead, galvanized iron, aluminum, copper, zinc, bronze, and tin.

## SECTION 8: Exposure control/personal protection

#### **Control Parameters**

Occupational exposure limits

**US.OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)** 

#### U.S. ACGIH Threshold Limit Values

Chemical Name	CAS-No.	Value	Control parameters
Ammonium bifluoride	1341-49-7	TWA	2.5 mg/m <sup>3</sup>
Dipropylene glycol monomethyl ether	34590-94-8	PEL	600 mg/m <sup>3</sup>
Fluorosilicic acid	16961-83-4	TWA	2.5 mg/m <sup>3</sup>

### Appropriate engineering controls:

## **Ventilation System:**

A system of local and/or general exhaust is recommended to keep employee exposures below the defined exposure limit requirements or guidelines. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, Industrial Ventilation, A Manual of Recommended Practices, most recent edition for details.

### **SECTION 8: Exposure control/personal protection (continued)**

### Individual protection measures, such as personal protective equipment (PPE)

**Eye Protection:** Use chemical safety goggles and/or full face shield where dusting or splashing of solutions is possible. Maintain eye wash fountain and guick-drench facilities in work area.

**Skin Protection:** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Hand protection:** Wear protective gloves. Butyl rubber, rubber (natural, latex), nitrile, polyvinyl chloride (PVC). Be aware that latex gloves can produce an allergic reaction in sensitive individuals. Gloves should have a breakthrough time sufficient for the amount of handling but allow dexterity for safe movement and handling. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Gloves showing signs of degradation should be changed to avoid skin contamination. Be aware that the liquid may penetrate the gloves. Frequent change is advisable.

**Personal Respirators (NIOSH Approved):** Wear suitable respiratory protection when vapors or mists are produced if the Workplace Exposure Limit is exceeded and there is insufficient ventilation or extraction. For emergencies or instances where the exposure levels are not known, use a full face piece positive-pressure, air-supplied respirator. Respirator must be fitted with a cartridge suitable for the chemical of concern. Consult with the supplier as to the compatibility of the equipment with the chemical of concern. CAUTION: Air purifying respirators do not protect the user in oxygen deficient atmospheres, use air supplied system.

**Thermal Hazards:** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations: Wash hands, change out of clothes as soon as possible.

Wash clothes. Shower or bathe as soon as possible.

Other protective measures: Have an eye bath and safety shower close by.

## **SECTION 9: Physical and chemical properties**

Appearance: Liquid
Colour: White water
Odour: No odour

Odour Threshold: No data available

**pH**: 0-2

Melting point/range:No data availableBoiling point/range:No data availableFlash point:No data availableEvaporation rate:No data availableFlammability (solid, gas):No data available

Upper/lower flammability of explosive limits: No data available

Vapour pressure (mm Hg):No data availableVapour density (Air=1):No data availableRelative density:No data available

Solubility(ies): Excellent

Partition coefficient (n-octanol/water): No data available

Auto-ignition temperature: No data available
Decomposition temperature: No data available
Viscosity, dynamic: No data available
No data available
Contains fluorides

### **SECTION 10: Stability and reactivity**

**Reactivity and/or chemical stability:** If stored and handled in accordance with standard industrial practices no hazardous reactions are known. Refer to section 7 for proper conditions.

**Possibility of hazardous reactions:** Hazardous polymerization will not occur.

**Conditions to avoid:** Avoid heat, freezing, direct sunlight, and moisture. Avoid storage with incompatible materials. Avoid storage in freezing conditions. Avoid storage near unprotected drainage systems. Avoid storage in an unstable manner or in a situation that would result in exposure to the product. It is advisable to store the product within some form of containment to prevent spillages reaching drainage systems. Do not allow the storage container to be left exposed to the atmosphere.

**Incompatible materials:** Strong acids, oxidizing agents and reactive metals (i.e., aluminum, tin, zinc, and their alloys).

**Hazardous decomposition products:** Refer to section 5 in case of a fire. No hazardous decomposition if stored and handled correctly.

## **SECTION 11: Toxicological information**

**Acute toxicity:** Toxicological testing has not been conducted with this material. The toxicology information listed below is based on the components of this material.

Category 3- Oral/Dermal: Harmful if; swallowed/in contact with skin.

Citric acid - Acute Toxicity Estimate (ATE)		
Oral LD <sub>50</sub>	Dermal LD <sub>50</sub>	
5,400 mg/kg (Rat)	> 2,000 mg/kg (Mouse)	

Dipropylene glycol monomethyl ether - Acute Toxicity Estimate (AT		
Oral LD <sub>50</sub>	Dermal LD <sub>50</sub>	
> 5,000 mg/kg (Rat)	9,510 mg/kg (Rabbit)	

F	<b>luorosilicic acid</b> – Acute Toxicity Estimate (A	TE)
Oral LD <sub>50</sub>	LC <sub>50</sub> (Lethal Concentrations)	Oral LD <sub>50</sub>
125 mg/kg (Rat)	1.11 mg/L (Rat) 1 h	200 mg/kg (Guinea pig)

**Skin Corrosion/irritation:** Category 1B: Causes severe skin burns and eye damage.

**Serious eye damage/irritation:** Category 1: Causes serious eye damage.

**Respiratory or skin sensitization:** Classification not possible.

Germ cell mutagenicity: Classification not possible.

**Carcinogenicity:** Classification not possible. **Reproductive toxicity:** Classification not possible.

### **SECTION 11: Toxicological information (continued)**

Specific Target Organ Toxicity - Single Exposure: Category 3: Narcotic effects.

Specific Target Organ Toxicity - Repeated Exposure: Classification not possible.

Aspiration hazard: Classification not possible.

## SECTION 12: Ecological information

**Toxicity:** Do not allow to escape into waterways, wastewater or soil. Eco toxicological studies of the product are not available. Please find below the data available to us from raw materials:

**Aquatic ecotoxicity:** Chronic: Category 2: Toxic to aquatic life with long lasting effects.

Dipropylene glycol monomethyl ether					
LC <sub>50</sub> /96 h, static	LC <sub>50</sub> /48 h, static	LC <sub>50</sub> /96 h, semi-	ErC <sub>50</sub> /96 h, static	Flow-through test,	
test	test	static test	test	22 d	
> 1,000 mg/L	1,919 mg/L	> 1,000 mg/L	> 969 mg/L (green	NOEC: > 0.5 mg/L	
(guppy)	(waterflea)	(shrimp)	algae)	LOEC: > 0.5 mg/L	
		. ,,	- ,	(waterflea)	

Citric a	cid
LC <sub>50</sub> (Leuciscus idus melanotus): 48 h	Static test (Daphnia magna): 24 h
440 mg/L	1,535 mg/L

	Fluorosi	licic acid	
LC <sub>50</sub> (Fish) 96 h	EC <sub>50</sub> (Crustaceans) 48 h	EC <sub>50</sub> (Algae) 96 h	EC <sub>50</sub> (Crustaceans) 96 h
Salmo Gairdneri	Daphnia Magna	Scenedesmus Specie	Mysidopsis Bahia
51.0 mg/L (as fluorides)	97 mg/L (as fluorides)	43 mg/L	10.5 mg/L (as fluorides)

Persistence and degradability: No data available for this product.

**Bioaccumulative potential:** No data available for this product.

**Mobility in soil:** No data available for this product.

**Other adverse effects:** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

#### **SECTION 13: Disposal considerations**

#### General information:

Do not allow unauthorized disposal to the environment. If operators are exposed to vapors during the disposal process then suitable respiratory protection should be worn. All other personal protective equipment as described in section 8 should be worn.

#### Disposal methods:

Avoid unauthorized disposal. Do not dump into any sewers, on the ground, or into any body of water. All disposal practices must be in compliance with federal, state/provincial and local laws and regulations. For a small spill, immediately hose down with cool water and dispose to drain. For a large spill, dike, collect and contact local authorities about disposal.

## **SECTION 14: Transport information**

UN Number: UN 1760

**UN Proper Shipping Name:** CORROSIVE LIQUID, N.O.S.(FLUOROSILICIC ACID)

Transport hazard class(es):

**DOT Hazard Class:** 8

**DOT Subsidiary Hazard Class:** Not Available CORROSIVE

Packing group, if available:

**Environmental Hazards:**Special precautions for user:
Not available

Transport in bulk according to Annex II of MARPOL 73/783 and the IBC Code 3: Not applicable

## **SECTION 15: Regulatory information**

Safety, health and environmental regulations/legislation specific for the substance or mixture

The ingredients of this product are listed on the TSCA inventory.

**Other Regulations:** OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

#### SARA 302 Components/ SARA 313 Components:

SARA 302: This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65) and/or CERCLA (40 CFR 302.4).

#### SARA 311/312 Tier II Hazard Ratings:

Component	CAS#	Fire	Reactivity	Pressure	Immediate	Chronic
Component	<b>ΟΛΟ</b> π	Hazard	Hazard	Hazard	Health Hazard	Health Hazard
Ammonium bifluoride	1341-49-7	No	No	No	Yes	No
Citric acid	77-92-9	No	No	No	Yes	No
Hydrofluorosilicic acid	16961-83-4	No	No	No	Yes	No
Dipropylene glycol monomethyl	34590-94-8	Yes	No	No	No	Yes
ether						

## **SECTION 15: Regulatory information (continued)**

The following components appear on one or more of the following state hazardous substance lists:

Component	CAS#	CA	FL	MA	MN	NJ	PA
Ammonium bifluoride	1341-49-7	No	No	Yes	No	Yes	Yes
Citric acid	77-92-9	No	No	No	No	Yes	Yes
Dipropylene glycol monomethyl ether	34590-94-8	No	No	Yes	No	Yes	Yes
Hydrofluorosilicic acid	16961-83-4	No	No	Yes	No	Yes	Yes

## California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

# SECTION 16: Other information including date of preparation or last revision

Chemical State: LiquidIssue Date:03-21-2018Chemical Type: MixtureRevision Date:01-31-2020

Version #: 02

2	Health
0	Flammability
1	Physical Hazard
С	Personal Protection

To the best of our knowledge, the information contained herein is accurate. However, neither U.N.X. Incorporated nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may represent unknown hazards and should be used within caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.