



LIGHTSTRIP


Aluminum Profile - Raceway Suspended


High-quality 6063 thin-wall aluminum, light-weight design featuring hidden cables and suspended by cables from the ceiling. The raceway space is enough to conceal seamless connectors with bottom feed and the general male/female connectors. It is superb for the facade where tidiness is required and the scenarios that lack of space for wiring. Please refer to install manual for proper installation practices.


ORDER CODE


MOUNTING PROFILE TYPE	STANDARD LENGTH	PROFILE	COLOR
A9 = Aluminum Raceway Suspended	3 = 19.68in (500mm) 5 = 39.37in (1000mm) 6 = 78.74in (2000mm)	I = LightStrip	1 = Standard

DIMENSIONS










Tolerance: ± 0.01in (0.3mm)

NOTES: 1. 2-L1 refers to two of symmetric L1 in each piece of profile. 2. (N-1)-L2 refers to (N minus one) of symmetric L2 in each piece of profile. "N" hereby stands for its corresponding "Hole Number" in the below table



ORDER CODE	LEGACY ORDER CODE	STANDARD LENGTH
A9-3-I-1	CH15RAL0M5SR	19.68in (500mm)
A9-5-I-1	CH15RAL01MSR	39.37in (1000mm)
A9-6-I-1	CH15RAL02MSR	78.74in (2000mm)

