Shelving

The "ai" branded shelving units have been trusted in the market for over 40 years, renowned for durability, stability, and quick, easy assembly. Their attractive, polished design makes them suitable not only for cold rooms but also for food store displays, professional kitchens, processing areas, and much more. Detailed information on each unit is available in their respective datasheets. While load capacity and intended use vary, all models share carefully selected materials, exclusive profile designs, and high-quality craftsmanship.



Assembly Video - Corner Composition

Choosing the Right Shelving

LIGHT STRONG Ideal for most cold room storage needs Specifically designed for heavyduty storage requirements Supports up to 240 kg per shelf Supports up to 400 kg per shelf Depths up to 600 mm Specifically designed for heavyduty storage requirements

LIGHT 1



STRONG 2



DUNNAGE RACKS

3

Usually used to keep crates off the floor, these racks are versatile enough for a range of other uses. They can be custom-sized to fit any shelf model in our Light and Strong lines. Please check the relevant datasheets for technical details.



Shelving aiguidovie.it

LIGHT Shelving

1



Perfect for any cold room

Designed with attention to detail, this versatile product combines high modularity, excellent quality, and truly competitive pricing.

Key Features



Custom-made to size. Highly modular, length increments every ~ 30 mm

AL+PP

Anodised aluminum alloy frame and polypropylene copolymer shelves



Rust-proof, with a 10-year warranty against corrosion from water and humidity



Suitable for use in food environments



Height-adjustable feet



Designed in compliance with current European safety regulations and standards



Stable and sturdy, requiring no anchors or stabilising crossbars. No plastic joints



Open-faced corner design to maximise storage space



Tested for use in cold rooms down to -30°C



Easy and quick assembly with a snap-fit system—no special tools needed

HACCP

Easy to clean and sanitise according to HACCP standards




Removable polypropylene shelves, dishwasher safe




Load capacity certified according to Eurocode 9: up to 240 kg per shelf

Configuration Options



Standard Heights and Optimal Layouts

Measurements are in millimetres




- * Shelf spacing can be adjusted during assembly, with predrilled holes every 150 mm
- * Custom heights available on request



Dimensions Overview


Depth Measurements

Measurements are in millimetres



Unit Lengths

Measurements are in millimetres






Lengths available every ~ 30 mm → more than 28 lenghts

Configuration Lengths



Units can be combined to reach any desiderd length by eliminating two central uprights



Shelving aiguidovie.it

Shelves



Gridded polypropylene shelves removable and dishwasher-safe.

- M Single-grid version, available in depths of 300, 400, and 450 mm (highlighting easy removability)
- Double-grid version, for 600 mm depth, with a central frame reinforcement underneath to increase the load capacity

Also available with a smooth transparent plastic cover (PETG), which rests on the shelves and fits between the uprights. This cover can be easily retrofitted to previously supplied shelving.



M-I Shelf with AISI 304 stainless steel cover



Hanging shelves for optional use on the upper part of the shelving:

2 oval bars 3 oval bars 4 oval bars

2 Triangular Caps



1232305M PVC end caps for closing the top of "T" -shaped Light shelving uprights





123**2307M** Snap-in pin and clip system for Light shelving

4 Slot Covers



123**2315** Complimentary covers for unused slots in uprights, supplied for aesthetic and safety reasons

5 Corner Hooks



123**2310M** Pair of hooks for gridded polypropylene shelves ("M")

33

123**2310MI** Pair of hooks for stainless steel-covered shelves ("MI")

6 Feet



123**2308M** Adjustable feet for "T"-shaped Light shelving uprights

7 "T"-shaped Upright



"T"-shaped 40x45x2,5 mm upright for Light shelving

10223155M "T"-shaped upright h 1550 mm
10223165M "T"-shaped upright h 1650 mm
10223185M "T"-shaped upright h 1850 mm
10223205M "T"-shaped upright h 2050 mm
1022301M "T"-shaped upright - different measurements

The codes refer to the uprights only (accessories are not included)

Shelving aiguidovie.it

STRONG Shelving

2



Ideal for heavy loads

Designed to meet high load demands, this shelving system supports standard spans up to **2000 mm in length** and **900 mm in depth** for each single unit.

Key features



Custom-made to size. Lengths: every ~30 mm (Q shelves) and every 90 mm (P shelves)



Wide range of standard depths: 300, 400, 450, 600, 700, 750, 800, 850, and 900 mm

AL+PP

Anodised aluminum alloy frame and polypropylene copolymer shelves



Rust-proof, with a 10year warranty against corrosion from water and humidity



Suitable for use in food environments



Designed in compliance with current European safety regulations and standards



Stable and sturdy, requiring no anchors or stabilising crossbars. No plastic joints



Open-faced corner design to maximise storage space



Tested for use in cold rooms down to -30°C



Height-adjustable feet



Easy and quick assembly with a snap-fit system—no special tools needed

НАССР

Easy to clean and sanitise according to HACCP standards




Removable polypropylene shelves, dishwasher safe




Load capacity certified according to Eurocode 9: up to **400 kg for shelf**

Configuration Options



Standard Heights and Optimal Layouts

Measurements are in millimetres




- * Shelf spacing can be adjusted during assembly, with predrilled holes every 150
- * Custom heights available on request



Dimensions Overview

Depth Measurements for P and Q Shelves

Measurements are in millimetres



To calculate max overall depth proceed as follows:

P SHELF: add 65 mm

Q SHELF: add 62 mm up to depth 450 mm and 33 mm from 600 mm onwards

Unit Lengths

Measurements are in millimetres



Q SHELF Lengths every \sim 30 mm from 632 to 2019 mm

More than 28 lengths available




P SHELF Lengths every ~ 90 mm from 640 to1990 mm More than 15 lengths available

Configuration Lengths



Units can be combined to reach any desiderd length by eliminating two central uprights




Shelving aiguidovie.it

1 Shelves



Shelves consist of removable polypropylene slat or gridded shelves, all dishwasher-safe.

P Single-slat version, available in depths of 300, 400, and 450 mm (highlighting easy removability)



measurements in millimetres

P **Double-slat version**, available in depths of 600, 700, 750, 800, 850 e 900 mm with a central frame reinforcement underneath to increase the load capacity





Q shelves are available also with a smooth transparent plastic cover (PETG), which rests on the shelves and fits between the uprights. This cover can be easily retrofitted to previously supplied shelving



P-I/Q-I Shelf with AISI 304 stainless steel cover

Hanging shelves for optional use on the upper part of the shelving:



134___P/Q 2 oval bars

5___P/Q 3 oval bars

P/Q 4 oval bars

2 Triangular Caps



STRONG SHELVING

3 Shelf Locking



123**2307P** Snap-in pin and clip system for Strong shelving

4 Slot Covers



123**2315** Complimentary covers for unused slots in uprights, supplied for aesthetic and safety reasons

5 Corner Hooks



123**2310P** Pair of hooks for slatted polypropylene shelves ("P")



123**2310PI** Pair of hooks for stainless steel-covered shelves "PI"



123**2310Q** Pair of hooks for gridded polypropylene shelves ("Q")

6 Feet



123**2308P** Adjustable feet for "T"-shaped Strong shelving uprights

7 "T"-shaped Upright

