

Serie / Series / Série **SPC**

MODELO MODELE MODÈLE				
	SPC501	SPC501B	NEW SPC1470	NEW SPC1470B
Precio Price Prix				
Medidas Measures [mm] Mesures 	687 x 728 x 2003 mm.	687 x 728 x 2003 mm.	1475 x 700 x 1187 mm.	1475 x 700 x 1187 mm.
Temperatura Temperature [°C] Température	+0°C/-8°C			
Clase Climática Climatic class [°C] Classe climatique	4 / 38°C			
Tensión/Frecuencia Electrical data Tension électrique	230V/1ph/50Hz			
Controlador Controller Régulateur	Digital / Digital / Électronique IP65			
Material Material [EXT/INT] Matériel	Int: acero Inox AISI 430 / Ext: acero Inox AISI 304 o Acero pintado epoxy [B] Int: Stainless Steel AISI 430 / Ext: Stainless Steel AISI 304 or Steel epoxy paint [B] Int: Stainless Steel AISI 430 / Ext: Acier Inox AISI 304 ou Acier peinture époxy [B]			
Espesor Thickness [mm] Épaisseur	50			
Aislamiento Isolation Isolation	40kg/m³ / Free CFC's / Zero ODP-GWP			
Capacidad Capacity [L] Capacité	500		440	
Puertas Doors Portes	1		2	
Nº Estantes Shelving N° d' étagères	5 [560x480]		6 [545x365]	
Sistema de frío Cooling System Système de froid	Forzado / Forced air / Ventilé			
Desescarche Defrost Dégivrage	Gas caliente / Hot gas / Gaz chaud			
Expansión Expansion Expansion	Capilar / Capillary / Capillaire		Válvula de expansión termostática / Thermostatic expansion valve / Détendeur thermostatique	
Potencia Power [W] Puissance	629		629	
Potencia frig. Cooling capacity [W A -10/-30°C] Puissance Frig.	567		567	
Consumo Consumption [kWh/24h] Consommation	6.32		-	
Clase energética Energy class Classe Énerg.	C		-	
Refrigerante Refrigerant Gaz	R-290			
Opcional Optional Options	Parrilla / Wire shelf / Grille métallique [502x119]			



1

