


## VIVID WAVE: SILICONE - 24V

Indoor & Outdoor Rated Linear Flex Profile - Direct DMX-Pixel



### PROFILE CAPABILITIES



### CERTIFICATIONS & FEATURES\*



### Fixture Order Code

E	A				B			
INPUT CONNECTORS	SERIES	MATERIAL	PROFILE	BENDING	JACKET/BASE + LENS COLOR	LED FUNCTION***	LED COLOR	CHIP + CRI
See Page 6 to select input connector	V = Vivid	1 = Silicone	F = Wave	1 = Side 2 = Top	W = White + Diffused	7 = Direct-DMX-Pixel All Colors 8 = Direct-DMX-Pixel-RGBW 2700K 3000K 4000K 2700K 3000K 4000K	H = 2200K J = 2700K L = 3000K M = 3500K N = 4000K Q = 5700K S = RGB U = 2200-5700K	1 = Epistar SMD LED Chip RGB 2 = Epistar SMD LED Chip + CRI80 Whites Tunable White RGBW

C	D	E	F	G
---	---	---	---	---

POWER	VOLTAGE + CIRCUIT TYPE**	ORDER UNIT LENGTH	OUTPUT CONNECTOR	MOUNTING PROFILE	MOUNTING ACCESSORIES	POWER SUPPLIES & CONTROLS:
E = 2.74W/ft (9W/m) RGB G = 3.66W/ft (12W/m) Whites Tunable White RGBW	2C = 24V DC CC	I = 6.56in (166.7mm) (14LEDs) Whites RGB RGBW Q = 6.56in (166.7mm) (28LEDs) Tunable White	See Page 6 to select output connector	See Page 9 to select mounting profiles	See Page 15 to select accessory	By Others By GLLS

\*Maximum IP and IK ratings achievable with appropriate accessories, and cable diameter: silicone direct DMX = 0.27in (6.8mm). \*\*The Constant Current (CC) Integrated Circuit extends max run length. Do not use a CC power supply, as it may cause damage. \*\*\*DMX fixtures ship with default addresses. For custom addressing, provide required addresses at ordering or adjust on-site with an address writer. Verify your controller supports the UCS512 IC, and confirm all requirements with our sales or quoting team before ordering.



# VIVID WAVE: SILICONE - 24V

Indoor & Outdoor Rated Linear Flex Profile - Direct DMX-Pixel



A

## MECHANICAL

### ASSEMBLY

Fixtures are carefully assembled using high-quality components to ensure durability and performance. Each unit is built to meet strict specifications, with attention to electrical safety, thermal management, and optical alignment.

### OVERALL & CUTTING LENGTHS

Fixtures feature defined overall lengths and specific cutting increments for easy customization. Cutting must be done at marked points to maintain proper function and consistent light output.

### JACKET COLOR

The white jacket with diffused white lens covers provide a clean, uniform appearance while softening light output for reduced glare. It enhances visual comfort and delivers smooth, even illumination ideal for architectural and display applications.

### BENDING RADIUS

Do not bend smaller than allowed minimum bend diameter, or may cause damage to the light & void warranty.

## OPERATION

### LIGHT ENGINE

Direct DMX light engines receive DMX512 signals for precise, real-time control of brightness, color, and effects. Each unit is addressable, making them ideal for complex architectural or stage lighting setups.

### ELECTRICAL

Designed to meet UL, CE, and RoHS standards, they feature overload, overvoltage, and short-circuit protection, along with low EMI and efficient thermal management for safe, reliable operation.

### DIMMING

Direct DMX 24V DC systems use DMX512 for smooth, flicker-free dimming with 8-bit or 16-bit resolution. They support standalone DMX controllers, DMX software, and networked systems like Art-Net or sACN for flexible lighting control.

## GENERAL

### WARRANTY

Limited 10-Year Warranty against defects in materials and manufacturing. Coverage applies to properly installed and maintained products. Damage from misuse or improper installation is not covered. GLLS may repair, replace, or issue credit for eligible claims.

### LUMEN MAINTENANCE

GLLS static lighting fixtures are tested to IES LM-84 and projected with IES TM-28 to ensure consistent lumen maintenance. Fixtures are designed to retain at least 70% of their initial brightness (L70) over a 10-year lifespan when properly installed and operated.

### CERTIFICATION

Tested to UL2108 Class 2 by Underwriters Laboratory for use in the USA and Canada. Exceeds ANSI C78.377A, CE, and RoHS standards. Must be used under Class 2 ratings to maintain certification.

UL Certificate #: E347880

Report Reference #: E347880-20130503

## TESTING

### OPTICAL TESTING

TEST	RESULTS
Spectrum Analysis	IES LM 79 (Lumen, CCT, CRI, XY, SDCM, Wavelength)
Photometric Distribution	IES LM 79
Lumen Maintenance & Lifetime	IES LM 84 & IES TM28

### TEMPERATURE TESTING

TEST	RESULTS
Normal Temperature Test	UL1598 & UL2388 & IEC60598-1 & IEC60598-2-21
Abnormal Operation Test	UL1598 & UL2388 & IEC60598-1 & IEC60598-2-21

### ENVIRONMENTAL TESTING

TEST	RESULTS
Salt Water Immersion	IEC60598-1, Salinity 4%
Salt Spray Test	IEC60068-2-11
Outdoor Exposure	Manufacturer-defined
Flame Resistance	UL94
UV Exposure	ASTMG 154, ISO 4892-3, UVA @ 340nm & 55
IPX8	EN 60598-1: 2015+A1:2018 Clause 9.2.2 & 9.2.8
Temperature Shock(Silicone)	Manufacturer-defined, -40°C - 60°C (typical temperature range)
Constant Temperature	Manufacturer-defined
12mm Needle Flame Test (Silicone)	IEC60695-11-5
650° Glow-wire Test (Silicone)	IEC60695-2-10

### DURABILITY TESTING

TEST	RESULTS
Bending Test	Manufacturer-defined, 500 cycles
Tensile Test	Manufacturer-defined, > The weight of light in max.
Twist Test	Manufacturer-defined, >200 cycles
Ball Impact	UL1598 & UL2388 & IEC60598-1 & IEC60598-2-21
IK	IEC62262



GLLS.COM | 1-888-580-6366

GLLS reserves the right to make any design changes for continuous improvement which will not affect the overall appearance or performance. REV. 20251230

# VIVID WAVE: SILICONE - 24V

Indoor & Outdoor Rated Linear Flex Profile - Direct DMX-Pixel



**B**

## LED COLORS



## Fixture Specifications & Optical Parameters - White Jacket + Diffused Lens - Side Bend

Color	LED Chip + CRI	LED Count	1 Connector Full/Dynamic*	2 Connectors Full/Dynamic*	Fixture Color Tolerance**	Wavelength/CCT	LED CRI	LED Color Tolerance	Lumen Count	Legacy Order Code
2200K	Epistar SMD LED Chip + CRI80	25 LEDs/ft (84 LEDs/m)	22.9ft (7m) / Not Recommended	45.9ft (14m) / Not Recommended	3 SDCM	2238 ± 66K	82-87	2.3SDCM	159lm/ft (520lm/m)	SF16E1015DE22K24DC
2700K	Epistar SMD LED Chip + CRI80	25 LEDs/ft (84 LEDs/m)	22.9ft (7m) / Not Recommended	45.9ft (14m) / Not Recommended	3 SDCM	2725 ± 85K	82-87	2.3SDCM	159lm/ft (520lm/m)	SF16E1015DE27K24DC
3000K	Epistar SMD LED Chip + CRI80	25 LEDs/ft (84 LEDs/m)	22.9ft (7m) / Not Recommended	45.9ft (14m) / Not Recommended	3 SDCM	3045 ± 105K	82-87	2.3SDCM	159lm/ft (520lm/m)	SF16E1015DE30K24DC
3500K	Epistar SMD LED Chip + CRI80	25 LEDs/ft (84 LEDs/m)	22.9ft (7m) / Not Recommended	45.9ft (14m) / Not Recommended	3 SDCM	3465 ± 245K	82-87	2.3SDCM	159lm/ft (520lm/m)	SF16E1015DE35K24DC
4000K	Epistar SMD LED Chip + CRI80	25 LEDs/ft (84 LEDs/m)	22.9ft (7m) / Not Recommended	45.9ft (14m) / Not Recommended	3 SDCM	3985 ± 150K	82-87	2.3SDCM	159lm/ft (520lm/m)	SF16E1015DE40K24DC
5700K	Epistar SMD LED Chip + CRI80	25 LEDs/ft (84 LEDs/m)	22.9ft (7m) / Not Recommended	45.9ft (14m) / Not Recommended	3 SDCM	5669 ± 305K	82-87	2.3SDCM	159lm/ft (520lm/m)	SF16E1015DE57K24DC
2200K; 5700K	Epistar SMD LED Chip + CRI80	50 LEDs/ft (168 LEDs/m)	19.6ft (6m) / Not Recommended	39.4ft (12m) / Not Recommended	3 SDCM	2238 ± 66K; 5669 ± 305K	82-87; 82-87	2.3SDCM; 2.3SDCM	76lm/ft (250lm/m); 85lm/ft (280lm/m)	SF16E1015DEPDW24DC
R; G; B; R+G+B	Epistar SMD LED Chip	25 LEDs/ft (84 LEDs/m)	22.9ft (7m) / Not Recommended	45.9ft (14m) / Not Recommended	N/A	618-624nm; 522-530nm; 468-474nm; N/A	N/A	3nm; 3nm; 3nm; N/A	15lm/ft (50lm/m); 49lm/ft (160lm/m); 9lm/ft (30lm/m); 73lm/ft (240lm/m)	SF16E1015DERGB24DC
R; G; B; 2700K	Epistar SMD LED Chip + CRI80	25 LEDs/ft (84 LEDs/m)	19.6ft (6m) / 32.8ft (10m)	39.4ft (12m) / 65.6ft (20m)	N/A	618-624nm; 522-530nm; 468-474nm; 2725 ± 145K	N/A; 82-87	3nm; 3nm; 3nm; 2.3SDCM	15lm/ft (50lm/m); 49lm/ft (160lm/m); 9lm/ft (30lm/m); 40lm/ft (130lm/m)	SF16E1015DER2724DC
R; G; B; 3000K	Epistar SMD LED Chip + CRI80	25 LEDs/ft (84 LEDs/m)	19.6ft (6m) / 32.8ft (10m)	39.4ft (12m) / 65.6ft (20m)	N/A	618-624nm; 522-530nm; 468-474nm; 3045 ± 140K	N/A; 82-87	3nm; 3nm; 3nm; 2.3SDCM	15lm/ft (50lm/m); 49lm/ft (160lm/m); 9lm/ft (30lm/m); 40lm/ft (130lm/m)	SF16E1015DER3024DC
R; G; B; 4000K	Epistar SMD LED Chip + CRI80	25 LEDs/ft (84 LEDs/m)	19.6ft (6m) / 32.8ft (10m)	39.4ft (12m) / 65.6ft (20m)	N/A	618-624nm; 522-530nm; 468-474nm; 3985 ± 275K	N/A; 82-87	3nm; 3nm; 3nm; 2.3SDCM	15lm/ft (50lm/m); 49lm/ft (160lm/m); 9lm/ft (30lm/m); 40lm/ft (130lm/m)	SF16E1015DER4024DC

\* Run length is based on a static full load with voltage drop calculated using a 0.3 m (0.98 ft) cable with silicone seamless connectors, excluding connector length—refer to specifications for details. Due to fragility, five-wire fixtures are not recommended to exceed 16.4ft (5m). \*\*Silicone products maintain  $\leq 3$  SDCM within a single production run and  $< 5$  SDCM between production runs.



GLLS.COM | 1-888-580-6366

GLLS reserves the right to make any design changes for continuous improvement which will not affect the overall appearance or performance. REV. 20251230

# VIVID WAVE: SILICONE - 24V

Indoor & Outdoor Rated Linear Flex Profile - Direct DMX-Pixel



**B**

## LED COLORS



## Fixture Specifications & Optical Parameters - White Jacket + Diffused Lens - Top Bend

COL-OR	LED CHIP + CRI	LED COUNT	1 CONNECTOR FULL/DYNAMIC*	2 CONNECTORS FULL/DYNAMIC*	Fixture Color Tolerance**	Wavelength/CCT	LED CRI	LED Color Tolerance	Lumen Count	Legacy Order Code
2200K	Epistar SMD LED Chip + CRI80	25 LEDs/ft (84 LEDs/m)	22.9ft (7m) / Not Recommended	45.9ft (14m) / Not Recommended	3 SDCM	2238 ± 66K	82-87	2.3SDCM	194lm/ft (635lm/m)	SF16E0015DE22K24DC
2700K	Epistar SMD LED Chip + CRI80	25 LEDs/ft (84 LEDs/m)	22.9ft (7m) / Not Recommended	45.9ft (14m) / Not Recommended	3 SDCM	2725 ± 85K	82-87	2.3SDCM	194lm/ft (635lm/m)	SF16E0015DE27K24DC
3000K	Epistar SMD LED Chip + CRI80	25 LEDs/ft (84 LEDs/m)	22.9ft (7m) / Not Recommended	45.9ft (14m) / Not Recommended	3 SDCM	3045 ± 105K	82-87	2.3SDCM	194lm/ft (635lm/m)	SF16E0015DE30K24DC
3500K	Epistar SMD LED Chip + CRI80	25 LEDs/ft (84 LEDs/m)	22.9ft (7m) / Not Recommended	45.9ft (14m) / Not Recommended	3 SDCM	3465 ± 245K	82-87	2.3SDCM	194lm/ft (635lm/m)	SF16E0015DE35K24DC
4000K	Epistar SMD LED Chip + CRI80	25 LEDs/ft (84 LEDs/m)	22.9ft (7m) / Not Recommended	45.9ft (14m) / Not Recommended	3 SDCM	3985 ± 150K	82-87	2.3SDCM	194lm/ft (635lm/m)	SF16E0015DE40K24DC
5700K	Epistar SMD LED Chip + CRI80	25 LEDs/ft (84 LEDs/m)	22.9ft (7m) / Not Recommended	45.9ft (14m) / Not Recommended	3 SDCM	5669 ± 305K	82-87	2.3SDCM	194lm/ft (635lm/m)	SF16E0015DE57K24DC
2200K; 5700K	Epistar SMD LED Chip + CRI80	50 LEDs/ft (168 LEDs/m)	19.6ft (6m) / Not Recommended	39.4ft (12m) / Not Recommended	3 SDCM	2238 ± 66K; 5669 ± 305K	82-87; 82-87	2.3SDCM; 2.3SDCM	91lm/ft (300lm/m); 104lm/ft (340lm/m)	SF16E0015DEPDW24DC
R; G; B; R+G+B	Epistar SMD LED Chip	25 LEDs/ft (84 LEDs/m)	22.9ft (7m) / Not Recommended	45.9ft (14m) / Not Recommended	N/A	618-624nm; 522-530nm; 468-474nm; N/A	N/A	3nm; 3nm; 3nm; N/A	20lm/ft (65lm/m); 61lm/ft (200lm/m); 12lm/ft (40lm/m); 93lm/ft (305lm/m)	SF16E0015DERGB48DC
R; G; B; 2700K	Epistar SMD LED Chip + CRI80	25 LEDs/ft (84 LEDs/m)	19.6ft (6m) / 32.8ft (10m)	39.4ft (12m) / 65.6ft (20m)	N/A	618-624nm; 522-530nm; 468-474nm; 2725 ± 145K	N/A; 82-87	3nm; 3nm; 3nm; 2.3SDCM	20lm/ft (65lm/m); 61lm/ft (200lm/m); 12lm/ft (40lm/m); 52lm/ft (170lm/m)	SF16E0015DER2724DC
R; G; B; 3000K	Epistar SMD LED Chip + CRI80	25 LEDs/ft (84 LEDs/m)	19.6ft (6m) / 32.8ft (10m)	39.4ft (12m) / 65.6ft (20m)	N/A	618-624nm; 522-530nm; 468-474nm; 3045 ± 140K	N/A; 82-87	3nm; 3nm; 3nm; 2.3SDCM	20lm/ft (65lm/m); 61lm/ft (200lm/m); 12lm/ft (40lm/m); 61lm/ft (200lm/m)	SF16E0015DER3024DC
R; G; B; 4000K	Epistar SMD LED Chip + CRI80	25 LEDs/ft (84 LEDs/m)	19.6ft (6m) / 32.8ft (10m)	39.4ft (12m) / 65.6ft (20m)	N/A	618-624nm; 522-530nm; 468-474nm; 3985 ± 275K	N/A; 82-87	3nm; 3nm; 3nm; 2.3SDCM	20lm/ft (65lm/m); 61lm/ft (200lm/m); 12lm/ft (40lm/m); 55lm/ft (180lm/m)	SF16E0015DER4024DC

\*Run length is based on a static full load with voltage drop calculated using a 0.3 m (0.98 ft) cable with silicone seamless connectors, excluding connector length—refer to specifications for details. Due to fragility, five-wire fixtures are not recommended to exceed 16.4ft (5m). \*\*Silicone products maintain ≤3 SDCM within a single production run and <5 SDCM between production runs.



GLLS.COM | 1-888-580-6366

GLLS reserves the right to make any design changes for continuous improvement which will not affect the overall appearance or performance. REV. 20251230

# VIVID WAVE: SILICONE - 24V

Indoor & Outdoor Rated Linear Flex Profile - Direct DMX-Pixel



## C


### POWER & VOLTAGE

COLOR	VOLTAGE + CIRCUIT TYPE*	POWER CONSUMPTION
2200K		
2700K		
3000K		
3500K		3.66W/ft (12W/m)
4000K		
5700K	24V DC CC	
2200K-5700K		
RGB		2.74W/ft (9W/m)
RGBW-27K		
RGBW-30K		3.66W/ft (12W/m)
RGBW-40K		

\*The Constant Current (CC) Integrated Circuit extends max run length. Do not use a CC power supply, as it may cause damage.

## D

### CUTTING INSTRUCTIONS



COLOR	ORDER UNIT (CUTTING UNIT)
2200K	
2700K	
3000K	
3500K	6.56in (166.7mm) (14LEDs)
4000K	
5700K	
2200K-5700K	6.56in (166.7mm) (28LEDs)
RGB	
RGBW-27K	
RGBW-30K	6.56in (166.7mm) (14LEDs)
RGBW-40K	



GLLS.COM | 1-888-580-6366

GLLS reserves the right to make any design changes for continuous improvement which will not affect the overall appearance or performance. REV. 20251230

# VIVID WAVE: SILICONE - 24V

Indoor & Outdoor Rated Linear Flex Profile - Direct DMX-Pixel



## E

### COMPATIBLE CONNECTORS

#### INPUT - 01

PROFILE	BEND	WIRING	INPUT CONNECTOR TYPE	INPUT ORIENTATION + TYPE	INPUT CABLE LENGTH (LEAD WIRE)
---------	------	--------	----------------------	--------------------------	--------------------------------

#### OUTPUT - 02

PROFILE	BEND	WIRING	OUTPUT CONNECTOR TYPE	OUTPUT ORIENTATION + TYPE	OUTPUT CABLE LENGTH (LEAD WIRE)
F = Wave	1 = Side 2 = Top 4 = N/A (End Cap)	6 = 5 Wire (Direct DMX-Pixel) 0 = N/A (End Cap)	2 = Silicone Seamless	A = End Exit B = Bottom Exit C = Side Left Exit D = Side Right Exit E = End Jumper H = Power T-Feed I = End Cap	1 = 0.98ft (0.3m) 2 = 3.28ft (1m) 3 = 9.84ft (3m) 4 = 16ft (5m) 5 = 32.81ft (10m) 6 = 49.21ft (15m) 7 = 65.62ft (20m) 8 = N/A

### LEGACY CONNECTOR ORDER CODE

XX	16E	X	00	XX	XX	X	XX	XXX	X
PRODUCT TYPE	PROFILE	BENDING	LIGHT EMITTING	FUNCTIONALITY	CONNECTOR TYPE	Fixture End	Exit Type	Length	
NA = DIY Accessories	16E = Wave	1 = Side 2 = Top	00 = 16E	2W = Static/DTW 3W = Tunable White/SPI-Pixel 4W = RGB 5W = RGBW 5D = DMX-Pixel 0W = For End Cap	SV = Swivel CL = Click SC = Snap BL = DIY Submersible SE = Seamless PO = Submersible	1 = Input Side 2 = Output Side 0 = Jumpers/T-feeds/ Seamless Bottom/ Seamless End 3 = Input/Output	EN = End BO = Bottom SL = Side Left SR = Side Right EJ = End Jumper BJ = Bottom Jumper TF = Power Feed EC = End Cap	0M3 = 0.98ft (30cm) 01M = 3.28ft (1m) 03M = 9.84ft (3m) 05M = 16ft (5m) 10M = 32.81ft (10m) 000 = For End Cap	P = Power or For End Cap S = Signal & Power
FA = Factory Accessories									



GLLS.COM | 1-888-580-6366

GLLS reserves the right to make any design changes for continuous improvement which will not affect the overall appearance or performance. REV. 20251230

# VIVID WAVE: SILICONE - 24V

Indoor & Outdoor Rated Linear Flex Profile - Direct DMX-Pixel



E

## SILICONE SEAMLESS CONNECTOR




### NOTES:


1. Connector Tolerance  $\pm 0.02\text{in}$  (0.5mm)
2. Cable diameter: Static, Tunable, RGBW, SPI Silicone & Dim to Warm =  $0.26\text{in}$  (6.5mm) & DMX Silicone =  $0.27\text{in}$  (6.8mm)
3. Do not apply force to the feed cable
4. Ensure Max. Cable Lengths are followed according to wire gage to avoid voltage drop

IP68; seamless; precise low profile dimension; high grade quality silicone & anti-wicking ferrule. Recommended for; wet environments; custom predetermined lengths; high/ low temperatures; increased humidity; direct UV exposure; harsh working conditions & increased handling forces during installation. Precision milling and special glue Silicone liquid injection-moulded workmanship enables an almost consistent size between connectors and lightbody, and the transparent terminal of the connector allows the seamless effects spliced end by end. DryWire technology applied on the cable eliminates the capillary phenomenon through wires, which secured the long-term reliability in outdoor or any wet environments. Custom factory assembly.


END EXIT: F#62A#




END CAP: F40218



## SCREW LOCK CONNECTOR ACCESSORY - IP67



## ANTI-WICKING FERRULE:



NOTE: The tolerance is  $\pm 0.08\text{in}$  (2mm).

### NOTES:

1. The anti-wicking ferrule is located at 4.53in (115mm) ( $\pm 0.39\text{in}$  [ $\pm 10\text{mm}$ ]) tolerance) from the connector on the cable. For protection against water ingress.
2. The removal of anti-wicking ferrule will void the warranty if any water ingress caused by it.



GLLS.COM | 1-888-580-6366

GLLS reserves the right to make any design changes for continuous improvement which will not affect the overall appearance or performance. REV. 20251230


# VIVID WAVE: SILICONE - 24V

Indoor & Outdoor Rated Linear Flex Profile - Direct DMX-Pixel




## E


### BOTTOM EXIT: F#62B#





### END JUMPER: F#62E1




### SIDE LEFT EXIT: F#62C#



### POWER T-FEED: F#62H#



### SIDE RIGHT EXIT: F#62D#



# VIVID WAVE: SILICONE - 24V

Indoor & Outdoor Rated Linear Flex Profile - Direct DMX-Pixel



## F

### MOUNTING PROFILES

MOUNTING PROFILE TYPE	STANDARD LENGTH	PROFILE	COLOR	BEND
A1 = Aluminum Basic	2 = 1.38in (35mm) 3 = 19.68in (500mm) 5 = 39.37in (1000mm) 6 = 78.74in (2000mm)			
A2 = Aluminum Recessed	2 = 1.38in (35mm) 3 = 19.68in (500mm) 5 = 39.37in (1000mm) 6 = 78.74in (2000mm)			
A3 = Aluminum Recessed Silicone Grip	1 = 0.79in (20mm) 3 = 19.68in (500mm) 5 = 39.37in (1000mm) 6 = 78.74in (2000mm)			4 = N/A
A4 = Aluminum Silicone Grip	1 = 0.79in (20mm) 3 = 19.68in (500mm) 5 = 39.37in (1000mm) 6 = 78.74in (2000mm)		1 = Standard	
A5 = Aluminum Flexible	3 = 19.68in (500mm) 5 = 39.37in (1000mm)	F = Wave		1 = Side
A8 = Aluminum Raceway	3 = 19.68in (500mm) 5 = 39.37in (1000mm) 6 = 78.74in (2000mm)			
A9 = Aluminum Raceway Suspended	3 = 19.68in (500mm) 5 = 39.37in (1000mm) 6 = 78.74in (2000mm)			
P1 = Plastic Reinforced	2 = 1.38in (35mm) 3 = 19.68in (500mm) 5 = 39.37in (1000mm) 6 = 78.74in (2000mm)			4 = N/A
C1 = Silicone Flexible	F = 2.16in (55mm) B = 4.33in (110mm) C = 7.87in (200mm) 3 = 19.68in (500mm) 5 = 39.37in (1000mm)		2 = Black 3 = White 0 = Custom	
S1 = Stainless Steel Clips	2 = 1.38in (35mm)		1 = Standard	



# VIVID WAVE: SILICONE - 24V


Indoor & Outdoor Rated Linear Flex Profile - Direct DMX-Pixel



F

## ALUMINUM PROFILE - BASIC


High-quality 6063 aluminum with thin-wall, light-weight design to fit the fixture tightly. It is deformation and rust resistant, and cost-effective. Please refer to install manual for proper installation practices..



NOTES: 1. 2-L1 refers to two of symmetric L1 in each piece of profile.  
2. (N-1)-L2 refers to (N minus one) of symmetric L2 in each piece of profile.  
"N" hereby stands for its corresponding "Hole Number" in the below table

## ALUMINUM PROFILE - RECESSED

High-quality 6063 aluminum with thin-wall, light-weight design to fit the fixture tightly. Recommended on projects with lighting mounted recessed in a cavity so only the lens is shown. It is deformation and rust resistant, and cost-effective. Please refer to install manual for proper installation practices.



NOTES: 1. 2-L1 refers to two of symmetric L1 in each piece of profile.  
2. (N-1)-L2 refers to (N minus one) of symmetric L2 in each piece of profile.  
"N" hereby stands for its corresponding "Hole Number" in the below table

ORDER CODE	LEGACY ORDER CODE	STANDARD LENGTH	L1	L2	SLOTTED HOLE	HOLE #
A22F14	CL16RRA3C5SD	1.38in (35mm)	0.69in (17.5mm)	N/A	0.16*0.39in (4*10mm)	1
A23F14	CH16RRA0M5SD	19.68in (500mm)	1.97in (50mm)	7.87in (200mm)	0.16*0.39in (4*10mm)	3
A25F14	CH16RRA01MSD	39.37in (1000mm)	3.93in (100mm)	7.87in (200mm)	0.16*0.39in (4*10mm)	5
A26F14	CH16RRA02MSD	78.74in (2000mm)	3.93in (100mm)	7.87in (200mm)	0.16*0.39in (4*10mm)	10



GLLS.COM | 1-888-580-6366

GLLS reserves the right to make any design changes for continuous improvement which will not affect the overall appearance or performance. REV. 20251230

# VIVID WAVE: SILICONE - 24V


Indoor & Outdoor Rated Linear Flex Profile - Direct DMX-Pixel



## F

### ALUMINUM PROFILE - RECESSED - SILICONE GRIP

High-quality 6063 aluminum with thin-wall, light-weight design to fit the fixture tightly. Includes a serrated silicone grip insert designed to hold fixture with additional force. Recommended on projects mounted upside down with lighting mounted recessed in a cavity so only the lens is shown. It is deformation and rust resistant, and cost-effective. Please refer to install manual for proper installation practices.




NOTES: 1. 2-L1 refers to two of symmetric L1 in each piece of profile.  
2. (N-1)-L2 refers to (N minus one) of symmetric L2 in each piece of profile.  
"N" hereby stands for its corresponding "Hole Number" in the below table

ORDER CODE	LEGACY ORDER CODE	STANDARD LENGTH	L1	L2	SLOTTED HOLE	HOLE #
A31F14	CL16RRA02CSE	0.79in (20mm)	0.39in (10mm)	N/A	0.16*0.39in (4*10mm)	1
A33F14	CH16RRA0M5SE	19.68in (500mm)	1.97in (50mm)	7.87in (200mm)	0.16*0.39in (4*10mm)	3
A35F14	CH16RRA01MSE	39.37in (1000mm)	3.93in (100mm)	7.87in (200mm)	0.16*0.39in (4*10mm)	5
A36F14	CH16RRA02MSE	78.74in (2000mm)	3.93in (100mm)	7.87in (200mm)	0.16*0.39in (4*10mm)	10

### ALUMINUM PROFILE - SILICONE GRIP

High-quality 6063 aluminum with thin-wall, light-weight design. Includes a serrated silicone grip insert designed to hold fixture with additional force. Recommended on projects mounted upside down. It is deformation and rust resistant, and cost-effective. Please refer to install manual for proper installation practices.



NOTES: 1. 2-L1 refers to two of symmetric L1 in each piece of profile.  
2. (N-1)-L2 refers to (N minus one) of symmetric L2 in each piece of profile.  
"N" hereby stands for its corresponding "Hole Number" in the below table

ORDER CODE	LEGACY ORDER CODE	STANDARD LENGTH	L1	L2	SLOTTED HOLE	HOLE #
A41F14	CL16RAL02CSE	0.79in (20mm)	0.39in (10mm)	N/A	0.16*0.39in (4*10mm)	1
A43F14	CH16RAL0M5SE	19.68in (500mm)	1.97in (50mm)	7.87in (200mm)	0.16*0.39in (4*10mm)	3
A45F14	CH16RAL01MSE	39.37in (1000mm)	3.93in (100mm)	7.87in (200mm)	0.16*0.39in (4*10mm)	5
A46F14	CH16RAL02MSE	78.74in (2000mm)	3.93in (100mm)	7.87in (200mm)	0.16*0.39in (4*10mm)	10



GLLS.COM | 1-888-580-6366

GLLS reserves the right to make any design changes for continuous improvement which will not affect the overall appearance or performance. REV. 20251230

# VIVID WAVE: SILICONE - 24V


Indoor & Outdoor Rated Linear Flex Profile - Direct DMX-Pixel



F

## ALUMINUM PROFILE - FLEXIBLE

It is an expanded design of the flexible aluminum profile, and caters for the continuously streamlined aesthetics of curve shape. The secondary precision cutting process, not only maintains the advantage of clamping force, but also enables the two-way side bending directions with super shape memory. Please refer to install manual for proper installation practices.




NOTES: 1. 2-L1 refers to two of symmetric L1 in each piece of profile.  
2. (N-1)-L2 refers to (N minus one) of symmetric L2 in each piece of profile.  
"N" hereby stands for its corresponding "Hole Number" in the below table

ORDER CODE	LEGACY ORDER CODE	STANDARD LENGTH	L1	L2	SLOTTED HOLE	HOLE #
A53F11	CH16FAL0M5SE	19.68in (500mm)	4.34in (110.3mm)	1.92in (48.9mm)	Ø 0.17in (4.2mm)	6
A55F11	CH16FAL01MSE	39.37in (1000mm)	4.59in (116.5mm)	3.89in (98.8mm)	Ø 0.17in (4.2mm)	10

## ALUMINUM PROFILE - RACEWAY

High-quality 6063 thin-wall aluminum, light-weight design featuring hidden cables. The raceway space is enough to conceal seamless connectors with bottom feed and the general male/female connectors. It is superb for the facade where tidiness is required and the scenarios that lack of space for wiring. Please refer to install manual for proper installation practices.



NOTES: 1. 2-L1 refers to two of symmetric L1 in each piece of profile.  
2. (N-1)-L2 refers to (N minus one) of symmetric L2 in each piece of profile.  
"N" hereby stands for its corresponding "Hole Number" in the below table

ORDER CODE	LEGACY ORDER CODE	STANDARD LENGTH	L1	L2	SLOTTED HOLE	HOLE #
A83F14	CH16RAL0M5RS	19.68in (500mm)	1.97in (50mm)	7.87in (200mm)	0.18*0.47in (4.5*12mm)	3
A85F14	CH16RAL01MRS	39.37in (1000mm)	3.93in (100mm)	7.87in (200mm)	0.18*0.47in (4.5*12mm)	5
A86F14	CH16RAL02MRS	78.74in (2000mm)	3.93in (100mm)	7.87in (200mm)	0.18*0.47in (4.5*12mm)	10



GLLS.COM | 1-888-580-6366

GLLS reserves the right to make any design changes for continuous improvement which will not affect the overall appearance or performance. REV. 20251230

# VIVID WAVE: SILICONE - 24V


Indoor & Outdoor Rated Linear Flex Profile - Direct DMX-Pixel



F


## ALUMINUM PROFILE - RACEWAY - SUSPENDED

High-quality 6063 thin-wall aluminum, light-weight design featuring hidden cables and suspended by cables from the ceiling. The raceway space is enough to conceal seamless connectors with bottom feed and the general male/female connectors. It is superb for the facade where tidiness is required and the scenarios that lack of space for wiring. Please refer to install manual for proper installation practices.



## PLASTIC PROFILE - REINFORCED

High Quality rigid plastic designed to securely hold fixtures. Recommended for use in extreme environments susceptible to increased water/humidity (SPA's and pools). Please refer to install manual for proper installation practices.



GLLS.COM | 1-888-580-6366

GLLS reserves the right to make any design changes for continuous improvement which will not affect the overall appearance or performance. REV. 20251230

# VIVID WAVE: SILICONE - 24V




Indoor & Outdoor Rated Linear Flex Profile - Direct DMX-Pixel




F

## SILICONE PROFILE - FLEXIBLE

An all-in-one mounting profile designed to unleash your creativity. This profile not only provides flexibility in installation methods, but also overcomes bending limitations by offering both top and side bending in a single profile. Fully encapsulated in UL-certified silicone, it excels in UV, weather, and corrosion resistance, making it suitable for underwater, high and low temperature environments. Elegant and square in appearance, it is available in black or white standard colors, or bespoke colors to blend in with the background. Supported by innovative serrated silicone fins, its clamping strength is strong enough to secure any installation method. Please refer to install manual for proper installation practices. Side and top bending.



Tolerance:  $\pm 0.01\text{in}$  (0.3mm)








NOTES: 1. 2-L1 refers to two of symmetric L1 in each piece of profile.  
2. (N-1)-L2 refers to (N minus one) of symmetric L2 in each piece of profile.  
"N" hereby stands for its corresponding "Hole Number" in the below table

ORDER CODE	LEGACY ORDER CODE: WHITE	LEGACY ORDER CODE: BLACK	STANDARD LENGTH	L1	L2	SLOTTED HOLE	HOLE #
C1FF#4	CH16FAN5C5SEW	CH16FAN5C5SEB	2.16in (55mm)	0.49in (12.5mm)	1.18in (30mm)	$\varnothing 0.12\text{in}$ (3mm)	2
C1BF#4	CH16FAN1C1SEW	CH16FAN1C1SEB	4.33in (110mm)	0.46in (11.6mm)	3.48in (88.4mm)	$\varnothing 0.12\text{in}$ (3mm)	2
C1CF#4	CH16FAN0M2SEW	CH16FAN0M2SEB	7.87in (200mm)	0.46in (11.6mm)	3.48in (88.4mm)	$\varnothing 0.12\text{in}$ (3mm)	3
C13F#4	CH16FAN0M5SEW	CH16FAN0M5SEB	19.68in (500mm)	1.14in (29mm)	3.48in (88.4mm)	$\varnothing 0.12\text{in}$ (3mm)	6
C15F#4	CH16FAN01MSEW	CH16FAN01MSEB	39.37in (1000mm)	0.54in (13.8mm)	3.48in (88.4mm)	$\varnothing 0.12\text{in}$ (3mm)	12

## STAINLESS STEEL PROFILE - CLIP

It uses grade 316 stainless steel with excellent property of deformation and rust resistance. The material makes it suitable for humid coastal surroundings and weak acid-base industrial environments that other mounting profiles can't accommodate. The structural design and material characteristics collectively ensure a tight clamping force. It's very convenient and reliable even for suspended installation in the curve shape. Please refer to install manual for proper installation practices.



ORDER CODE	LEGACY ORDER CODE	STANDARD LENGTH	SLOTTED HOLE	HOLE #
S12F14	CL16RSS3C5SD	1.38in (35mm)	$\varnothing 0.18\text{in}$ (4.5mm)	3



GLLS.COM | 1-888-580-6366

GLLS reserves the right to make any design changes for continuous improvement which will not affect the overall appearance or performance. REV. 20251230

# VIVID WAVE: SILICONE - 24V

Indoor & Outdoor Rated Linear Flex Profile - Direct DMX-Pixel






G

## MOUNTING ACCESSORIES

MOUNTING ACCESSORY TYPE	PROFILE
MA1 = Pivot Bracket	
MA2 = Rotary Bracket	
MA3 = Side Bracket	
MA4 = Ceiling Clip	
MA5 - Suspended Rod + Clip	
MA6 = Suspended Wire Kit	
MA7 = Alignment Bracket - Aluminum Basic	
MA8 = Alignment Bracket - Aluminum Silicone Grip	

## PIVOT BRACKET

Applicable to all mounting profiles.



GLLS.COM | 1-888-580-6366

GLLS reserves the right to make any design changes for continuous improvement which will not affect the overall appearance or performance. REV. 20251230

# VIVID WAVE: SILICONE - 24V





Indoor & Outdoor Rated Linear Flex Profile - Direct DMX-Pixel



G



## ROTARY BRACKET

Applicable to all mounting profiles.



## SIDE MOUNTING BRACKET

Applicable to all mounting profiles.



GLLS.COM | 1-888-580-6366

GLLS reserves the right to make any design changes for continuous improvement which will not affect the overall appearance or performance. REV. 20251230

# VIVID WAVE: SILICONE - 24V


Indoor & Outdoor Rated Linear Flex Profile - Direct DMX-Pixel



G


## CEILING CLIP BRACKET

Applicable to aluminum profile - recessed - silicone grip



## SUSPENDED WIRE

Applicable to Aluminum Profile - Silicone Grip. 2 kits of stainless steel wires for 39.37in (1000mm) of profile & 3 kits of stainless steel wires for 78.74in (2000mm) of profile.



GLLS.COM | 1-888-580-6366

GLLS reserves the right to make any design changes for continuous improvement which will not affect the overall appearance or performance. REV. 20251230



# VIVID WAVE: SILICONE - 24V

Indoor & Outdoor Rated Linear Flex Profile - Direct DMX-Pixel




G

## SUSPENDED MOUNTING CLIP + ROD




## ALIGNMENT BRACKET - ALUMINUM BASIC

Applicable to aluminum basic



## ALIGNMENT BRACKET - ALUMINUM SILICONE GRIP

Applicable to aluminum silicone grip



GLLS.COM | 1-888-580-6366

GLLS reserves the right to make any design changes for continuous improvement which will not affect the overall appearance or performance. REV. 20251230