



LINEAR FLEX FIXTURE + CONNECTOR PRODUCT ORDER CODE

INPUT CONNECTOR						FIXTURE												OUTPUT CONNECTOR					
X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	XX	X	X	X	X	X	X	X	
PROFILE	BENDING	WIRING	CONNECTOR TYPE	ORIENTATION + TYPE	CABLE LENGTH (LEAD WIRE)	SERIES	MATERIAL	PROFILE	BENDING	JACKET/BASE + LENS COLOR	COLOR FUNCTION	COLOR	CHIP + CRI	POWER W/FT	VOLTAGE/ CIRCUIT TYPE*	ORDER (CUTTING) LENGTH	PROFILE (PRODUCT) SPECIFIC	PROFILE	BENDING	WIRING	CONNECTOR TYPE	ORIENTATION + TYPE	CABLE LENGTH (LEAD WIRE)
A = BASIC	1 = SIDE	1 = 2 WIRE (STATIC/DIM TO WARM)	1 = PVC SEAMLESS	A = END EXIT	1 = 0.98ft (0.3m)	V = VIVID	1 = SILICONE	A = BASIC	1 = SIDE	W = WHITE + DIFFUSED (STANDARD)	1 = STATIC	A = AMBER	1 = EPISTAR SMD LED	A = 1.07W/ft (3.5W/m)	1V = 5V DC	A = 0.73in (18.5mm)	A = 12°	A = BASIC	1 = SIDE	1 = 2 WIRE (STATIC/DIM TO WARM)	1 = PVC SEAMLESS	A = END EXIT	1 = 0.98ft (0.3m)
B = CONTOUR	2 = TOP		2 = SILICONE SEAMLESS	B = BOTTOM EXIT	2 = 3.28ft (1m)	L = LANDSCAPE FLEX	2 = PVC	B = CONTOUR	2 = TOP		2 = TUNABLE WHITE PWM	B = BLUE	2 = EPISTAR SMD LED + CRI80	B = 1.37W/ft (4.5W/m)	2V = 12V DC / CV (CONSTANT VOLTAGE)	B = 1.64in (41.7mm)	B = 25°	B = CONTOUR	2 = TOP		2 = SILICONE SEAMLESS	B = BOTTOM EXIT	2 = 3.28ft (1m)
C = S160	3 = MULTI	2 = 3 WIRE (TUNABLE WHITE PWM/ SPI PIXEL)	3 = PVC SUBMERSIBLE UL676	C = SIDE LEFT EXIT	3 = 9.84ft (3m)	A = AQUA NEON		C = S160	3 = MULTI	B = BLACK + DIFFUSED	3 = RGB PWM	C = GREEN	3 = EPISTAR SMD LED + CRI90	C = 1.82W/ft (6W/m)	3V = 24V DC / CV (CONSTANT VOLTAGE)	C = 1.97in (50mm)	C = 15°25°	C = S160	3 = MULTI	2 = 3 WIRE (TUNABLE WHITE PWM/ SPI PIXEL)	3 = PVC SUBMERSIBLE UL676	C = SIDE LEFT EXIT	3 = 9.84ft (3m)
D = S270	4 = N/A		4 = SILICONE SUBMERSIBLE UL676	D = SIDE RIGHT EXIT	4 = 16.4ft (5m)	S = SAUNA FLEX		D = S270	4 = N/A	D = BLACK + BLACK	4 = RGBW PWM	D = YELLOW	4 = EPISTAR SMD LED + CRI95	D = 2.43W/ft (8W/m)	4V = 48V DC / CV (CONSTANT VOLTAGE)	D = 2.19in (55.6mm)	D = 15°40°	D = S270	4 = N/A		4 = SILICONE SUBMERSIBLE UL676	D = SIDE RIGHT EXIT	4 = 16.4ft (5m)
E = WAVE MINI		3 = 3 WIRE (SPI-PIXEL POWER FEED)	5 = 120V CONNECTOR (FUSE + SCREW)	E = END JUMPER	5 = 32.81ft (10m)	E = LINE VOLTAGE		E = WAVE MINI		G = GRAY + DIFFUSED	5 = SPI-PIXEL	E = RED	5 = NICHIA SMD LED	E = 2.74W/ft (9W/m)	1A = 12V AC	E = 0.66in (16.7mm)	E = 15°60°	E = WAVE MINI		3 = 3 WIRE (SPI-PIXEL POWER FEED)	5 = 120V CONNECTOR (FUSE + SCREW)	E = END JUMPER	5 = 32.81ft (10m)
F = WAVE		4 = 4 WIRE (RGB PWM)	6 = SWIVEL	F = BOTTOM JUMPER	6 = 49.21ft (15m)	H = VIVID HIGH-OUTPUT		F = WAVE		R = RED + RED	6 = SPI-PIXEL-RGBW	G = 2100K	6 = PRO LED CHIP + CRI80	F = 3.05W/ft (10W/m)	2A = 120V AC	F = 3.28in (83.3mm)	F = 20°40°@RGB	F = WAVE		4 = 4 WIRE (RGB PWM)	6 = SWIVEL	F = BOTTOM JUMPER	6 = 49.21ft (15m)
G = WAVE XL		5 = 5 WIRE (RGBW PWM)	7 = SNAP	G = SIDE JUMPER	7 = 65.62ft (20m)	M = MULTIFLEX		G = WAVE XL		L = BLUE + BLUE	7 = DIRECT DMX-PIXEL	H = 2200K	7 = PRO LED CHIP + CRI80	G = 3.66W/ft (12W/m)	3A = 230V AC	G = 3.94in (100mm)	G = 20°40°@RGBW	G = WAVE XL		5 = 5 WIRE (RGBW PWM)	7 = SNAP	G = SIDE JUMPER	7 = 65.62ft (20m)
H = WAVE 320		6 = 5 WIRE (DIRECT DMX-PIXEL)	8 = CLICK	H = POWER T-FEED	8 = N/A	I = LUMIFORM SS		H = WAVE 320		C = GREEN + GREEN	8 = DIRECT DMX-PIXEL-RGBW	I = 2500K	8 = PRO LED CHIP + CRI80	H = 5.48W/ft (18W/m)	1C = 12V DC / CR (CURRENT REGULATED)	H = 4.92in (125mm)	H = ENERGY RELATED PRODUCTS	H = WAVE 320		6 = 5 WIRE (DIRECT DMX-PIXEL)	8 = CLICK	H = POWER T-FEED	8 = N/A
I = LIGHTSTRIP		0 = N/A	X = CUSTOM	I = END CAP	9 = 1.64ft (0.5m)	G = LUMIFORM ALUMINIUM		I = LIGHTSTRIP		O = ORANGE + ORANGE	9 = DIM TO WARM	J = 2700K	9 = PRO LED CHIP + CRI80	I = 4.57W/ft (15W/m)	2C = 24V DC / CR (CURRENT REGULATED)	I = 6.56in (166.7mm)	X1 = WAVE PCB	I = LIGHTSTRIP		0 = N/A	8 = CLICK	I = END CAP	9 = 1.64ft (0.5m)
J = LIGHTSTRIP XL				J = END EXIT EXTENSIBLE	0 = 0.84ft (0.26m)	O = AQUA NEON HIGH OUTPUT		J = LIGHTSTRIP XL		N = TRANSPARENT + TRANSPARENT (LIGHT STRIP STANDARD)	X = CUSTOM	K = 2600K	A = PRO LED CHIP + CRI90	J = 5.02W/ft (16.5W/m)	X = CUSTOM	J = 7.87in (200mm)		J = LIGHTSTRIP XL			8 = CLICK	J = END EXIT EXTENSIBLE	0 = 0.84ft (0.26m)
K = C12				K = SIDE EXIT EXTENSIBLE	A = 6.56ft (2m)			K = C12		T = WHITE + TRANSPARENT		L = 3000K	X = CUSTOM	K = 2.19W/ft (7.2W/m)	3C = 48V DC / CR (CURRENT REGULATED)	K = 9.84in (250mm)		K = C12			7 = SNAP	K = SIDE EXIT EXTENSIBLE	A = 6.56ft (2m)
L = ORBIT WAVE				L = ORBIT WAVE	X = CUSTOM			L = ORBIT WAVE		A = BLACK + TRANSPARENT		M = 3500K		L = 6.71W/ft (22W/m)	X = CUSTOM	L = 19.7in (500.38mm)		L = ORBIT WAVE			8 = CLICK	L = ORBIT WAVE	X = CUSTOM
M = ORBIT LS (LIGHT STRIP)				M = ORBIT LS (LIGHT STRIP)				M = ORBIT LS (LIGHT STRIP)		E = WHITE JACKET/ BLACK BASE + DIFFUSED		N = 4000K		M = 1.22W/ft (4W/m)		M = 7.87in (200mm)		M = ORBIT LS (LIGHT STRIP)			X = CUSTOM	M = BOTTOM EXIT EXTENSIBLE	
N = ORBIT GX (GRAZER)				N = ORBIT GX (GRAZER)				N = ORBIT GX (GRAZER)		P = OPAL + DIFFUSED-		Z = 4200K		N = 7.31W/ft (24W/m)		N = 9.84in (250mm)		N = ORBIT LS (LIGHT STRIP)				N = END EXIT EXTENSIBLE	
				O = SIDE EXIT NON-EXTENSIBLE				O = ORBIT WAVE		X = CUSTOM		O = 4500K		O = 1.98W/ft (6.5W/m)		O = 11.9mm		M = ORBIT LS (LIGHT STRIP)				O = SIDE EXIT NON-EXTENSIBLE	
				Q = BOTTOM EXIT NON-EXTENSIBLE				M = ORBIT LS (LIGHT STRIP)				P = 5000K		Q = 1.10W/ft (3.6W/m)		Q = 39.37in (1000mm)		N = ORBIT GX (GRAZER)				Q = BOTTOM EXIT NON-EXTENSIBLE	
				R = TOP EXIT				M = ORBIT LS (LIGHT STRIP)				R = 6500K		R = 1.52W/ft (5W/m)		R = 20.8mm		N = ORBIT GX (GRAZER)				R = TOP EXIT	
				S = MIDDLE CONNECTOR				M = ORBIT LS (LIGHT STRIP)				S = RBG		Q = 1.98W/ft (6.5W/m)		S = 0.82in (20.8mm)		N = ORBIT GX (GRAZER)				S = MIDDLE CONNECTOR	
				T = JUMPER INPUT				N = ORBIT GX (GRAZER)				T = 1800K-3000K		Q = 1.10W/ft (3.6W/m)		T = 71.4mm		N = ORBIT GX (GRAZER)				T = JUMPER INPUT	
				U = T-FEED INPUT				N = ORBIT GX (GRAZER)				U = 2200K-5700K		R = 4.88W/ft (16W/m)		U = 1.40in (35.7mm)		N = ORBIT GX (GRAZER)				U = T-FEED INPUT	
				V = MIDDLE CONNECTOR INPUT				N = ORBIT GX (GRAZER)				V = 2200K-6500K		P = 4.88W/ft (16W/m)		V = 45.5mm		N = ORBIT GX (GRAZER)				V = MIDDLE CONNECTOR INPUT	
				Y = EXTENSIBLE 02 EXIT + FEMALE SCREW LOCK				N = ORBIT GX (GRAZER)				W = 2500K-5000K		X = CUSTOM		Y = 1.78in (45.5mm)		N = ORBIT GX (GRAZER)				Y = EXTENSIBLE 02 EXIT + FEMALE SCREW LOCK	
				X = CUSTOM				N = ORBIT GX (GRAZER)				1 = 2100K-5500K				X = CUSTOM		N = ORBIT GX (GRAZER)				X = CUSTOM	
								N = ORBIT GX (GRAZER)				2 = 2700K-6500K						N = ORBIT GX (GRAZER)					
								N = ORBIT GX (GRAZER)				3 = 2400K						N = ORBIT GX (GRAZER)					
								N = ORBIT GX (GRAZER)				4 = 2700K-5700K						N = ORBIT GX (GRAZER)					
								N = ORBIT GX (GRAZER)				5 = PINK						N = ORBIT GX (GRAZER)					
								N = ORBIT GX (GRAZER)				6 = 2000K						N = ORBIT GX (GRAZER)					
								N = ORBIT GX (GRAZER)				7 = 2700K-6000K						N = ORBIT GX (GRAZER)					
								N = ORBIT GX (GRAZER)				8 = 1800K-5000K						N = ORBIT GX (GRAZER)					
								N = ORBIT GX (GRAZER)				X = CUSTOM						N = ORBIT GX (GRAZER)					