


ORBIT

Silicone Profile - Flexible




An all-in-one mounting profile designed to unleash your creativity. This profile not only provides flexibility in installation methods, but also overcomes bending limitations by offering both top and side bending in a single profile. Fully encapsulated in UL-certified silicone, it excels in UV, weather, and corrosion resistance, making it suitable for underwater, high and low temperature environments. Elegant and square in appearance, it is available in black or white standard colors, or bespoke colors to blend in with the background. Supported by innovative serrated silicone fins, its clamping strength is strong enough to secure any installation method. Please refer to install manual for proper installation practices.




ORDER CODE

MOUNTING PROFILE TYPE	STANDARD LENGTH	PROFILE	COLOR	BENDING
C1 = Silicone Flexible	F = 2.17in (55mm) B = 4.33in (110mm) C = 7.87in (200mm) 3 = 19.68in (500mm) 5 = 39.37in (1000mm)	L = Orbit	2 = Black 3 = White 0 = Custom	3 = Multi

DIMENSIONS



Tolerance: ± 0.01 in (0.3mm)



NOTES: 1. 2-L1 refers to two of symmetric L1 in each piece of profile.
2. (N-1)-L2 refers to (N minus one) of symmetric L2 in each piece of profile.
"N" hereby stands for its corresponding "Hole Number" in the below table

ORDER CODE	LEGACY ORDER CODE WHITE	LEGACY ORDER CODE BLACK	STANDARD LENGTH	L1	L2	SLOTTED HOLE	HOLE #
C1FL#3	CH23FAN5C5SEW	CH23FAN5C5SEB	2.17in (55mm)	0.49in (12.5mm)	1.18in (30mm)	0.12in (3mm)	2
C1BL#3	CH23FAN1C1SEW	CH23FAN1C1SEB	4.33in (110mm)	0.46in (11.6mm)	3.48in (88.4mm)	0.12in (3mm)	2
C1CL#3	CH23FAN0M2SEW	CH23FAN0M2SEB	7.87in (200mm)	0.46in (11.6mm)	3.48in (88.4mm)	0.12in (3mm)	3
C13L#3	CH23FAN0M5SEW	CH23FAN0M5SEB	19.68in (500mm)	1.14in (29mm)	3.48in (88.4mm)	0.12in (3mm)	6
C15L#3	CH23FAN01MSEW	CH23FAN01MSEB	39.37in (1000mm)	0.54in (13.8mm)	3.48in (88.4mm)	0.12in (3mm)	12