WAVE

PVC Compact Submersible



IP68; extremely durable, underwater, UL676 rated. Recommended for; long-term submersed in wet environments up to the depth of 16.40ft (5m) (water is skin safe for extended periods); high temperature and humidity environments (mounting surface temperature <140°F(60°C); custom predetermined lengths and larger connector; harsh working conditions & increased handling forces during installation. Custom factory assembly.

NOTES:
1. Connector Tolerance ±0.02in (0.5mm)
2. Cable diameter: Static, Tunable & SPI PVC = 0.24in (6mm)
3. Do not apply force to the feed cable
4. Ensure Max. Cable Lengths are followed according to wire gage to avoid voltage drop



ORDER CODE


INPUT - 01

PROFILE	BEND	WIRING	INPUT CONNECTOR TYPE	INPUT ORIENTATION + TYPE	INPUT CABLE LENGTH (LEAD WIRE)
F					


OUTPUT - 02

PROFILE	BEND	WIRING	OUTPUT CONNECTOR TYPE	OUTPUT ORIENTATION + TYPE	OUTPUT CABLE LENGTH (LEAD WIRE)
F					
F = Wave	1 = Side 2 = Top 4 = N/A (End Cap)	1 = 2 Wire (Static/Dim To Warm) 2 = 3 Wire (Tunable White PWM/ SPI Pixel) 0 = N/A (End Cap)	0 = PVC Compact Submersible	A = End Exit B = Bottom Exit C = Side Left Exit D = Side Right Exit I = End Cap	3 = 9.84ft (3m) 8 = N/A

END EXIT: F##0A3



END CAP: F400I8




WAVE


PVC Submersible

COMPLEXITY, SIMPLIFIED.

BOTTOM EXIT: F##0B3



SIDE LEFT EXIT: F##0C3



SIDE RIGHT EXIT: F##0D3

