

Bavak Speedgate Comparison Matrix

Specifications**	B-Protect	B-Secure	B-Trackless ***	B-Access
Bottom drive	-	X	-	-
Top-drive	X	-	-	-
Side drive - top-guiding rail	-	-	-	X
Side drive - trackless	-	-	X	-
Maximum width (clear opening)*	20' (6.1 m)	19' - 8" (6.0m)	24' - 7" (7.5m)	18' - 0.5" (5.5m)
Maximum height (clear opening)*	15' (4.5m)	10' (3.0m)	10' (3.0m)	10' (3.0m)
Panels with standard picket infill	X	X	X	X
Bullet resistant cladding up to FB6	X	-	-	-
Resistance RC2 till RC4 (EN1627) cladded	X	-	-	-
Resistance RC2 till RC4 (EN1627) pickets	X	-	-	-
UL325-compliance. Approved by (Notifying Body) Intertek.	X	X	X	-
Anti-climb tubes over hinges	optional	optional	optional	optional
Safety Edges (set of 8 per full gate)	X	X	X	X
Mechanical locking of gate	Center-in-line blocking of gearwheels	Motorreductor	Electro Mechanical Brake	Electro Mechanical Brake
Speedgate single version (1 folding panel)	-	-	X	-
Dual safetyloop detector	X	X	X	X
Dual Presenceloop / automatic openening loopdetector	Optional	Optional	Optional	Optional
Column integrated traffic lights (optional)	Optional	Optional	Optional	Optional
Special design (custom infill optional)	Optional	Optional	Optional	Optional

*

If you require different dimensions, please get in touch with Bavak

**

Other customized options available (touch screen controls, other user controls, free standing traffic lights, custom gate panels, various decorative and custom finishes, functional top framework, etc.

The B-Trackless our most popular high security general-purpose model