

	B-Protect	B-Secure	B-Trackless	B-Access
Bottom drive	-	X	-	-
Top-drive	X	-	-	-
Side drive - top-guiding rail	-	-	-	X
Side drive - trackless	-	-	X	-
Maximum width	19' - 8" / 6.000 mm*	19' - 8" / 6.000 mm*	26' - 3" / 8.000 mm	19' - 8" / 6.000 mm
Maximum height	16' - 5" / 5.000 mm*	14' - 9" / 4.500 mm*	8' - 2" / 2.500 mm	9' - 10" / 3.000 mm
Panels with standard picket infill	X	X	X	X
Bullet resistant cladding up to FB6	X	-	-	-
Burglar resistance RC2 till RC4 (EN1627) cladded	X	-	-	-
Burglar resistance RC2 till RC4 (EN1627) pickets	X	-	-	-
Underwriters Laboratories - UL325	-	X	X	-
Anti-climb tubes over hinges	X	X - optional	-	-
Safety Edges x4	X	X	X	X
Mechanical locking in bottom tray	-	X	-	-
Mechanical locking in upper tray	X	-	-	-
Speedgate single version (1 bi-folding panel)	-	-	X	X
Integrated loop detectors	X	X	X	X

Panels provided with LED strips (optional)	-	-	Optional	-
Column integrated traffic lights (optional)	Optional	Optional	Optional	Optional
Special design (custom infill panel optional)	Optional	Optional	Optional	Optional

*non standard sizes on request

Other customized options available (touch screen controls, other user controls, free standing traffic lights, custom gate panels, various decorative and custom finishes, functional top framework, etc.)

Please contact Bavak US for more information: Bavak Security Group, Inc, Radford, VA | P (703) 980-5429 | Email - info@bavak.com