

SAFESPRAY ROAD SIDE SPRAYING



ROAD SIDE SPRAYING

The **SafeSpray Vehicle System (SVS)** ticks all the boxes for government organisations, contractors and anyone serious about the safety of their spray crews. Designed around feedback and input from professionals in the field, the SVS meets every requirement. Turn any standard ute into a dedicated spray vehicle and customise it with numerous upgrades and options to suit your specific application.



Under Tray Nozzle



DIMENSIONS

LONG UNIT

Single Cab Ute

2280mm x 1750mm

SHORT UNIT

Dual Cab

1700mm x 1750mm

1300 077 033



Find out how we can help.

rapidvehiclesystems.com.au

SPECIFICATIONS

TANK	300L - Dual Cab 400L / 500L / 600L / 675L - Single Cab	UV stabilised chemical resistant polyethylene with integral sump, 15 year guarantee, Australian Made AS 2010:1999 and AS 4766:2006 compliant
FRAME	Steel	Hot dip galvanised with rear fork access and spill tray with raised certified mounting system
LOCKERS	Aluminium, white	Heavy duty aluminum with gas struts and locking mechanisms, vented and bunged with drain bung, Australian Made
PUMP	Maruyama Triplex	MSD51 Triplex plunger pump, 45L/min 580psi. Made in Japan with 3 year warranty.
	Bertolini PA530	3 piston semi-hydraulic diaphragm pump, 54L/min 580psi. Made in Italy with 2 year warranty.
ENGINE	Honda GX200E / 10A	6.5HP genuine Honda, 4 stroke, low oil alert, high charge capacity, Electric start
	Hatz 1B20	5.4kW Power, direct injection method, compact & lightweight construction
SAFELoad	10L	Safe Chemical Handling system with four separate drum suction hoses.
		Hands free rinsing, mixing and measuring cylinder
CONTROL PANEL		High / low pressure 6-way regulating manifold Kerbside outlet for knapsack filling Kerbside tank fill
HOSE REEL	Single or Twin (100m / 150m)	Buddy Smart Reel – 12/24V auto rewind hose reel with My-Pace multiple speed remote, overrun protection, low voltage cut-out, 20A max limit
FILTER	Suction Filter	1 1/4" suction filter with 25mm hoesetails and 32 mesh screen filter, shut-off piston enables ease of cleaning
SAFETY FEATURE		Emergency Stop and Battery Isolator

PRODUCT FEATURE

ELECTRICALLY ACTUATED ROADSIDE BOOM	1.5m impact resistant poly boom arm with breakaway Electric lowering and raising via in-cab controls Two x swivel nozzle bodies with calibration matched nozzles for behind guard rails and 3m off the tip. OPTIONAL: Removable double nozzle shroud with folding dropper mechanism mounted on quick attach pins.
UNDER TRAY ADJUSTABLE NOZZLE KIT	Three swivel bodies with individual ball valves for maximum adjustment with single solenoi in-cab control. One nozzle tip calibration matched to road-side boom.
TRAFFIC CONE HOLDER	Galvanised traffic cone spike with top latch to prevent cones jumping off.
FLASHING BEACONS	Two top mount LED amber beacons mounted on locker boxes.
LED SIGN BOARDS	Options of compact to large LED sign boards.
SECONDARY TANK	Secondary fresh water tank with secondary control panel with transfer system with metering. Avaliable in variety of sizes depending on vehicle GVM and space allowance (trucks only).