



OWL



Accelerates Towards a Greener Tomorrow

2 & 3 Wheeler charging solution by **goEgo**



Housing Society



Workspaces



Commercial & Retail



OCPP Certified CSMS Platform



Robin



Albatross



#startupindia



Explore the easiest charging experience with **goME** app



Impactware Technology Solutions Pvt.Ltd.

goEgo : Mfg Unit: Plot No. 36, Sector No. 05, Auric City, MIDC Industrial Area, Shendra, Chh. Sambhajinagar, 431154, Maharashtra, India

goEgo : Registered office : C/o SSCo, Office number 16, 1184/4, Gokul Nagar, FC Road, Dnyaneshwar Paduka Chowk, Shivaji Nagar, Pune 411005

www.goego.in

sales@goegonetwork.com

Sales: (+91)7066710101, Customer Care(+91)8956887475



TECHNICAL INFORMATION

PARAMETER	SPECIFICATION		SPECIFICATION
Model Series	OWL	ROBIN	ALBATROSS
Model Number	GEG-OWLA-1K1-BAC-3S-C	GEG-ROBA-3K3-BAC-1S-C	GEG-ALBA-3K3-BAC-3S-C
INPUT			
Input Supply	Single phase 180 - 264V AC @ 15A	Single phase 180 - 264V AC @ 15A	3 Phase 400-415V AC @ 15A
Input Frequency	45~65 Hz	45~65 Hz	45~65 Hz
Input Wires	3 wires- L, N, PE	3 wires- L, N, PE	5 wires - 3P, N , PE
OUTPUT			
No. Output Connector	3 Sockets	1 Socket	3 Sockets
Power Output	1.1kW Max. per output	3.3kW Max. per output	3.3kW Max. per output
Output Connector Type	IEC 60309 / Residential Socket	IEC 60309 / Residential Socket	IEC 60309 / Residential Socket
USER INTERFACE			
Display	20 X 4 character LCD / 4.3"TFT Display(Optional)	20 X 4 character LCD / 4.3"TFT Display(Optional)	20 X 4 - character LCD
SIM Slot	Nano size SIM card for GSM connectivity	Nano size SIM card for GSM connectivity	Nano size SIM card for GSM connectivity
Push Button	Push button for Start /Stop session for each socket	Push button for Start /Stop session	Push button for Start /Stop session for each socket
LED Indication	1 Multicolor LED indication for charging status	Multicolor LED indication for charging status	Multicolor LED indication for charging status
COMMUNICATION			
EVSE to Server	OCPP 1.6	OCPP 1.6	OCPP 1.6
Cloud Connectivity	Wi-Fi, 3G/4G	Wi-Fi, 3G/4G	Wi-Fi, 3G/4G
User Authentication	RFID Enabled, Mobile App(goME)	RFID Enabled, Mobile App(goME)	RFID Enabled, Mobile App(goME)
SAFETY AND PROTECTION			
Safety Measures	Emergency Stop Button	Emergency Stop Button	Emergency Stop Button
Protection	Over voltage, under voltage, over current, short circuit, surge protection, over temperature, ground fault, residual current	Over voltage, under voltage, over current, short circuit, surge protection, over temperature, ground fault, residual current	Over voltage, under voltage, over current, short circuit, surge protection, over temperature, ground fault, residual current
MCB current breaking rating	25A for a 16 Amp rated charger	25A for a 16 Amp rated charger	25A for a 16 Amp rated charger
Earth (ground) fault protection	Leakage current < 30mA	Leakage current < 30mA	Leakage current < 30mA
ENVIRONMENTAL			
Operating Temperature	0°C to + 55°C	5°C to + 55°C	5°C to + 55°C
Operating Humidity	5 to 95 % relative humidity, non-condensing	5 to 95 % relative humidity, non-condensing	5 to 95 % relative humidity, non-condensing
MECHANICAL			
Dimensions	(H x W x D) 515 x 340 x 180 mm	(H x W x D) 515 x 340 x 180 mm	(H x W x D) 515 x 340 x 180 mm
Material	Plastic	Plastic	Plastic
Cooling	Natural Air Cooled	Natural Air Cooled	Natural Air Cooled
Net Weight	4 Kg	3 Kg	9 Kg
Mounting Type	Wall Mount, Pole Mount	Wall Mount, Pole Mount	Wall Mount, Pole Mount
IP rating	IP 65	IP 65	IP 65
COMPLIANCE & CERTIFICATION			
Standard	LEV AC IS17017-22-1	LEV AC IS17017-22-1	AIS 138-1
Certification	ARAI	ARAI	ARAI