



Powering Green Rides, Effortlessly

4 wheeler ev charging solution by goEgo



Housing
Society



Workspaces



Commercial
& Retail



Eagle



Falcon



Eagle Dual Gun



Explore the easiest charging experience with goME app



#startupindia



Impactware Technology Solutions Pvt.Ltd.

goEgo : Mfg Unit: Plot No. 36, Sector No. 05, Auric City, MIDC Industrial Area, Shendra, Chh. Sambhajinagar, 431154, Maharashtra, India

goEgo : Registered office : C/o SSCO, Office number 16, 1184/4, Gokul Nagar, FC Road, Dnyaneshwar Paduka Chowk, Shivaji Nagar, Pune 411005

www.goego.in

sales@goegonetwork.com

Sales: (+91)7066710101, Customer Care(+91)8956887475



TECHNICAL INFORMATION				
PARAMETER	SPECIFICATION		SPECIFICATION	
Model Series	EAGLE	EAGLE DUAL GUN	Falcon 11	Falcon 22
Model Number	GEG-ELLA-7K4-TYP2-1C-C	GEG-ELLA-7K4-TYP2-2C-C	GEG-FALA-11K-TYP2-IC-C	GEG-FALA-22K-TYP2-IC-C
INPUT				
Input Supply	1 phase input, 180-264V AC @ 32A each phase	3 phase input, 400-415V AC @ 64A each phase	3 phase input, 400-415V AC @ 16A each phase	3 phase input, 400-415V AC @ 32A each phase
Input Frequency	45~65 Hz	45~65 Hz	45~65 Hz	45~65 Hz
Input Wires	3 wires- L, N, PE	5 wires- L1, L2, L3, N, PE	5 wires- L1, L2, L3, N, PE	5 wires- L1, L2, L3, N, PE
OUTPUT				
No. Output Connector	1 Cable (cable length 5 Meter)	2 Cable (cable length 5 Meter)	1 Cable (cable length 5 Meter)	1 Cable (cable length 5 Meter)
Power Output	32A / 7.4kW Max. per output	32A / 7.4kW Max. per output	11kW Max. per output	22kW Max. per output
Output Connector Type	Type - 2 IEC 62196	Type - 2 IEC 62196	Type - 2 IEC 62196	Type - 2 IEC 62196
Dynamic Load Balancing	Compatible over OCPP	Compatible over OCPP	Compatible over OCPP	Compatible over OCPP
USER INTERFACE				
Display	20 X 4 character LCD / 4.3"TFT LCD(Optional)	20 × 4 character LCD	20 x 4 - character LCD/4.3"TFT LCD(Optional)	20 x 4 - character LCD/4.3"TFT LCD(Optional)
SIM Slot	Nano size SIM card for GSM connectivity	General size M to M SIM card for GSM connectivity	Nano size SIM card for GSM connectivity	Nano size SIM card for GSM connectivity
LED Indication	1 Multicolor LED indication for charging status	1 Multicolor LED indication for charging status	1 Multicolor LED indication for charging status	1 Multicolor LED indication for charging status
COMMUNICATION				
EVSE to Server	OCPP 1.6	OCPP 1.6	OCPP 1.6	OCPP 1.6
Cloud Connectivity	Wi-Fi, 3G/4G	Wi-Fi, 3G/4G	Wi-Fi, 3G/4G	Wi-Fi, 3G/4G
User Authentication	RFID Enabled, Mobile App(goME)	RFID Enabled, Mobile App(goME)	RFID Enabled, Mobile App(goME)	RFID Enabled, Mobile App(goME)
SAFETY AND PROTECTION				
Safety Measures	Emergency Stop Button	Emergency Stop Button	Emergency Stop Button	Emergency Stop Button
Protection	Over voltage, under voltage, over current, short circuit, surge protection, over temperature, ground fault, residual current protection	Over voltage, under voltage, over current, short circuit, surge protection, over temperature, ground fault, residual current protection	Over voltage, under voltage, over current, short circuit, surge protection, over temperature, ground fault, residual current protection	Over voltage, under voltage, over current, short circuit, surge protection, over temperature, ground fault, residual current protection
Earth (ground) fault protection	Leakage current < 30mA	Leakage current < 30mA(for AC)	Leakage current < 30mA(for AC)	Leakage current < 30mA(for AC)
ENVIRONMENTAL				
Operating Temperature	-25°C to + 55°C	0°C to + 55°C	0°C to + 55°C	0°C to + 55°C
Operating Humidity	5 to 95 % relative humidity, non-condensing	5 to 95 % relative humidity, non-condensing	5 to 95 % relative humidity, non-condensing	5 to 95 % relative humidity, non-condensing
MECHANICAL				
Dimensions	(H x W x D) 515 x 340 x 170 mm	(H x W x D) 690 x 435 x 215 mm	(H x W x D) 515 x 340 x 170 mm	(H x W x D) 515 x 340 x 170 mm
Material	Plastic	MS-CRCA	Plastic	Plastic
Cooling	Natural Air Cooled	Natural Air Cooled	Natural Air Cooled	Natural Air Cooled
Net Weight	6 Kg	14Kg	7 Kg	8 Kg
Mounting Type	Wall Mount, Pole Mount	Wall Mount, Pole Mount	Wall / Pole mount	Wall / Pole mount
IP rating	IP 65	IP 54	IP 65	IP 65
COMPLIANCE & CERTIFICATION				
Standard	IEC 61851-1/IS17017 (Type 2 AC)	IEC 61851-1/IS 17017	IEC 61851-1/IS17017 (Type 2 AC)	IEC 61851-1/IS17017 (Type 2 AC)
Certification	ARAI	ARAI	ARAI	ARAI