

RealScan-FC

Compact Palm & Tenprint Enrollment Scanner




RealScan-FC is an all-in-one palmprint live scanner for capturing various types of fingerprint and palmprint including flats, rolls, palms and writer's palms. Featuring Xperix's cutting-edge optical & biometric technologies, it is capable of capturing the highest quality images regardless of the physical condition of fingers. RealScan-FC also supports user convenient features like voice instruction, foot switch and mobile power supply. With proven reliability of FBI certification, RealScan-FC is designed to provide perfect live scanning solution for various criminal ID applications.

xperix

RealScan-FC

Compact Palm & Tenprint Enrollment Scanner



Hardware Features

- Compact & light weight palm-print scanner
- Embedded DSP for high-speed image processing
- Extra wide active image area for easy capturing
- Built-in speaker for sound & voice instruction
- High speed USB 2.0 interface
- Mobile operation through car power supply
- FBI IQS Appendix F / Appendix P Standards compliance
- DC12V or USB Power Only

Software Features

- Image quality check
- Sequence check in rolls and slaps acquisition
- Automatic segmentation of four finger slaps
- Slippage detection for flats and rolls
- Automatic capturing
- Ghost image elimination
- SDK for quick and easy integration into any systems

Specifications

- Scan function 4-finger combined print and palms under fingers up to 5 "x 5" - Rotated fingerprints up to 1.6 "x 1.6"
- Full palmpoint up to 4.5 "x 3", rotated and flat fingerprints up to 5 "x 1.6", rotated fingerprint up to 1.6 "x 1.6" - 500 dpi

Fingerprint Types	Single rolls / single flats / dual-finger flats / four-finger slaps upper & lower palm-prints, writer's palm-prints
Resolution	500 dpi, 256 gray
Platen Size (W x L)	5.16" x 5.12"(131.2 x 130.2 mm)
Image Size (W x L)	Palm Prints : 2500 x 2500 Four Finger Slap : 1600 x 1500 Single Flats / Rolls : 800 x 750
Image Format	ANSI / NIST-ITL 1-2007 / 2011 ISO / IEC FCD 19794-4 ANSI / NIST-ITL 1-2000 ANSI / NIST-ITL 1-2000 Interpol Implementation
Maximum Capture Area	2500 x 2500
Image Quality Standards	FBI IQS Appendix F / Appendix P
Ingress Protection	IP64 (Sealed between bezel and sensor surface)
Operating Temperature	0°C - 50°C
Operating Humidity	From 10 to 90%, non-condensing
Dimension (W x L x H)	7.6" x 12.4" x 5.9" (193 x 315 x 150mm (156mm, Foot Rubber Inclusive))
Power Supply	12VDC or USB Power
Weight	5.26kg
Interface	USB 3.2 Gen 1, USB-C
Operating Systems	Windows : Windows 8 or higher 32/64 bit Linux : Ubuntu, Debian, Fedora, Cent OS 32/64bit Android 5.0 or higher (Custom 4.0)
Certificate	FBI, WHQL, CE, FCC, UL, KC, WEEE, RoHS, REACH, BIS
Accessory	Foot Switch (Optional)



Xperix Inc.

#305~308, 3F, Building A, Tera Tower 2, 201 Songpa-daero, Songpa-gu, Seoul, Republic of Korea

T +82 1588 8817 E sales_id@xperix.com www.xperix.com



©Xperix Inc. Xperix and identifying product names and numbers herein are registered trade marks of Xperix Inc. All non-Xperix brands and product names are trademarks or registered trademarks of their respective companies. Product appearance, build status and/or specifications are subject to change without notice.