

BioMini Slim 2

Ultra-slim FAP20 Authentication Scanner



BioMini Slim 2 is FAP20 certified fingerprint scanner featuring an array of cutting-edge technologies. Along with its 13.5mm slim optical sensor, BioMini Slim 2 features Xperix's proprietary Multi-dynamic Range(M-DR) technology, FBI PIV and Mobile ID FAP20 compliance and Android device support. BioMini Slim 2 also provides developers more physical flexibility with its reduced form factor and the ultra-slim optical sensor ensures robust operation over time. BioMini Slim 2 provides advanced artificial Intelligence-based Live Finger Detection technology which is compliant with ISO 30107-3 PAD Level 1 & 2 Standard. Applying LFD technology, BioMini Slim 2 distinguishes fake fingerprints made from various materials including clay, rubber, silicon, glue, paper, film, and more.



BioMini Slim 2

Ultra-slim FAP20 Authentication Scanner

FEATURES



- World's slimmest FAP 20 optical sensor



- FBI PIV and FBI Mobile ID FAP20 certificates
- Image compression standard: WSQ



- Capturing high-quality fingerprint images even when the finger is dry & wet.
- Operates under direct sunlight up to 100,000 LUX



- Live Fingerprint Detection (LFD) Technology
 - ISO 30107-3 Compliant (PAD Level 1 & 2)
 - Distinguishes fake fingerprints made from various materials including clay, rubber, silicon, glue, paper, film and more



- Easy Integration
 - BioMini SDK for easy application development
 - Android, MS Windows & Linux compatible
 - Multi-threaded code design for multi-core CPU utilization



- No need to type in a password
- Instant login by touching your finger

SPECIFICATIONS

Sensor	Image Quality Standards	FBI PIV / FBI Mobile ID FAP20
	Live Finger Detection	O
	Sensor Type	Optical
	Resolution	500 ppi
	Image Grayscale	8-bit, 256 levels
	Platen Size (W x L)	16.5 mm x 21 mm
	Sensing Area (W x H)	15.2 mm x 20.3 mm
H/W	Image Size (W x H)	300 x 400 pixels
	Interface	USB 2.0 High Speed
	Sensor Surface	Optic Glass (Scratch free)
	Operating Temperature	From -10°C to 55°C
	Operating humidity	0% - 90%, non-condensing
	Ingress Protection	IP65 (Sealed between bezel and sensor surface)
S/W	Dimensions (W x L x H)	72.8 mm x 40.7 mm x 18.5 mm
	Weight	91g
	Windows	Windows 10 or higher 32/64bit
	Linux	Ubuntu, Debian, Fedora, OpenSUSE, CentOS 32/64bit
	Android Android 5.0 or higher	O
	Image Format	RAW, BMP, WSQ, ISO 19794-4
	Template Type	Xperix, ISO 19794-2, ANSI-378
Certification	Live Finger Detection	ISO 30107-3 Complaint (PAD Level 1 & 2)
	FBI / Image Certifications	FBI, CE, FCC, KC, RoHS, CB, IEC 62471, WEEE, REACH, BIS, USB-IF, WHQL, PAD Level 1 & 2 by Bixelab



Xperix Inc.

#1207, 37, Sagimakgol-ro 62beon-gil, Jungwon-gu, Seongnam-si, Gyeonggi-do, 13211, Republic of Korea

Inquiry: sales_id@xperix.com | www.xperix.com

©2026 Xperix Inc. Xperix and identifying product names and numbers herein are registered trade marks of Xperix Inc. All non-Xperix brands and product names are trademarks or registered trademarks of their respective companies. Product appearance, build status and/or specifications are subject to change without notice. [XPX_BMS2_PB_REV06_EN_260814]