

FHD-235

FibroPool® MEA

SWIMMING POOL HEAT PUMP



Designed and engineered
in the USA

WWW.FIBROPOOL.COM
WWW.FIBROPOOL.AE

MODEL:FHD-235	
Heating Capacity	8.0kW
(A24°C/W26°C)	27300 BTU/h
COP	5.5
Input Power	2.29kw
Input Current	8.3A
Cooling Capacity	6.0kW
(A43°C/W30°C)	20500 BTU/h
COP	3.0
Input Power	2.0kW
Input Current	9.09A
Power Supply	220VAC/1PH/50Hz
Compressor	Rotary
Air Direction	Horizontal
Water Inlet/Outlet	1_1/2"
Rated Water Flow	2.42m³/h
Water Pressure Drop	16kpa
Refrigerant Type	R410A/900g
Max. Discharge Pressure	4.2MPa
Max.Suction Presure	1.5MPa
Water Proof Class	IPX4
Electric Insulation Class	I
Net Dimension(LxW×H)	1012×347×615
Net Weight	60Kg
Noise	48dB(A)
Air Temperature Range	5°C-50°C

● **Note**

(1)Heating: Outdoor air temperature:24°C/19°C, Outlet water Temperature:26°C
Cooling:Outdoor air temperature:43°C, Outlet water temperature:30°C, Input water temperature:32°C.

Features and Benefits of FibroPool FHD Heat Pumps

1. Eco-Friendly and Cost-Effective Heating and Cooling

- **Advanced Refrigerant R410a:** Uses an environmentally friendly refrigerant to reduce carbon footprint and harmful gas emissions.
- **Hydrophilic Aluminum Foil Evaporator:** Enhances efficiency and durability.
- **Electric Expansion Valve:** Ensures optimal performance.
- **Harnessing Nature's Energy:** Transfers free energy from outside air to your pool, reducing heating costs by over 80%.
- **High Coefficient of Performance (COP):** Delivers a COP of over 5x, significantly more efficient than natural gas heating at only 80%.
- **Comprehensive Warranty:** 5 years for the compressor, 3 years for the heat exchanger, and 1 year for the heat pump body and other parts against manufacturing defects.

2. "IceMelt" Technology

- **Extended Swimming Season:** Operates in a wide range of temperatures from -5°C to +55°C.
- **Efficient in Freezing Conditions:** Continues to heat even in sub-zero temperatures, minimizing heat loss.
- **Versatile Temperature Control:** Heats or cools pool water to your desired refreshing temperature.
- **Auto-Defrost Feature:** Prevents ice buildup for uninterrupted operation.
- **Auto Mode Operation:** Set it and forget it for hassle-free use.

3. Durable and Efficient Heat Exchange System

- **High-Quality Titanium Pipe:** Spiral-threaded GR1 titanium pipe heat exchanger resists chemical corrosion and enhances durability.
- **Fast and Efficient Heating:** Heats water quickly and efficiently with 19mm diameter and 1.0mm wall thickness copper piping.
- **Longevity:** Designed to provide long-lasting performance without sacrificing efficiency.

4. User-Friendly Control Unit

- **Digital Display:** Bright, accurate, and easy-to-read display.
- **Convenient Settings:** Timer and temperature settings for customized operation.
- **Self-Diagnostics:** On-board diagnostics with error code display for easy troubleshooting.

5. Comprehensive Safety and Functionality

- **Dual Functionality:** Offers both heating and cooling functions.
- **Automated Operation:** Features auto operation, restart, and defrost for minimal user intervention.
- **Safety Protections:** Includes protections against insufficient water flow, high/low pressure, overload, and more.
- **Temperature Monitoring:** Measures inlet and outlet water temperatures for precise control.

6. Easy Installation

- Optimized Design: Simplified electrical wiring and hydraulic connections for quick setup.
- Cost-Effective: Saves time and reduces installation costs with its efficient design.

7. Ultra-Quiet Operation

- Noise-Absorbing Structure: Built with noise-resistant insulation foam.
- Anti-Vibration Features: Includes anti-vibration rubber feet for quieter operation.
- Specialized Fan Design: Equipped with a specially designed fan and PI bearing for reduced noise and increased lifespan.

FibroPool® MEA

WWW.FIBROPOOL.COM



WWW.FIBROPOOL.AE



Designed and engineered in the USA

We reserve the right to change all or part of the features of the articles or contents of this document, with out prior notice.