



CORVO V

A SNIPER RIFLE, IN .50 BMG.

We've designed Corvo to have more control over the extreme power, holding our accuracy flag high. To give you an idea, think about the accuracy of a sniper firearm system together with the energy of a .50 BMG caliber.

 **VICTRIX**
A R M A M E N T S

Destination use

Law Enforcement
Military

Caliber / Twist rate

.50 BMG (12,7x99) (1/15)

Barrel length

27"

Weight

13.2 kg (29.10 lb) with an empty magazine, muzzle brake, fluted barrel length 27" and no scope

Dimension

Closed overall length: 1175 mm (46.25")

Open overall length: 1420 mm (55.90")

With muzzle brake and fluted barrel length 27"

Base rifle

Lapped and fluted match-grade rifled barrel in AISI 420

Barrel muzzle thread M24x1mm

Buttstock with horizontal and vertical multiple lever adjustments, a retractable monopod with quick positioning adjustment and fine adjustment, and an insulated cheek piece

Single feed and single stack 5-round magazine

Reversible EVO button folding system

Octagonal elliptic forend with M-LOK® system, a 45 MoA integrated monobloc top rail and an integrated monobloc rail for mounting a bipod according to STANAG 4694/Mil std 1913

Ergonomic and interchangeable zero angle flat top grip for standard AR platform

45 MoA action rail according to STANAG 4694/Mil std 1913

Detachable multifunction carry handle with quick mount:

- with QM (Quick mount) attachment for picatinny rail
- ergonomic handle
- integrated picatinny rail
- hook for rope attachment
- QD (Quick detach) attachments
- tripod attachment with 1/4" – 20 UNC and 3/8" – 16 UNC threads
- front magnetic bit holder for field maintenance

Victrix ProAngle detachable muzzle brake featuring 4 forward-canted chambers

Action in AISI 420 worked out from billet through milling and turning with finish on grinding machinery. Bolt with 3 symmetric lugs: first lug at the bottom of the cylinder in vertical position (at 6 o'clock), two side lugs arranged at an angle of 120 degree, dirt/ice grooves integral

PVD finish on the action and on the bolt

Victrix Professional Plus trigger with three positions top safety: standard setting approx. 1000 gr (35.27 oz)

Explorer Cases case for transport with military specifications cod. 15416 with custom cut interior

Cleaning and tool kit with cordura pouch

Nr. 1 additional single feed and single stack 5-round magazine

Tactical sling and QD (Quick Detach) sling rings

ROME Caliga bipod

User manual and welcome kit

Stock colour

Every and each component made of light alloy undergoes a hard black anodising
CERAKOTE ceramic polymer firearm coatings available in three colours:


Dark Grey

Dark Olive Drab Green

Medium Flat Brown

Optional

Side picatinny rails for forend with M-LOK® system according to STANAG 4694/Mil std 1913



VICTRIX
PROFESSIONAL