




PWR LIGHTING

PWRBLOX PIXELDOT FLUSH DATASHEET



www.pwr-lighting.com

GENERAL


Product name	The PWR Blox Pixeldot Flush
Order PN	PWR-BLX-DOT-FLUSH-6000 PWR-BLX-DOT-FLUSH-2700
Description	Pixelcontrollable mini dot for mounting in-& outdoor with RGBW LED Light source.

ELECTRICAL

Light Source	RGBW/2700K or 6000K
Expected average LED lifetime	50,000~70,000 hours at 70% lumen maintenance at 25 °C
Power	54lm @RGBW Full 2W max. 24Vdc 0,09A
Certification	IP65, C E, RoHS

CONTROLLER

PWR PIXELBLOX	PWR-BLX-CTRL8
Description	SPI protocol, UCS8904 with integrated sender/receiver for stable data transfer over long distance 100% compatible with all fixtures off the PWR BLOX series



CONNECTIVITY

Connector

Input: 30cm lead cable with IP65 XLR4 Pin male connector
Output: 30cm lead cable with IP65 XLR4 Pin female connector

MECHANICAL

Housing

Powerder coated dia-casting aluminum in black finish

Dimensions

50 (Dia.) x 48 (H) mm

Weight

0,20kg

Operating temperature

-20 °C ~ +50 °C

Storage temperature

-20 °C ~ +70 °C

Mounting & positioning

Screw holes & tie-wrap recesses

ACCESSORIES


Diffusers

Dome
> Contact us for customization

FIXTURE CONTROL

DMX channels

4ch



PWRBLOX PIXELDOT FLUSH DATASHEET

