




PWR LIGHTING

PWRBLOX PIXELDOT STRING DATASHEET



www.pwr-lighting.com



PWRBLOX PIXELDOT STRING DATASHEET

GENERAL


Product name	The PWR Blox Pixeldot String
Order PN	PWR-PB-DOTSTRING-6000 PWR-PB-DOTSTRING-2700
Description	Pixelcontrollable mini dotstring for in-& outdoor use with RGBW LED Lightsource. Tool free interchangeable diffusers

ELECTRICAL

Light Source	RGBW/2700K or 6000K
Expected average LED lifetime	50,000~70,000 hours at 70% lumen maintenance at 25 °C
Power	216lm @RGBW Full 8W max. 24Vdc 0,36A
Certification	IP65, C E, RoHS

CONTROLLER

PWR PIXELBLOX	PWR-BLX-CTRL8
Description	SPI protocol, UCS8904 with integrated sender/receiver for stable data transfer over long distance 100% compatible with all fixtures off the PWR BLOX series





PWRBLOX PIXELDOT STRING DATASHEET

CONNECTIVITY

Connector

Input: IP65 XLR4 Pin male connector
Output: IP65 XLR4 Pin female connector

MECHANICAL

Housing

Powerder coated dia-casting aluminum in black finish

Dimensions

60 x 32 x 22 mm (per pixel)

Weight

0,16kg/dot

Operating temperature

-20 °C ~ +50 °C

Storage temperature

-20 °C ~ +70 °C

Mounting & positioning

Screwing holes & tie wrap recesses

ACCESSORIES

Diffusers with internal screw thread

Teardrop
Dome
Flat




Contact us for customization

FIXTURE CONTROL

DMX channels

4ch





PWRBLOX PIXELDOT STRING DATASHEET

