



Marine Safety Center Vapor Control System (VCS) Plan Review Information Sheet (PRIS)



Vessel Name	0	Shipyard	Jeffboat
Official Number	0	Hull Number	02-2967 & 02-2968

1. This sheet consolidates critical VCS parameters for MSC Staff Engineers and CG Field Inspectors dealing with Vapor Control Systems. CG Inspectors should verify the vessel's VCS design is consistent with the information listed in boxes 2, 6, 7 & 8 prior to updating the vapor control endorsement on the vessel's Certificate of Inspection. For cases where the information in the VCS PRIS does not reflect the vessel's design the CG Inspector should contact the MSC's Cargo Authority branch.

2. Tank Maximum Design Working Pressure psig Raised Trunk
Flush Deck

3. Authorized Maximum Cargo Transfer Rate bbl/hr

4. Authorized Maximum Cargo Density lbm/ft³

5. Authorized VCS Categories

6. Cargoes with the highest vapor density and/or pressure drop:
 a. Cargo Name Dodecylbenzene
 b. Cargo Name Gasoline

7. Pressure Vacuum Valve:		8. VCS Pipe Sizes:	
Manufacturer <input type="text" value="BERGAN KLPH-6"/>	Settings in psig:	Approx. Inside Diameter	
Size <input type="text" value="6 Inch"/>	Pressure-side <input type="text" value="3.0"/>	Longitudinal Header (inches)	<input type="text" value="8"/>
CG Approval <input type="text" value="Yes"/>	Vacuum-side <input type="text" value="0.5"/>	Transverse Header (Inches)	<input type="text" value="8"/>
Required Venting Capacity of Pressure-Side of P/V valve		<input type="text" value="9045"/>	<input type="text" value="bbl/hr (air)"/>
Required Venting Capacity of Vacuum-Side of P/V valve		<input type="text" value="4285"/>	<input type="text" value="bbl/hr (air)"/>

9. Tank Overfill Protection System (check appropriate box or boxes)

a. High Level/Tank Overfill Alarm	<input checked="" type="checkbox"/>	Type	<input type="text" value="0"/>
b. Overfill Control Shutdown	<input checked="" type="checkbox"/>	Type	<input type="text" value="0"/>
c. Spill Valve	<input type="checkbox"/>	Type	<input type="text" value="0"/>
d. Rupture Disk	<input type="checkbox"/>	Type	<input type="text" value="0"/>

Meets ASTM F1271 Setting in psig

10. Closed Gauging Verify the vessel has closed gauging that satisfies 46 CFR 39.20-3 and 151.15-10(c).

11. Instructions/Guidelines for the OCMI:

11a. The following is the Marine Safety Center's recommended COI endorsement
 "Only those cargoes named in the vessel's Cargo Authority Attachment, Serial #C2-0300544, dated 22Apr2003, may be carried and then only in the tanks indicated. In accordance with 46 CFR Part 39, excluding part 39.40, this vessel's vapor control system has been inspected to the plans approved by Marine Safety Center letters Serial #: E2-0304361 dated 18Mar2003 and C2-0300544, dated 22Apr2003, and found acceptable for collection of bulk liquid cargo vapors annotated with "Yes" in the CAA's VCS column."

11b. The Marine Safety Center approval letter/s must be available at the OCMI's request.

11c. Verify isolation valve at the vapor connection flange is manually operable and designed in a way it is "clearly" open or closed.

11d. Previous applicable VCS approval letters:

VCS Approval Letter

MSC Plan Reviewer

**CBC 132 and CBC 133
02-2967 and 02-2968
4,285 BBL/HR MAX TRANSFER RATE**

