



BARGE "CBC 383"

INNAGE TRIM TABLE

	1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.	
	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>
1 PORT	00-0/8	- 00-0/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-2/8	- 00-2/8	00-1/4	- 00-1/4	00-1/4	- 00-1/4
1 STBD	00-0/8	- 00-0/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-2/8	- 00-2/8	00-1/4	- 00-1/4	00-1/4	- 00-1/4
2 PORT	00-0/8	- 00-0/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/4	- 00-1/4	00-1/4	- 00-1/4	00-1/4	- 00-1/4
2 STBD	00-0/8	- 00-0/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/4	- 00-1/4	00-1/4	- 00-1/4	00-1/4	- 00-1/4
3 PORT	- 00-1/2	00-1/2	- 01-1/8	01-1/8	- 01-5/8	01-5/8	- 02-1/4	02-1/4	- 02-3/4	02-3/4	- 03-3/8	03-3/8
3 STBD	- 00-1/2	00-1/2	- 01-1/8	01-1/8	- 01-5/8	01-5/8	- 02-1/4	02-1/4	- 02-3/4	02-3/4	- 03-3/8	03-3/8

(ALL MEASUREMENTS ABOVE ARE IN INCHES)

EXAMPLE FOR ABOVE TRIM CORRECTIONS:

FWD. DRAFT = 4'-00"
 AFT DRAFT = 6'-00"
 DIFF. = 2'-00" (DOWN BY STERN)

THE CORRECTION FOR 2'-00" TRIM DOWN BY STERN FOR 1 PORT IS - 00-1/8"
 FOR A MEASURED INNAGE GAUGE OF 4'-00" ON 1 PORT, THE TRIM CORRECTED INNAGE IS 3'-11 7/8"

LENGTH BETWEEN DRAFT MARKS: 253'-09"

May 17, 2013

PRECISION MEASUREMENT
 & ANALYSIS, INC.
 P.O. Box 2092
 Pearland, Texas 77588

<http://www.pmacorp.net>



BARGE "CBC 383"

ULLAGE TRIM TABLE

	1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.	
	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>
1 PORT	- 00-0/8	00-0/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-2/8	00-2/8	- 00-1/4	00-1/4	- 00-1/4	00-1/4
1 STBD	- 00-0/8	00-0/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-2/8	00-2/8	- 00-1/4	00-1/4	- 00-1/4	00-1/4
2 PORT	- 00-0/8	00-0/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/4	00-1/4	- 00-1/4	00-1/4	- 00-1/4	00-1/4
2 STBD	- 00-0/8	00-0/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/4	00-1/4	- 00-1/4	00-1/4	- 00-1/4	00-1/4
3 PORT	00-1/2	- 00-1/2	01-1/8	- 01-1/8	01-5/8	- 01-5/8	02-1/4	- 02-1/4	02-3/4	- 02-3/4	03-3/8	- 03-3/8
3 STBD	00-1/2	- 00-1/2	01-1/8	- 01-1/8	01-5/8	- 01-5/8	02-1/4	- 02-1/4	02-3/4	- 02-3/4	03-3/8	- 03-3/8

(ALL MEASUREMENTS ABOVE ARE IN INCHES)

EXAMPLE FOR ABOVE TRIM CORRECTIONS:

FWD. DRAFT = 4'-00"
 AFT DRAFT = 6'-00"
 DIFF. = 2'-00" (DOWN BY STERN)

THE CORRECTION FOR 2'-00" TRIM DOWN BY STERN FOR 1 PORT IS 00-1/8"
 FOR A MEASURED ULLAGE GAUGE OF 4'-00" ON 1 PORT, THE TRIM CORRECTED ULLAGE IS 4'-00 1/8"

LENGTH BETWEEN DRAFT MARKS: 253'-09"

May 17, 2013

PRECISION MEASUREMENT
 & ANALYSIS, INC.
 P.O. Box 2092
 Pearland, Texas 77588

<http://www.pmacorp.net>

