

OUTAGE TABLE

1 PORT

HULL NO. 4319

[illegible]

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

INSPECTORATE AMERICA CORPORATION



ISO 9002 ACCREDITED

BARGE "7029"
CONOCO, INC.
OUTAGE TABLE

TANK NO.
2 PORT OR STAR.

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4319

[illegible]

- CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 17'-3 1/4" (RIM OF MANWAY HATCH OPPOSITE HINGE)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION

INSPECTORATE
ISO 9002 ACCREDITED

BARGE "7029"
CONOCO, INC.
OUTAGE TABLE.

TANK NO.
3 PORT OR STAR.

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4319

0 FT.	1 FT.	2 FT.	3 FT.	4 FT.	5 FT.	6 FT.	7 FT.	8 FT.	9 FT.	10 FT.	11 FT.	12 FT.	13 FT.	14 FT.	15 FT.	16 FT.	17 FT.
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3
4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5
6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6
7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7
8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8
9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9
10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10
11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11
12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12
13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13
14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14
15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15
16	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16
17	17	17	17	17	17	17	17	17	17	17	17	17	17	17	17	17	17
18	18	18	18	18	18	18	18	18	18	18	18	18	18	18	18	18	18
19	19	19	19	19	19	19	19	19	19	19	19	19	19	19	19	19	19
20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20
21	21	21	21	21	21	21	21	21	21	21	21	21	21	21	21	21	21
22	22	22	22	22	22	22	22	22	22	22	22	22	22	22	22	22	22
23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23
24	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24
25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25
26	26	26	26	26	26	26	26	26	26	26	26	26	26	26	26	26	26
27	27	27	27	27	27	27	27	27	27	27	27	27	27	27	27	27	27
28	28	28	28	28	28	28	28	28	28	28	28	28	28	28	28	28	28
29	29	29	29	29	29	29	29	29	29	29	29	29	29	29	29	29	29
30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30
31	31	31	31	31													

- CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 17'3 1/2" (RIM OF MANWAY HATCH OPPOSITE HINGE)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

INSPECTORATE AMERICA CORPORATION



BARGE "7029"

CONOCO, INC.

HULL NO. 4319

CORRECTION TABLE FOR TRIM AFT.			
FOR INNAGE GAUGES ONLY			
TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	(-) 0' - 1"	(-) 0' - 1"	(+) 0' - 1"
1'-0"	(-) 0' - 2"	(-) 0' - 2"	(+) 0' - 2"
1'-6"	(-) 0' - 3"	(-) 0' - 2 7/8"	(+) 0' - 3"
2'-0"	(-) 0' - 4"	(-) 0' - 3 7/8"	(+) 0' - 4"
2'-6"	(-) 0' - 5"	(-) 0' - 4 7/8"	(+) 0' - 5"
3'-0"	(-) 0' - 5 7/8"	(-) 0' - 5 7/8"	(+) 0' - 6 1/8"
3'-6"	(-) 0' - 6 7/8"	(-) 0' - 6 7/8"	(+) 0' - 7 1/8"
4'-0"	(-) 0' - 7 7/8"	(-) 0' - 7 7/8"	(+) 0' - 8 1/8"
4'-6"	(-) 0' - 8 7/8"	(-) 0' - 8 7/8"	(+) 0' - 9 1/8"
5'-0"	(-) 0' - 9 7/8"	(-) 0' - 9 3/4"	(+) 0' - 10 1/8"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 9/17/98 BY: 

INSPECTORATE AMERICA CORPORATION