



BARGE "CBC-329"

CANAL BARGE COMPANY

HULL NO. 4327

CORRECTION TABLE FOR TRIM AFT.

FOR INNGAGE GAUGES ONLY

TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	(-) 0' - 1"	(-) 0' - 0 7/8"	(+) 0' - 0 7/8"
1'-0"	(-) 0' - 1 7/8"	(-) 0' - 1 7/8"	(+) 0' - 1 7/8"
1'-6"	(-) 0' - 2 7/8"	(-) 0' - 2 3/4"	(+) 0' - 2 7/8"
2'-0"	(-) 0' - 3 3/4"	(-) 0' - 3 5/8"	(+) 0' - 3 3/4"
2'-6"	(-) 0' - 4 3/4"	(-) 0' - 4 5/8"	(+) 0' - 4 3/4"
3'-0"	(-) 0' - 5 5/8"	(-) 0' - 5 1/2"	(+) 0' - 5 5/8"
3'-6"	(-) 0' - 6 5/8"	(-) 0' - 6 3/8"	(+) 0' - 6 5/8"
4'-0"	(-) 0' - 7 1/2"	(-) 0' - 7 3/8"	(+) 0' - 7 5/8"
4'-6"	(-) 0' - 8 1/2"	(-) 0' - 8 1/4"	(+) 0' - 8 1/2"
5'-0"	(-) 0' - 9 3/8"	(-) 0' - 9 1/8"	(+) 0' - 9 1/2"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED, TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 1/25/99

BY:


INSPECTORATE AMERICA CORPORATION



BARGE "CBC-329"
CANAL BARGE COMPANY
INNAGE TABLE

TANK NO.

1 PORT OR STAR.

HULL NO. 4327

Table with columns for measurement points (0 FT. to 14 FT.) and rows for various dimensions (W, L, H, etc.). Includes a note: 'BARGE SHOULD BE ON EVEN LEVEL, KEEL WHEN GAUGES ARE TAKEN'.

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-1" (RIM OF "D" DIAMETER HATCH)
LOCATED ON EXPANSION (TRUNK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

Signature

INSPECTORATE AMERICA CORPORATION

STAMPED: 1/25/99



BARGE "CBC-329"
CANAL BARGE COMPANY
INNAGE TABLE

TANK NO.
2 PORT OR STAR.

BARGE SHOULD BE ON EVEN KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4327

Table with columns for Gauge Height (0 FT. to 14 FT.), Capacity (M, W, R), and Capacity in US Gallons. Includes a 'CAPACITIES GREATER IN US GALLONS' section at the bottom.

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-0 3/4" (FROM 8" DIAMETER HATCH)
LOCATED ON EXPANSION TRUNK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

INSPECTORATE AMERICA CORPORATION
[Signature]

STRAPPED: 125099



ISO 9002 ACCREDITED

BARGE "CBC-329"
CANAL BARGE COMPANY
INNAGE TABLE

TANK NO.
3 PORT OR STAR.

HULL NO. 4327

Table with columns: N, O.F.T., M, 1.F.T., M, 2.F.T., M, 3.F.T., M, 4.F.T., M, 5.F.T., M, 6.F.T., M, 7.F.T., M, 8.F.T., M, 9.F.T., M, 10.F.T., M, 11.F.T., M, 12.F.T., M, 13.F.T., M, 14.F.T. Rows contain numerical data for each measurement point.

CAPACITY BELOW STRIKE POINT


REFERENCE GAUGE HEIGHT: 15'-0 1/2" (RIM OF 8" DIAMETER HATCH
LOCATED ON EXPANSION TRUNK)

STRAPPED: 12/5/98

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

[Signature]

INSPECTORATE AMERICA CORPORATION



BARGE "CBC-329"
CANAL BARGE COMPANY
OUTAGE TABLE

TANK NO.
1 PORT OR STAR.

BARGE SHOULD BE ON EVEN LEVEL KEEL WHEN GAUGES ARE TAKEN


HULL NO. 4327

Table with columns: M, N, O FT., N, 1 FT., N, 2 FT., N, 3 FT., N, 4 FT., N, 5 FT., N, 6 FT., N, 7 FT., N, 8 FT., N, 9 FT., N, 10 FT., N, 11 FT., N, 12 FT., N, 13 FT., N, 14 FT., N, 15 FT. Each column contains numerical data points for various gauges.

* CAPACITY BELOW STRIKE POINT
REFERENCE GAUGE HEIGHT : 15'-4" (RIM OF 6" DIAMETER HATCH
LOCATED ON EXPANSION TRUNKS)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION
[Signature]



BARGE "CBC-329"
CANAL BARGE COMPANY
OUTAGE TABLE

TANK NO.
2 PORT OR STAR.

BARGE SHOULD BE ON EVEN KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4327

Table with columns: M, 0 FT., 1 FT., 2 FT., 3 FT., 4 FT., 5 FT., 6 FT., 7 FT., 8 FT., 9 FT., 10 FT., 11 FT., 12 FT., 13 FT., 14 FT., 15 FT. Each column contains multiple rows of numerical data representing measurements at different heights.

REFERENCE GAUGE HEIGHT : 15'-0 3/4" (RIM OF 6" DIAMETER HATCH
LOCATED ON EXPANSION TRUNK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION
[Signature]

CAPACITIES GIVEN IN US GALLONS
CAPACITY BELOW STRIKE POINT



BARGE "CBC-329"
CANAL BARGE COMPANY
OUTAGE TABLE

TANK NO.
3 PORT OR STAR.

BARGE SHOULD BE ON EVEN LEVEL WHEN GAUGES ARE TAKEN

HULL NO. 4327

Table with columns: N, O, F.T., 1.F.T., 2.F.T., 3.F.T., 4.F.T., 5.F.T., 6.F.T., 7.F.T., 8.F.T., 9.F.T., 10.F.T., 11.F.T., 12.F.T., 13.F.T., 14.F.T., 15.F.T. and rows of numerical data representing measurements at various heights.

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-0" 1/2" (RIM OF 8" DIAMETER HATCH LOCATED ON EXPANSION TRUNK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION

STRAPPED: 1/25/99

CBC 329 Fuel Strapping Table

IN GALLONS

CBC 329-CBC 338

Feet Inches	0	1	2	3
0	0	3456	6912	10368
1	288	3744	7200	10656
2	576	4032	7488	10944
3	864	4320	7776	11232
4	1152	4608	8064	11520
5	1440	4896	8352	11808
6	1728	5184	8640	
7	2016	5472	8928	
8	2304	5760	9216	
9	2592	6048	9504	
10	2880	6336	9792	
11	3168	6624	10080	