

2.8 Wagon

FAT TRUCK[®]
INDUSTRIAL OFF-ROAD UTILITY VEHICLES



RufDiamond LTD.
62 Smelter Road
Coniston Ontario, Canada P0M 1M0
705-419-2653
info@rufdiamond.com
www.rufdiamond.com

2.8 Wagon

SPECIFICATIONS

PERFORMANCE		ENGINE		TIRES		OPTIONS
Payload	2200 lb (1000 kg)	Make	Caterpillar	Front & Rear	FAT TRUCK® LGP 1640 x 640 x 610	Custom color
Passengers capacity	8 (2 front + 6 rear)	Model	C2.2 Turbo diesel	Pressure	0.5 to 4.5 PSI (0.07 to 0.31BAR)	Front LED light bar
Maximum speed on land	25 mph (40 km/h)	Emission standards	EPA Tier 4 Final EU Stage V	Pressure control	Automatic pressure control	Rear LED Light bar
Maximum speed on water	3.1 mph (5 km/h)	Number of cylinders 4 cylinders Displacement 135 po³ (2.22 L) Horsepower @ 2800 RPM 74 hp (55 kW) Torque @ 1400 RPM 199 lb-ft (270 N-m) Cooling System Liquid cooled		FUEL SYSTEM		Side working LED lights front
Maximum uphill & downhill	35°/ 70%			Capacity	21 US Gal (80 L)	Side working LED lights rear
Maximum sidehill	22°/ 40%			Average fuel autonomy	12 h	4 corner LED beacon amber lights
Turning radius	0°			STANDARD EQUIPMENT		Search light
Shipping weight	5440 lb (2443 kg)			Doors	Lockable	Inclinometer with alarm
Ground pressure fully loaded	1.6 lb/po² (0.11 kg/cm²)		Operator seats	2 front seats with 3-points seat belts	Backup camera	
SAFETY FEATURES		ELECTRICAL		Lights	Front, brakes, position, flashers, dome	4-way backup camera
ROPS	ISO 3471	Voltage	12 V	Horn	Electric	Backup alarm
EPA	Stage V	Alternator capacity	275 A	Ingress	Front ladder with grab handles	Front mirrors
Brakes	Automatic safety brake	Battery capacity	960 CCA	Standard color	Red or white	Air conditioning
DIMENSIONS		Battery type	AGM	Fire extinguisher	2.5 lb ABC	35 000 BTU cab heater
Height	101 in (2565 mm)	TRANSMISSION		4 sliding side windows		Front feet heater
Length	146.5 in (3720 mm)	Type	Hydrostatic	Bilge pump		Fuel cab heater
Width	100 in (2540 mm)	Final drive	Carbon fiber synchronous belts	Cup holders		Ventilation Fans
Ground clearance	20.7 in (526 mm)	BRAKES		First aid kit		Fuel heater for engine water and transmission oil
CONTROLS		Brakes	Positive deceleration through hydrostatic transmission	Front and rear bumpers		110V heater cold engine water and transmission oil
Controller	Microprocessor	Parking brakes	Brake disc applied pressure released	Lockable fuel cap		Rear seats with 2 pts safety belts
Steering	Joystick			Operator & Maintenance manual		Rear seats with 3 pts safety belts
Display	Color display			Master cut-off switch		4-forward facing seats
WARRANTY				2x 12 V charging ports		Roof Rack with side ladder
Limited 1 year / 1000 hours (Which ever comes first)						Radio Bluetooth
						Rear hitch receiver
						Pintle hook
						Additional battery

