FT2 PICKUP





INDUSTRIAL OFF-ROAD UTILITY VEHICLES



WE'LL GET YOU THERE



62 Smelter Road Coniston, Ontario, P0M 1M0 705-4192653 | info@rufdiamond.com

www.rufdiamond.com

FT2 PICKUP





INDUSTRIAL OFF-ROAD UTILITY VEHICLES

SPECIFICATIONS

| PERFORMANCE | |
|------------------------------|--------------------------------------------|
| Payload on land | 2000 lb (905 kg) |
| Payload on water | 1500 lb (679 kg) |
| Passenger capacity | 4 (2 front + 2 rear) |
| Maximum speed on land | 20 mph (32 km/h) |
| Maximum speed on water | 3.1 mph (5 km/h) |
| Maximum uphill & downhill | 35°/70% |
| Maximum sidehill | 22°/ 40% |
| Turning radius | 0° |
| Base vehicle shipping weight | 4200 lb (1900 kg) |
| Ground pressure fully loaded | $2 \text{ lb/po}^2 (0.14 \text{ kg/cm}^2)$ |
| | |

| CVEETA | FEATURES |
|--------|-----------------|
| SALLII | FLAIUNLS |

| ROPS | ISO 3471 |
|----------------|------------------------|
| EPA / Emission | Tier 4 Final/Stage V |
| Brakes | Automatic safety brake |

DIMENSIONS

| Height with roof rack | 91.5 in (2323 mm) |
|------------------------------|-------------------|
| Height with air conditioning | 101 in (2562 mm) |
| Length | 129 in (3283 mm) |
| Width | 98 in (2489 mm) |
| Ground clearance | 18 in (457 mm) |

CONTROLS

| Controller | Microprocessor |
|------------|----------------|
| Steering | Joystick |
| Display | Color display |

WARRANTY

Limited 1 year / 1000 hours (Whichever comes first)





ENGINE HATZ Make 3H50TICD Model **Emission standards** EPA Tier 4 final EURO Stage V Number of cylinders 3 cylinders 89 po³ (1.46 L) Displacement Horsepower @ 2400 RPM 56 hp (42 kW) Torque @ 1600 RPM 136 lb-ft (184 N-m) Cooling system Liquid cooled **ELECTRICAL**

| Voltage | 12 V |
|---------------------|---------|
| Alternator capacity | 110 A |
| Battery capacity | 960 CCA |
| Battery type | AGM |
| | |

TRANSMISSION

Type

| BRAKES | |
|----------------|-----------------------|
| Brakes | Positive deceleration |
| | through hydrostatic |
| | transmission |
| Parking brakes | Brake disc applied, |

Hydrostatic

pressure released

TIRES

| Front & Rear | FAT TRUCK® LGP 52 x 24 x 20 in |
|--------------|---------------------------------------------------|
| Pressure | 0.5 to 6 PSI (0.0035 to 0.42 kg/cm ²) |

FUEL SYSTEM

Standard color: Black

| Capacity | 19.5 US Gal (74 L) |
|-----------------------|--------------------|
| Average fuel autonomy | 12 h |

STANDARD EQUIPMENT

| Statitual a Coloi. Diack |
|-----------------------------------------|
| Super Fat Tires ^{MD} |
| Front doors |
| Operator seats |
| Lights: Front, brakes, position, flashe |

ers, dome

Electric horn

Fire extinguisher 2.5 lb ABC 2 front seats with 3-point seat belts

Rear tailgate with ladder

Retractable front ladder and handles

Bilge pump First aid kit

Front and rear bumpers

Lockable fuel cap Cup holders

Operator & Maintenance manual

OPTIONS

Air conditioning Front winch Additional battery Rear hitch

Front and rear shackles

Studs for ice

Engine & hydraulic heater 110 V

Canopy with openable windows, dome light

Heater/Defroster

Extra heater

Front windshield with wiper

Custom color

Front roof rack

Rear roof rack

Rear vinyl canopy

Exterior mirrors

Back-up camera

Back-up alarm

4-Way camera system

Rear ROPS

Rear seats with safety belts

Directional light with remote control

Front, side and rear light LED bar

LED strobe light

Electronic inclinometer

Cold weather package

Ventilation fan

Storage box

Tow package

Wheel Pods™

Transportation trailer

Amphibious trailer





